



US009207046B1

(12) **United States Patent**  
**Warren**

(10) **Patent No.:** **US 9,207,046 B1**  
(45) **Date of Patent:** **Dec. 8, 2015**

(54) **REACTIVE ARMOR SYSTEM AND METHOD**

(71) Applicant: **ARMORDYNAMICS, INC.**, New York, NY (US)

(72) Inventor: **David Warren**, Stone Ridge, NY (US)

(73) Assignee: **Armor Dynamics, Inc.**, Stone Ridge, NY (US)

(\* ) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **13/753,853**

(22) Filed: **Jan. 30, 2013**

**Related U.S. Application Data**

(63) Continuation of application No. 13/237,691, filed on Sep. 20, 2011, now Pat. No. 8,387,512, which is a continuation of application No. 12/385,126, filed on Mar. 21, 2009, now Pat. No. 8,104,396, which is a continuation-in-part of application No. 11/979,309, filed on Nov. 1, 2007, now Pat. No. 7,628,104, and a continuation of application No. 11/296,402, filed on Dec. 8, 2005, now Pat. No. 7,383,761, said application No. 12/385,126 is a continuation of application No. 11/978,663, filed on Oct. 30, 2007, now Pat. No. 8,074,553, which is a continuation-in-part of application No. 11/296,402, filed on Dec. 8, 2005, now Pat. No. 7,383,761.

(60) Provisional application No. 61/064,851, filed on Mar. 31, 2008, provisional application No. 60/634,120, filed on Dec. 8, 2004, provisional application No. 60/689,531, filed on Jun. 13, 2005.

(51) **Int. Cl.**  
**F41H 5/007** (2006.01)

(52) **U.S. Cl.**  
CPC ..... **F41H 5/007** (2013.01)

(58) **Field of Classification Search**

CPC ..... F41H 5/007  
USPC ..... 89/36.17, 902  
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,806,509	A	9/1957	Bozzacco et al.	
3,427,139	A	2/1969	Gregory	
3,431,818	A	3/1969	King	
3,750,355	A	8/1973	Blum	
3,860,052	A	1/1975	Schroeder	
4,081,581	A	3/1978	Littell	
4,111,097	A	9/1978	Lasker	
4,111,713	A	9/1978	Beck	
4,186,648	A	2/1980	Clausen et al.	
4,665,794	A *	5/1987	Gerber et al.	89/36.02
4,821,620	A	4/1989	Cartee et al.	
4,953,442	A	9/1990	Bartusko	
5,266,379	A	11/1993	Schaeffer et al.	
5,293,806	A	3/1994	Gonzalez	
5,376,443	A	12/1994	Sijan et al.	
5,517,894	A	5/1996	Bohne et al.	
5,723,807	A	3/1998	Kuhn, II	

(Continued)


*Primary Examiner* — Stephen M Johnson

(74) *Attorney, Agent, or Firm* — Andrews Kurth LLP; Sean S. Wooden

(57) **ABSTRACT**

An armor system that includes a reactive armor component including a disruptive layer. The disruptive layer includes a plurality of three-dimensional geometric shapes each defining at least one hollow space and explosive material. The explosive material is deposited in the at least one hollow space. The disruptive layer also includes explosive material surrounding the geometric shapes and a layer of explosive material on top of the geometric shapes. The armor system may further include a non-reactive armor component.

**9 Claims, 11 Drawing Sheets**



(56)

**References Cited**

U.S. PATENT DOCUMENTS

5,967,211	A	10/1999	Lucas et al.	6,713,008	B1	3/2004	Teeter
6,034,155	A	3/2000	Espeland et al.	6,959,744	B2	11/2005	Sandstrom et al.
6,112,635	A	9/2000	Cohen	6,962,102	B1	11/2005	Johnston et al.
6,370,690	B1	4/2002	Neal	7,080,587	B2	7/2006	Benyami et al.
6,408,734	B1	6/2002	Cohen	7,216,576	B2	5/2007	Henry et al.
6,532,857	B1	3/2003	Shih et al.	7,300,893	B2	11/2007	Barsoum et al.
6,575,075	B2	6/2003	Cohen	7,866,248	B2	1/2011	Moore et al.
6,635,357	B2	10/2003	Moxson et al.	7,908,959	B2	3/2011	Pavon
6,642,159	B1	11/2003	Bhatnagar et al.	8,272,311	B2 *	9/2012	Cannon ..... 89/36.17
				2002/0178900	A1	12/2002	Ghiorse et al.
				2004/0083880	A1 *	5/2004	Cohen ..... 89/36.02
				2008/0264243	A1	10/2008	Lucuta et al.

\* cited by examiner




FIG. 1B




FIG. 1A




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 3A

FIG. 3B




FIG. 3C




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6






FIG. 7A




FIG. 7B




FIG. 8




FIG. 9

RHA	Dura sheet 2mm	Dura sheet 6.4mm	Ceramic Tiles	Dura Sheet 1 gram per ceramic tile	Dura sheet 2 grams per ceramic tile
1.14	0.823	0.81	0.55	0.48	0.45
0.625	0.601	1.05	0.428	0.326	0.301




FIG. 10




FIG. 11

## CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 13/237,691, entitled "Reactive Armor System and Method," filed Sep. 20, 2011, now U.S. Pat. No. 8,387,512, and which is a continuation of U.S. patent application Ser. No. 12/385,126, filed on Mar. 31, 2009, now U.S. Pat. No. 8,104,396, entitled "Reactive Armor System and Method," which claims the priority of U.S. Provisional Application Ser. No. 61/064,851, entitled "Reactive Armor System and Method," ("the '851 application") and filed Mar. 31, 2008, and is a continuation in part of U.S. patent application Ser. No. 11/979,309, now U.S. Pat. No. 7,628,104, entitled "Methods and Apparatus for Providing Ballistic Protection," filed Nov. 1, 2007 ("the '309 application") and U.S. patent application Ser. No. 11/978,663, entitled "Apparatus for Providing Protection From Ballistic Rounds, Projectiles, Fragments and Explosives," filed Oct. 30, 2007 ("the '663 application"), which are a continuation and continuation-in-part, respectively, of U.S. patent application Ser. No. 11/296,402, now U.S. Pat. No. 7,383,761, entitled "Methods and Apparatus for Providing Ballistic Protection," ("the '761 patent"), which was filed Dec. 8, 2005. The above applications and patent are all incorporated herein by reference.

## BACKGROUND

Light-weight vehicles are being subjected to a growing and significant problem, Explosively Formed Projectiles (EFPs). Originally reactive armor was designed to defeat anti-tank rounds. These rounds use a conical shape charge capable of producing a high temperature jet delivering a tremendous amount of energy on a single point. EFPs are highly dense solid matter traveling at 7,000 to 8,000 fps with very high kinetic energy making it much harder to stop using a flying plate method.

## Stopping a Projectile

The basic concept in stopping a projectile is that work must equal energy. The more work the armor can do on the projectile, the more kinetic energy it can absorb. Conventional armor augments work by increased frictional force through hardness, tensile strength and thickness of the armor system.

Normal force is what gives rise to the friction force, the magnitudes of these forces being related by the coefficient of friction " $\mu$ " between the two materials:

$$f = \mu N$$

Therefore, given the mass and velocity of the projectile a simple equation would define the thickness "d" and "F" force to stop the projectile. See FIG. 11.

The hydrodynamic impact of an EFP delivers an enormous amount of energy. In the past, stopping an EFP has been directly related to the density of the armor. It has always been a balance between weight and thickness. The current solution of using rolled homogeneous armor (RHA) backing with Polyethylene and other composites is not a viable solution for light-weight vehicles. For example, to defeat a 135 mm EFP the required armor would be 12-16 inches thick and 80-120 lbs/psf. Using this logic to stop the current threat the armor system would need to be more than 21 inches thick.

Conventional reactive armor systems are omni-directional thus, the back pressure is rather significant. When designing a proactive armor for light-weight vehicles, the back pressure is a major factor to consider.

Embodiments overcome the disadvantages of the prior art. These and other advantages are provided by an armor system that includes a reactive armor component including a disruptive layer that includes a plurality of three-dimensional geometric shapes each defining at least one hollow space and explosive material, in that the explosive material is deposited in the at least one hollow space, explosive material surrounding the geometric shapes, and a layer of explosive material on top of the geometric shapes.

## DESCRIPTION OF THE DRAWINGS

The detailed description will refer to the following drawings, wherein like numerals refer to like elements, and wherein:

FIGS. 1A-1B are diagrams illustrating embodiments of ceramic tiles and explosive material that may be used in embodiments of reactive armor.

FIGS. 2A-2D are diagrams illustrating embodiments of ceramic tiles that may be used in embodiments of reactive armor.

FIGS. 3A-3B are diagrams illustrating an embodiment of ceramic tiles and explosive material, and arrangements of same, that may be used in embodiments of reactive armor.

FIG. 3C is a diagram illustrating a cross-section of a portion of an embodiment of reactive armor that may include a layer of ceramic tiles.

FIG. 4A is a diagram illustrating an embodiment of ceramic tiles and explosive material, and arrangements of same, that may be used in embodiments of reactive armor.

FIG. 4B is a diagram illustrating a cross-section of a portion of an embodiment of reactive armor that may include a layer of ceramic tiles.

FIG. 5A is a diagram illustrating an embodiment of ceramic tiles and explosive material, and arrangements of same, that may be used in embodiments of reactive armor.

FIG. 5B is a diagram illustrating a cross-section of a portion of an embodiment of reactive armor that may include a layer of ceramic tiles.

FIG. 6 is a diagram illustrating a cross-section of a portion of an embodiment of reactive armor that may include a layer of ceramic tiles.

FIGS. 7A and 7B are diagrams illustrating a cross-section of ceramic tiles that may be used in an embodiment of the reactive armor.

FIG. 8 is a diagram illustrating a cross-section of a layer of ceramic tiles that may be used in an embodiment of reactive armor.

FIG. 9 is a diagram illustrating a cross-section of a portion of an embodiment of reactive armor that may include a layer of ceramic tiles.

FIG. 10 is a table and graph illustrating results of a test of an embodiment of reactive armor.

FIG. 11 illustrates a bullet entering a piece of armor.

## DETAILED DESCRIPTION

Described herein are embodiments of an armor system and method for defeating armor piercing rounds, EFPs, RPGs and other threats to personnel, vehicles, buildings and property. In bridging the gap between conventional reactive armor systems and the need to minimize back pressure, embodiments provide a focused, directional system that results in little back pressure using a minimal amount of explosive but still provides protection against EFPs. Embodiments provide a new

armor system designed for light-weight armored vehicles that is both passive and reactive to defeat armor piercing rounds as well as EFPs. This armor is based on Magmacore™ armor technology that uses a unique 3D matrix for displacing energy as well as several patent pending related applications. See, e.g., the '761 patent and the other cross-referenced applications above.

Embodiments described herein are designed to defeat EFPs by using counter measure shape charges, focusing a tremendous amount of kinetic energy at the point of contact. In various embodiments, armor materials are engineered to be consumed in the reaction of defeating an EFP, thus minimizing secondary fragmentation.

Performance Capabilities:	
Conventional Reactive Armor	Reactive Armor Described Herein
Ineffective against EFPs	Anti-EFP armor system
Produce tremendous backpressure	Minimize backpressure
Enormous secondary frags	Reduces secondary frags
Heavy	Light
Conventional Passive Armor	Reactive Armor Described Herein
Thick and bulky	Low profile
Heavy	Lightweight
Tremendous over pressure	Reduces over pressure
Greatly reduce vehicle mobility	Minimal impact on vehicle mobility

Embodiments described herein provide an armor system that is both passive and reactive and which has the following characteristics:

Multi-Threat Capability	Has the ability to take multiple hits from a varying combination of threats (ball rounds, armor piercing and shape charges).
Light Weight	Is designed for light weight vehicles.
Scalable	May be customized to meet varying threats.
Minimize Secondary Fragments	Minimizes collateral damages and reducing secondary fragmentation.
Reduce Back Pressure	Proactive counter response minimizes shock trauma effects to vehicle compartments.
Low Profile	Low profile minimizes the impact to the vehicle's overall dimensions and reduces the impact on the vehicles functionality.

Building on the Magmacore™ armor concept of a 3D matrix for displacing energy, the embodiments described herein provide a viable armor to defeat EFPs and other threats. Embodiments described herein have a unique three-dimensional rigid core designed for structural integrity and to displace energy. This design includes a three-prong approach to defeat EFPs; (1) disrupt the EFP, (2) deliver a focused energy "shape charge" and (3) absorb the resulting shock.

Embodiments of the reactive armor described herein provide a passive and reactive armor system, all-in-one, developed specifically for light armored vehicles. Some additional advantages of reactive armor system embodiments are: it is scalable for a range of threats, has flat and curved surfaces, is lightweight, and has a low profile.

With reference now to FIGS. 1A-1B, embodiments of ceramic tiles 100 used to provide the unique three-dimensional rigid core of embodiments of the reactive armor system are shown. Here, ceramic tiles 100 are hexagonal-shaped and may be placed together as shown. The embodiments shown illustrate different geometric arrangements of ceramic tiles 100, such as linear groupings or wider groupings. In other

embodiments, the ceramic tiles may be square or other geometric shape. Each tile shown may have a partially hollowed out section or space 102 in which other material may be placed. In embodiments, the hollowed out space 102 may extend all the way through the center of ceramic tiles 100 or part-way through. If part-way through, the hollowed out space 102 may be on one side or both sides of ceramic tile 100. In embodiments, the space 102 may be filled with a plastic explosive or other explosive material 104. The plastic explosive or other explosive material 104 may provide the reactive component of the reactive armor.

In the embodiment shown, the explosive material 104 is pentaerythritol tetranitrate (PETN). In the embodiment shown in FIG. 1A, ceramic tiles 100 may be filled with 1 gram of PETN explosive material 104 per ceramic tile 100. In the embodiment shown in FIG. 1B, ceramic tiles 100 may be filled with 2 grams of PETN explosive material 104 per ceramic tile 100. The different amounts of explosive material 104 may be determined by the volume of the hollowed out space 102 in ceramic tiles 100. In the embodiment shown in FIG. 1A, for example, the hollowed out space 102 may be large enough to permit up to a 1 gram of explosive material 104. In the embodiment shown in FIG. 1B, for example, the hollowed out space 102 may be large enough to permit up to 2 grams of explosive material 104.

It is also important to note that ceramic tiles 100 may be sized larger or smaller depending on the nature of the expected threats. If more explosive material 104 and larger ceramic tiles 100 are needed to provide effective static armor functionality, larger ceramic tiles 100 may be used.

In the reactive armor, the explosive material 104 reacts to an EFP, or other threat such as an RPG, to deliver focused energy (a shape charge), disrupting the EFP affects. Ceramic tiles 100 may be made of virtually any three-dimensional shape, such as cubes, cylinders, spheres, etc. The tiles may be made out of various materials, other than ceramics, and filled with other materials, such as sand.

With reference now to FIGS. 2A-2D, shown are various embodiments of hexagonal ceramic tiles 200. Each embodiment has a hollow space or spaces 202 in which PETN or other explosive material may be placed. In some of the embodiments shown, the hollow space 202 is on the top and bottom of ceramic tile 200. In other embodiments, the hollow space 202 extends part way through ceramic tile 200 on one side. If ceramic tiles 200 include multiple hollow spaces 202, each hollow space 202 may be of different size and shape.

In FIG. 2A, ceramic tile 200 includes two hollow spaces 202 in the center of ceramic tile 200. The hollow spaces 202 extend partially towards the middle of ceramic tile 200. The depth of the hollow spaces 202 may be varied to accommodate more or less explosive material. In the embodiment shown, ceramic tile 200 may have a height of 10 units (e.g., 10 millimeters) and a width of 20 units, providing a relatively short and wide ceramic tile 200. The depth of each hollow space 202 is 2 units, leaving a center, non-hollowed out section 206 of 6 units. The hollow spaces 202 may also leave a tile wall 208 of 2 units thick surrounding the hollow spaces 202. The shape, size, position and other characteristics of the hollow spaces 202 and ceramic tile 200 help to shape the explosive charge produced by the explosive material deposited into the hollow spaces 202.

Ceramic tile 200 shown in FIG. 2B may have a height of 14 units (e.g., 14 millimeters) and a width of 12 units, providing a relatively tall and narrow ceramic tile 200. The depth of each hollow space 202 is also 2 units, leaving a center, non-hollowed out section 206 of 10 units. The hollow spaces 202 may also leave a tile wall 208 of 2 units thick surrounding the

5

hollow spaces **202**. The shape, size, position and other characteristics of the hollow spaces **202** and ceramic tile **200** help to shape the explosive charge produced by the explosive material deposited into the hollow spaces **202**.

Ceramic tile **200** shown in FIG. 2C may have a height of 14 units (e.g., 14 millimeters) and a width of 12 units, providing a relatively tall and narrow ceramic tile **200**. Ceramic tile **200** shown in FIG. 2C, however, only has one hollow space **202**. The hollow space **202** shown may have depth of 10 units, leaving a non-hollowed out section **206** of 4 units on one end (e.g., the top) of ceramic tile **200**. The hollow spaces **202** may also leave a tile wall **208** of 2 units thick surrounding the hollow space **202**. In the embodiment shown here, the hollow space **202** may be circular in shape, as opposed to the hexagonal shape shown in FIGS. 2A-2B. This illustrates that a variety of hollow space shapes may be used which are not limited by the shape of ceramic tile **200**. The shape, size, position and other characteristics of the hollow space **202** and ceramic tile **200** help to shape the explosive charge produced by the explosive material deposited into the hollow spaces **202**. Ceramic tile **200** shown in FIG. 2D may be nearly identical to ceramic tile **200** shown in FIG. 2C, except that hollow space **202** may be hexagonal in shape. The dimensions, shapes and configurations of ceramic tiles **200**, hollow spaces **202**, non-hollowed out sections **206** and tile walls **208** may be varied to shape the charge and provide armor characteristics best fitting the application of the ceramic armor.

With reference now to FIGS. 3A-3C, shown are embodiments of ceramic tiles **300** and arrangements thereof that may be used in an embodiment of reactive armor **320**. With reference to FIG. 3A, ceramic tiles **300** may be hexagonal and may have shallow (relative to the thickness of the tiles) hollow spaces **302** on the top and bottom of ceramic tile **300** (e.g., similar to ceramic tile **200** shown in FIG. 2A as described above).

With reference to FIG. 3B, hollow spaces **302** may have explosive material **304** deposited along inner side of walls **306**. In the embodiments shown, PETN or other plastic sheet explosive (RDX, HMX, etc.) explosive material **304** may be placed along the inside of walls **306** of the hollow spaces **302**. The explosive may be placed in both the top and bottom hollow spaces **302** or in only one of the hollow spaces **302** in ceramic tiles **300**. The explosive may not fill the entire hollow space **302**. Different ceramic tiles **300** may have different amounts of explosive and explosive may be placed in the top or bottom in different ceramic tiles **302**. Basically, the placing of the explosive may be configured for the threat or threats reactive armor **320** is intended to address.

FIG. 3B also shows an example of how ceramic tiles **300** may be arranged next to each other in a ceramic tile layer **324** of reactive armor **320**. Ceramic tile layer **324** may include a single ceramic tile-height layer of ceramic tiles **300** arranged as shown in FIG. 3B, or otherwise arranged. Likewise, ceramic tile layer **324** may include multiple ceramic tile-height layers of ceramic tiles **300**, stacked on top of one another.

With reference to FIG. 3C, shown is an embodiment of reactive armor **320**. A cross-section of a partial portion of reactive armor **320** is shown. Reactive armor **320** may include a self-healing layer **322**, e.g., a self-healing polymer skin (e.g., Rhinocast) layer, such as described in the '761 patent or the other cross-referenced patent applications above. When fragments, explosives or other projectiles impact on self-healing layer **322**, it "self-heals," closing or partially closing any holes made in self-healing layer **322**. Self-healing layer **322** helps to keep ceramic tile **300** fragments within armor **320**, maintaining the integrity of ceramic armor **320** and

6

extending its useful life. Self-healing outer layer **322** may encapsulate the ceramic tile layer.

Self-healing layer **322** may be deposited on top of and help contain ceramic tile layer **324**. Ceramic tile layer **324**, as described above, may include ceramic tiles **300** with explosive **304** deposited along the side walls **306**. As described above, ceramic tile layer **324** may include a single layer of ceramic tiles **300** or multiple layers of ceramic tiles **300** stacked on top of one another. Ceramic tiles **300** may be arranged within each layer as shown in FIG. 3B or otherwise. Ceramic tiles **300** may provide stopping, static armor aspects of reactive armor **320** as well as reactive armor aspects described herein. See '761 patent or the other cross-referenced patent applications above.

Reactive armor **320** may also include a backing layer **326**. Backing layer **326** may provide backing and additional static armor functionality of reactive armor. Backing layer **326** may also provide protection from reactive armor affects on non-threat side of reactive armor **320**. See the '761 patent or the other cross-referenced patent applications for description of backing layers. Backing layer **326** may be made from a variety of materials (e.g., steel, plastic, composite, wood, Magmacore™ armor as described in the '761 patent or the other cross-referenced patent applications) and may be secured to the tiles with an epoxy. Different tiles, such as those shown in FIG. 2, may be used. Additional explosive may also be placed as a sheet on top of the ceramic tile layer **324** or between ceramic tiles **300** in the reactive armor **320**.

With reference now to FIGS. 4A and 4B, shown are embodiments of ceramic tiles **400** and arrangements thereof that may be used in an embodiment of reactive armor **420**. In embodiments, the ceramic tiles may have shallow (relative to the thickness of the tiles) hollow spaces **402** on the top and bottom of ceramic tiles **400**. The hollow spaces **402** may be filled with explosive material **404**, as shown. The explosive material **404** may be PETN, RDX, HMX, other plastic sheet explosive, or other explosive filling the hollow spaces **402**. The explosive material **404** may fill both the top and the bottom hollow spaces **402**, or either of the hollow spaces **402** in ceramic tile **400**. The explosive material **404** may not fill the entire hollow space. Different ceramic tiles **400** may have different amounts of explosive and explosive may be placed in the top or bottom in different ceramic tiles **400**. Basically, the placing of the explosive material **404** may be configured for the threat.

With reference to FIG. 4B, shown is an embodiment of reactive armor **420**. A cross-section of a partial portion of reactive armor **420** is shown. Reactive armor **420** may include a self-healing layer **422**, a ceramic tile layer **424**, and a backing layer **426**. Each layer may be configured as described above with reference to FIG. 3C. As there, the different layers may be secured to each other with an epoxy, other adhesive or fastener. Different tiles, such as shown in FIG. 2, may be used. Additional explosive may also be placed as a sheet on top of ceramic tile layer **424** or between ceramic tiles **400** in reactive armor **420**.

With reference now to FIGS. 5A-5B, shown are embodiments of ceramic tiles **500** and arrangements thereof that may be used in an embodiment of reactive armor **520**. Ceramic tiles **500** may be hexagonal ceramic tiles that may include hollow spaces **502** on top and bottom of center of ceramic tiles **500**. As shown, ceramic tiles **500** may include no explosive material. As shown in FIG. 5B, reactive armor **520** may include a self-healing layer **522**, a ceramic tile layer **524**, and a backing layer **526**. Each layer may be configured as described above with reference to FIG. 3C. As there, the different layers may be secured to each other with an epoxy,



other adhesive or fastener. Different tiles, such as shown in FIG. 2, may be used. To provide a reactive armor component, an explosive material layer 504 may be placed as a sheet on top of the ceramic tile layer 524 or between ceramic tiles 500.

With reference now to FIG. 6, shown are embodiments of ceramic tiles 600 and arrangements thereof that may be used in an embodiment of reactive armor 620. Ceramic tiles 600 may be hexagonal ceramic tiles that may include hollow spaces 602 on top and bottom of center of ceramic tiles 600. As shown, ceramic tiles 600 may include no explosive material. Reactive armor 620 may include a self-healing layer 622, a ceramic tile layer 624, and a backing layer 626. Each layer may be configured as described above with reference to FIG. 3C. The self-healing layer 622 may be a polymer skin formed with a layer of wire mesh embedded therein. The wire mesh helps to keep ceramic tile 600 fragments within armor 620, maintaining the integrity of ceramic armor 620 and extending its useful life. The wire mesh may also help to contain explosive fragments. The backing layer 626 may be three-dimensional (3D) safety glass with wire mesh. To provide a reactive armor component, an explosive material 604 may be placed as a sheet on top of ceramic tile layer 624. Alternatively, explosive material 604 may be placed between ceramic tiles 600.

With reference now to FIGS. 7A and 7B, shown are embodiments of ceramic tiles 700 and potential forces resulting from reactive armor utilizing ceramic tiles 700. FIG. 7A illustrates a progressive cross-section view of reactive tile 700, with the potential forces indicated by arrows. Plastic explosive is generally omni-directional. For effective reactive armor, the explosive material 704 should be shaped to have an effective direction. A washer or similar device 705 may be placed into the hollow spaces in the ceramic tiles to shape the explosive. In the three right-most ceramic tiles 700 shown, explosive material in the bottom hollow space 702 of ceramic tile 700 may fill a thin layer above a washer 705, in the hole of the washer 705 (the narrow vertical channel) and below the washer 705. Embodiments of the reactive armor described herein may use a systematized chain reaction to minimize backpressure. The point of impact of the EFP, RPG, fragment, explosive force or other projectile (e.g., in the middle of the tile), triggers the explosion of the explosive material 704 in the vertical channel formed in the washer 705, propagating kinetic force downward, shown by downward arrow. This kinetic force triggers the explosion of the explosive material in the bottom of the hollow space 702, shown by the bottom-most upward arrows, propagating kinetic force upwards, shown by the top upward arrows, against the EFP, RPG, fragment, explosive force or other projectile. This reaction minimizes the affects of the EFP, RPG, fragment, explosive force or other projectile. FIG. 7B illustrates a single ceramic tile 700 and the various forces and reactive forces described above. The large downward arrow represents the downward force of the EFP, RPG, fragment, explosive force or other projectile, the bottom-most upward arrows kinetic force reflecting off of the backing layer as a result of the explosive material in the channel exploding, the middle upward arrows the explosive force of the explosive material in the bottom of the hollow space 702 and the top-most upward arrows the kinetic force resulting from that explosive force.

With reference now to FIG. 8, shown is a cross-section of a portion of an embodiment of ceramic tile layer 824 that may be used in reactive armor. This drawing illustrates that the ceramic tiles are designed to contain explosives and explosive force and prevent propagation of the explosives and explosive forces. The explosive force impacts on ceramic tile layer 824 at intersection of two ceramic tiles 800. This triggers resulting

reactive armor explosions and resulting opposing kinetic forces, as shown. The explosive material 804 in the two impacted ceramic tiles 800 explodes. However, the ceramic tile walls 806 contain the explosions of the explosive material 804, helping to direct or shape these explosions upwards against the EFP, RPG, fragment, explosive force or other projectile. By helping to shape the explosions of the explosive material 804 upwards, the walls 806 also help prevent the horizontal spread of the explosive affects to adjacent ceramic tiles 800.

With reference now to FIG. 9, shown is a cross-section of a portion of reactive armor 920. As in FIG. 8 above, this drawing illustrates that the ceramic tiles are designed to contain explosives and explosive force and prevent propagation of the explosives and explosive forces. The explosive force impacts on ceramic tile layer 924 at intersection of two ceramic tiles 900. This triggers resulting reactive armor explosions and resulting opposing kinetic forces, as shown. The explosive material 904 in the two impacted ceramic tiles 900 explodes. However, the walls 906 contain the explosions of the explosive material 904, helping to direct or shape these explosions upwards against the EFP, RPG, fragment, explosive force or other projectile. By helping to shape the explosions of the explosive material 904 upwards, the walls 906 also help prevent the horizontal spread of the explosive affects to adjacent ceramic tiles 900.

Reactive armor 920 may include a ceramic tile layer 924 and a backing layer 926. Reactive armor 920 may also include a self-healing layer, which is not shown in FIG. 9. Downward explosive force resulting from EFP, RPG, fragment, explosive force or other projectile and explosive material 904 explosion (e.g., in vertical channel formed by washer 905), generates a reactive upward kinetic force from backing layer 926, as shown. Backing layer 926 may be steel. The steel may represent a vehicle. Reactive armor 920 may be affixed to the exterior of the vehicle. Unlike conventional reactive armor the majority of the material used in the reactive armor 920 described herein is designed to be consumed, minimizing secondary fragmentations.

#### Summary of Reactive Armor Results

Various testing, as illustrated and described in the '851 application, was performed on embodiments of the reactive armor described herein. During testing, embodiments of the reactive armor were able to greatly reduce the depth and width of the cut from various explosions, such as a 5400 grain Liner Shape Charge (LSC) (used to minimize the possibility of skewing the tests used a 5400 grain linear shape charge known for its' consistency). The unimpeded Liner Shape Charge cut into the RHA the furthest. The 2 mm Dura Sheet Explosive did help reduce the depth and width of the cut, but with great back pressure. Increasing the Dura Sheet Explosive to 6.4 mm did not improve the results from 2 mm of Dura Sheet Explosive, however the back pressure was so great that it deformed the 1¼ steel. In this case the Dura Sheet Explosive actually was helping the LSC.

The best result achieved was using ceramic tiles with 2 grams of Dura Sheet Explosive per ceramic tile. See the table and graph in FIG. 10.

In developing the reactive armor, testing was conducted to confirm the structure of the ceramic layer or core provides protection to the explosive and that the reactive armor embodiments is stable in non-EFP conditions. The strain tests performed determined that reactive armor, with ceramic tiles filled with explosive material, would not detonate from the affects of a non-EFP/RPG impact. See the '851 application.

A pinch test was also performed to see if the ceramic tiles filled with explosive material would detonate and the result was no detonation. The ceramic tiles contained the explosive from redundant detonation in this pressure test. See the '851 application.

Additional tests were performed to determine if reactive armor with ceramic tiles filled with explosive material would detonate from the affects of small arms fire. The result was no detonation. Another test was conducted to determine structural performance and the result was that the reactive armor with ceramic tiles filled with explosive material contained the explosion from the redundant detonation with 1/2 lbs of PETN.

Various embodiments of reactive armor and various combinations of the reactive armor embodiments described herein may be used to address a threat from EFPs, RPGs and threats. For example, multiple layers of reactive armor embodiments described herein may be used. Layers of reactive armor combined with layers of armor described in the '309 application, the '663 application, and/or the '761 patent. Such combinations may be configured, for example, as described in '309 application, the '663 application, and/or the '761 patent. One of the many advantages of the reactive armor, armor described in the '309 application, the '662 application, and/or the '761 patent, is that it may be designed to address virtually any threat.

The terms and descriptions used herein are set forth by way of illustration only and are not meant as limitations. Those skilled in the art will recognize that many variations are possible within the spirit and scope of the invention as defined in the following claims, and their equivalents, in which all terms are to be understood in their broadest possible sense unless otherwise indicated.

The invention claimed is:

1. An armor system comprising:

a reactive armor component including a disruptive layer that includes:

- 5 a plurality of three-dimensional geometric shapes each defining at least one hollow space and explosive material, wherein the explosive material is deposited in the at least one hollow space of substantially all of the geometric shapes;
- 10 explosive material surrounding the geometric shapes; and
- a layer of explosive material on top of the geometric shapes.

15 2. The armor system of claim 1 further including at least one non-reactive armor component.

3. The armor system of claim 1 wherein the geometric shapes are spheres.

20 4. The armor system of claim 1 wherein the geometric shapes are cubes.

5. The armor system of claim 1 wherein the geometric shapes are hexagonal.

6. The armor system of claim 1 wherein the geometric shapes are spherical.

25 7. The armor system of claim 1 wherein the geometric shapes are cylinders.

8. The armor system of claim 1 further comprising a backing portion.

30 9. The armor system of claim 8 wherein the backing portion includes a passive armor layer.

\* \* \* \* \*