

(12) **United States Patent**
Pletcher et al.

(10) **Patent No.:** **US 9,158,133 B1**
(45) **Date of Patent:** **Oct. 13, 2015**

(54) **CONTACT LENS EMPLOYING OPTICAL SIGNALS FOR POWER AND/OR COMMUNICATION**

4,463,149 A 7/1984 Ellis
4,555,372 A 11/1985 Kunzler et al.
4,604,479 A 8/1986 Ellis
4,632,844 A 12/1986 Yanagihara et al.
4,686,267 A 8/1987 Ellis et al.
4,740,533 A 4/1988 Su et al.

(75) Inventors: **Nathan Pletcher**, Mountain View, CA (US); **Brian Otis**, Sunnyvale, CA (US)

(Continued)

(73) Assignee: **Google Inc.**, Mountain View, CA (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 517 days.

EP 0369942 5/1990
EP 686372 12/1995

(Continued)

(21) Appl. No.: **13/559,350**

OTHER PUBLICATIONS

(22) Filed: **Jul. 26, 2012**

Wall, K., "Active contact lens that lets you see like the Terminator patented," Feb. 10, 2012, <http://www.patexia.com/feed/active-contact-lens-that-lets-you-see-like-the-terminator-patented-2407>, Last accessed Mar. 28, 2012, 5 pages.

(Continued)

(51) **Int. Cl.**
G02C 1/00 (2006.01)
G02C 11/00 (2006.01)
G02C 7/04 (2006.01)

Primary Examiner — Huy K Mai

(52) **U.S. Cl.**
CPC . **G02C 11/10** (2013.01); **G02C 7/04** (2013.01)

(74) *Attorney, Agent, or Firm* — McDonnell Boehnen Hulbert & Berghoff LLP

(58) **Field of Classification Search**
CPC G02C 7/04; G02C 7/049; G02C 11/10
USPC 351/158, 159.02, 159.03
See application file for complete search history.

(57) **ABSTRACT**



(56) **References Cited**

Apparatus, systems and methods employing contact lens sensors are provided. In some aspects, a contact lens includes a substrate that forms at least a portion of the body of the contact lens; an optical communication device disposed on or within the substrate; and a photodetector disposed on or within the substrate, wherein the photodetector harvests light emitted from a device and generates power from the harvested light. In some aspects, an apparatus comprises a tag having a circuit including: an optical communication device; and a photodetector that harvests light received and generates power from the harvested light. The tag can be disposed on or within a contact lens in various aspects.

U.S. PATENT DOCUMENTS

3,958,560 A 5/1976 March
4,014,321 A 3/1977 March
4,055,378 A 10/1977 Feneberg et al.
4,122,942 A 10/1978 Wolfson
4,136,250 A 1/1979 Mueller et al.
4,143,949 A 3/1979 Chen
4,153,641 A 5/1979 Deichert et al.
4,214,014 A 7/1980 Hofer et al.
4,309,085 A 1/1982 Morrison
4,312,575 A 1/1982 Peyman et al.
4,401,371 A 8/1983 Neefe

14 Claims, 9 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

| | | | | | | | |
|-----------|----|---------|-------------------|--------------|-----|---------|------------------------------|
| 4,826,936 | A | 5/1989 | Ellis | 7,728,949 | B2 | 6/2010 | Clarke et al. |
| 4,996,275 | A | 2/1991 | Ellis et al. | 7,751,896 | B2 | 7/2010 | Graf et al. |
| 4,997,770 | A | 3/1991 | Giles et al. | 7,799,243 | B2 | 9/2010 | Mather et al. |
| 5,032,658 | A | 7/1991 | Baron et al. | 7,809,417 | B2 | 10/2010 | Abreu |
| 5,034,461 | A | 7/1991 | Lai et al. | 7,878,650 | B2 | 2/2011 | Fritsch et al. |
| 5,070,215 | A | 12/1991 | Bambury et al. | 7,885,698 | B2 | 2/2011 | Feldman |
| 5,135,297 | A | 8/1992 | Valint et al. | 7,907,931 | B2 | 3/2011 | Hartigan et al. |
| 5,177,165 | A | 1/1993 | Valint et al. | 7,926,940 | B2 | 4/2011 | Blum et al. |
| 5,177,168 | A | 1/1993 | Baron et al. | 7,931,832 | B2 | 4/2011 | Pugh et al. |
| 5,219,965 | A | 6/1993 | Valint et al. | 7,964,390 | B2 | 6/2011 | Rozakis et al. |
| 5,260,000 | A | 11/1993 | Nandu et al. | 8,080,187 | B2 | 12/2011 | Tepedino, Jr. et al. |
| 5,271,875 | A | 12/1993 | Appleton et al. | 8,096,654 | B2 | 1/2012 | Amirparviz et al. |
| 5,310,779 | A | 5/1994 | Lai | 8,118,752 | B2 | 2/2012 | Hetling et al. |
| 5,321,108 | A | 6/1994 | Kunzler et al. | 8,142,016 | B2 | 3/2012 | Legerton et al. |
| 5,326,584 | A | 7/1994 | Kamel et al. | 8,224,415 | B2 | 7/2012 | Budiman |
| 5,336,797 | A | 8/1994 | McGee et al. | 8,446,341 | B2* | 5/2013 | Amirparviz et al. 345/7 |
| 5,346,976 | A | 9/1994 | Ellis et al. | 2002/0193674 | A1 | 12/2002 | Fleischman et al. |
| 5,358,995 | A | 10/1994 | Lai et al. | 2003/0179094 | A1 | 9/2003 | Abreu |
| 5,364,918 | A | 11/1994 | Valint et al. | 2004/0027536 | A1 | 2/2004 | Blum et al. |
| 5,387,662 | A | 2/1995 | Kunzler et al. | 2004/0116794 | A1 | 6/2004 | Fink et al. |
| 5,449,729 | A | 9/1995 | Lai | 2005/0045589 | A1 | 3/2005 | Rastogi et al. |
| 5,472,436 | A | 12/1995 | Fremstad | 2005/0221276 | A1 | 10/2005 | Rozakis et al. |
| 5,512,205 | A | 4/1996 | Lai | 2007/0016074 | A1 | 1/2007 | Abreu |
| 5,585,871 | A | 12/1996 | Linden | 2007/0030443 | A1 | 2/2007 | Chapoy et al. |
| 5,610,252 | A | 3/1997 | Bambury et al. | 2007/0121065 | A1 | 5/2007 | Cox et al. |
| 5,616,757 | A | 4/1997 | Bambury et al. | 2007/0188710 | A1 | 8/2007 | Hetling et al. |
| 5,682,210 | A | 10/1997 | Weirich | 2008/0208335 | A1 | 8/2008 | Blum et al. |
| 5,708,094 | A | 1/1998 | Lai et al. | 2008/0218696 | A1 | 9/2008 | Mir |
| 5,710,302 | A | 1/1998 | Kunzler et al. | 2009/0033863 | A1 | 2/2009 | Blum et al. |
| 5,714,557 | A | 2/1998 | Kunzler et al. | 2009/0036761 | A1 | 2/2009 | Abreu |
| 5,726,733 | A | 3/1998 | Lai et al. | 2009/0057164 | A1 | 3/2009 | Minick et al. |
| 5,760,100 | A | 6/1998 | Nicholson et al. | 2009/0076367 | A1 | 3/2009 | Sit et al. |
| 5,908,906 | A | 6/1999 | Kunzler et al. | 2009/0118604 | A1 | 5/2009 | Phan et al. |
| 5,981,669 | A | 11/1999 | Valint et al. | 2009/0189830 | A1 | 7/2009 | Deering et al. |
| 6,087,941 | A | 7/2000 | Ferraz | 2009/0196460 | A1 | 8/2009 | Jakobs et al. |
| 6,131,580 | A | 10/2000 | Ratner et al. | 2010/0001926 | A1 | 1/2010 | Amirparviz et al. |
| 6,193,369 | B1 | 2/2001 | Valint et al. | 2010/0013114 | A1 | 1/2010 | Bowers et al. |
| 6,200,626 | B1 | 3/2001 | Grobe et al. | 2010/0016704 | A1 | 1/2010 | Naber et al. |
| 6,213,604 | B1 | 4/2001 | Valint et al. | 2010/0028559 | A1 | 2/2010 | Yan et al. |
| 6,312,393 | B1 | 11/2001 | Abreu | 2010/0072643 | A1 | 3/2010 | Pugh et al. |
| 6,348,507 | B1 | 2/2002 | Heiler et al. | 2010/0109175 | A1 | 5/2010 | Pugh et al. |
| 6,366,794 | B1 | 4/2002 | Moussy et al. | 2010/0110372 | A1 | 5/2010 | Pugh et al. |
| 6,423,001 | B1 | 7/2002 | Abreu | 2010/0113901 | A1 | 5/2010 | Zhang et al. |
| 6,428,839 | B1 | 8/2002 | Kunzler et al. | 2010/0133510 | A1 | 6/2010 | Kim et al. |
| 6,431,705 | B1 | 8/2002 | Linden | 2010/0249548 | A1 | 9/2010 | Muller |
| 6,440,571 | B1 | 8/2002 | Valint et al. | 2011/0015512 | A1 | 1/2011 | Pan et al. |
| 6,450,642 | B1 | 9/2002 | Jethmalani et al. | 2011/0028807 | A1 | 2/2011 | Abreu |
| 6,532,298 | B1 | 3/2003 | Cambier et al. | 2011/0040161 | A1 | 2/2011 | Abreu |
| 6,550,915 | B1 | 4/2003 | Grobe, III | 2011/0055317 | A1 | 3/2011 | Vonog et al. |
| 6,570,386 | B2 | 5/2003 | Goldstein | 2011/0063568 | A1 | 3/2011 | Meng et al. |
| 6,579,235 | B1 | 6/2003 | Abita et al. | 2011/0084834 | A1 | 4/2011 | Sabeta |
| 6,599,559 | B1 | 7/2003 | McGee et al. | 2011/0116035 | A1 | 5/2011 | Fritsch et al. |
| 6,614,408 | B1 | 9/2003 | Mann | 2011/0157541 | A1 | 6/2011 | Peyman |
| 6,630,243 | B2 | 10/2003 | Valint et al. | 2011/0157544 | A1 | 6/2011 | Pugh et al. |
| 6,638,563 | B2 | 10/2003 | McGee et al. | 2011/0184271 | A1 | 7/2011 | Veciana et al. |
| 6,726,322 | B2 | 4/2004 | Andino et al. | 2011/0274680 | A1 | 11/2011 | Mazed et al. |
| 6,735,328 | B1 | 5/2004 | Helbing et al. | 2011/0286064 | A1 | 11/2011 | Burles et al. |
| 6,779,888 | B2 | 8/2004 | Marmo | 2011/0298794 | A1 | 12/2011 | Freedman |
| 6,804,560 | B2 | 10/2004 | Nisch et al. | 2012/0026458 | A1 | 2/2012 | Qiu et al. |
| 6,851,805 | B2 | 2/2005 | Blum et al. | 2012/0038881 | A1 | 2/2012 | Amirparviz et al. |
| 6,885,818 | B2 | 4/2005 | Goldstein | 2012/0041287 | A1 | 2/2012 | Goodall et al. |
| 6,939,299 | B1 | 9/2005 | Petersen et al. | 2012/0041552 | A1 | 2/2012 | Chuck et al. |
| 6,980,842 | B2 | 12/2005 | March et al. | 2012/0069254 | A1 | 3/2012 | Burton |
| 7,018,040 | B2 | 3/2006 | Blum et al. | 2012/0075168 | A1 | 3/2012 | Osterhout et al. |
| 7,131,945 | B2 | 11/2006 | Fink et al. | 2012/0075574 | A1 | 3/2012 | Pugh et al. |
| 7,169,106 | B2 | 1/2007 | Fleischman et al. | 2012/0078071 | A1 | 3/2012 | Bohm et al. |
| 7,398,119 | B2 | 7/2008 | Lambert et al. | 2012/0088258 | A1 | 4/2012 | Bishop et al. |
| 7,423,801 | B2 | 9/2008 | Kaufman et al. | 2012/0092612 | A1 | 4/2012 | Binder |
| 7,429,465 | B2 | 9/2008 | Muller et al. | 2012/0109296 | A1 | 5/2012 | Fan |
| 7,441,892 | B2 | 10/2008 | Hsu | 2012/0177576 | A1 | 7/2012 | Hu |
| 7,443,016 | B2 | 10/2008 | Tsai et al. | 2012/0201755 | A1 | 8/2012 | Rozakis et al. |
| 7,450,981 | B2 | 11/2008 | Jeon | 2012/0245444 | A1 | 9/2012 | Otis et al. |
| 7,639,845 | B2 | 12/2009 | Utsunomiya | 2012/0259188 | A1 | 10/2012 | Besling |
| 7,654,671 | B2 | 2/2010 | Glynn | | | | |
| 7,699,465 | B2 | 4/2010 | Dootjes et al. | | | | |

FOREIGN PATENT DOCUMENTS

| | | |
|----|---------|---------|
| EP | 1061874 | 12/2000 |
| EP | 1617757 | 1/2006 |
| EP | 1818008 | 8/2007 |

(56)

References Cited

FOREIGN PATENT DOCUMENTS

| | | |
|----|-------------|---------|
| EP | 1947501 | 7/2008 |
| EP | 2457122 | 5/2012 |
| WO | 95/04609 | 2/1995 |
| WO | 0116641 | 3/2001 |
| WO | 01/34312 | 5/2001 |
| WO | 03065876 | 8/2003 |
| WO | 2004/060431 | 7/2004 |
| WO | 2004064629 | 8/2004 |
| WO | 2006015315 | 2/2006 |
| WO | 2009094643 | 7/2009 |
| WO | 2010105728 | 9/2010 |
| WO | 2010/133317 | 11/2010 |
| WO | 2011/011344 | 1/2011 |
| WO | 2011034592 | 3/2011 |
| WO | 2011035228 | 3/2011 |
| WO | 2011035262 | 3/2011 |
| WO | 2011083105 | 7/2011 |
| WO | 2011163080 | 12/2011 |
| WO | 2012035429 | 3/2012 |
| WO | 2012037455 | 3/2012 |
| WO | 2012051167 | 4/2012 |
| WO | 2012051223 | 4/2012 |
| WO | 2012052765 | 4/2012 |

OTHER PUBLICATIONS

- Parviz, Babak A., "Augmented Reality in a Contact Lens," IEEE Spectrum, Sep. 2009, <http://spectrum.ieee.org/biomedical/bionics/augmented-reality-in-a-contact-lens/0>, Last accessed Mar. 14, 2012, 6 pages.
- Bionic contact lens 'to project emails before eyes,' <http://www.kurzweilai.net/forums/topic/bionic-contact-lens-to-project-emails-before-eyes>, Last accessed Mar. 14, 2012, 2 pages.
- Tweedie, et al., "Contact creep compliance of viscoelastic materials via nanoindentation," J. Mater. Res., Jun. 2006, vol. 21, No. 2, pp. 1576-1589, Materials Research Society.
- Brahim, et al., "Polypyrrole-hydrogel composites for the construction of clinically important biosensors," 2002, Biosensors & Bioelectronics, vol. 17, pp. 53-59.
- Huang, et al., "Wrinkling of Ultrathin Polymer Films," Mater. Res. Soc. Symp. Proc., 2006, vol. 924, 6 pages, Materials Research Society.
- Zarbin, et al., "Nanotechnology in ophthalmology," Can J Ophthalmol, 2010, vol. 45, No. 5, pp. 457-476.
- Selner, et al., "Novel Contact Lens Electrode Array for Multi-electrode Electroretinography (meERG)," IEEE, 2011, 2 pages.
- Liao, et al., "A 3- μ W CMOS Glucose Sensor for Wireless Contact-Lens Tear Glucose Monitoring," IEEE Journal of Solid-State Circuits, Jan. 2012, vol. 47, No. 1, pp. 335-344.
- Chen, et al., "Microfabricated Implantable Parylene-Based Wireless Passive Intraocular Pressure Sensors," Journal of Microelectromechanical Systems, Dec. 2008, vol. 17, No. 6, pp. 1342-1351.
- Thomas, et al., "Functional Contact Lenses for Remote Health Monitoring in Developing Countries," IEEE Global Humanitarian Technology Conference, 2011, pp. 212-217, IEEE Computer Society.
- Pandey, et al., "A Fully Integrated RF-Powered Contact Lens With a Single Element Display," IEEE Transactions On Biomedical Circuits And Systems, Dec. 2010, vol. 4, No. 6, pages.
- Lingley, et al., "Multipurpose integrated active contact lenses," SPIE, 2009, 2 pages.
- Chu, et al., "Soft Contact-lens Sensor for Monitoring Tear Sugar as Novel Wearable Device of Body Sensor Network," http://www.ksi.edu/seke/dms11/DMS2_Kohji_Mitsubayashi.pdf, Last accessed Jul. 27, 2012, 4 pages.
- Liao, et al., "A 3 μ W Wirelessly Powered CMOS Glucose Sensor for an Active Contact Lens," 2011 IEEE International Solid-State Circuits Conference, Session 2, Feb. 21, 2011, 3 pages.
- Hurst, "How contact lenses could help save your life," Mail Online, Apr. 19, 2010, <http://www.dailymail.co.uk/health/article-1267345/How-contact-lenses-help-save-life.html>, Last accessed Jul. 27, 2012.
- Lončar, et al., "Design and Fabrication of Silicon Photonic Crystal Optical Waveguides," Journal of Lightwave Technology, Oct. 2000, vol. 18, No. 10, pp. 1402-1411.
- Liu, et al., "Miniature Amperometric Self-Powered Continuous Glucose Sensor with Linear Response," Analytical Chemistry, 7 pages.
- Baxter, "Capacitive Sensors," 2000, 17 pages.
- Lingley, et al., "A Single-Pixel Wireless Contact Lens Display," Journal of Micromechanics and Microengineering, 2011, 9 pages.
- Badugu et al., "A Glucose Sensing Contact Lens: A Non-Invasive Technique for Continuous Physiological Glucose Monitoring," Journal of Fluorescence, Sep. 2003, pp. 371-374, vol. 13, No. 5.
- Carlson et al., "A 20 mV Input Boost Converter With Efficient Digital Control for Thermoelectric Energy Harvesting," IEEE Journal of Solid-State Circuits, Apr. 2010, pp. 741-750, vol. 45, No. 4.
- Chu et al., "Biomedical soft contact-lens sensor for in situ ocular biomonitoring of tear contents," Biomed Microdevices, 2011, pp. 603-611, vol. 13.
- Chu et al., "Soft contact lens biosensor for in situ monitoring of tear glucose as non-invasive blood sugar assessment," Talanta, 2011, pp. 960-965, vol. 83.
- "Contact Lenses: Look Into My Eyes," The Economist, Jun. 2, 2011, <http://www.economist.com/node/18750624/print>, Last accessed Mar. 13, 2012, 8 pages.
- Haders, "New Controlled Release Technologies Broaden Opportunities for Ophthalmic Therapies," Drug Delivery Technology, Jul./Aug. 2009, pp. 48-53, vol. 8, No. 7.
- Ho et al., "Contact Lens With Integrated Inorganic Semiconductor Devices," MEMS 2008. IEEE 21st International Conference on. IEEE, 2008., pp. 403-406.
- Holloway, "Microsoft developing electronic contact lens to monitor blood sugar," Gizmag, Jan. 5, 2012, <http://www.gizmag.com/microsoft-electronic-diabetic-contact-lens/20987/>, Last accessed Mar. 13, 2012, 5 pages.
- Lähdesmäki et al., "Possibilities for Continuous Glucose Monitoring by a Functional Contact Lens," IEEE Instrumentation & Measurement Magazine, Jun. 2010, pp. 14-17.
- Lingley et al., "A contact lens with integrated micro solar cells," Microsyst Technol, 2012, pp. 453-458, vol. 18.
- Murdan, "Electro-responsive drug delivery from hydrogels," Journal of Controlled Release, 2003, pp. 1-17, vol. 92.
- Parviz, Babak A., "For Your Eyes Only," IEEE Spectrum, Sep. 2009, pp. 36-41.
- Saeedi, E. et al., "Self-assembled crystalline semiconductor optoelectronics on glass and plastic," J. Micromech. Microeng., 2008, pp. 1-7, vol. 18.
- Saeedi et al., "Self-Assembled Inorganic Micro-Display on Plastic," Micro Electro Mechanical Systems, 2007. MEMS. IEEE 20th International Conference on. IEEE, 2007., pp. 755-758.
- Sensimed Triggerfish, Sensimed Brochure, 2010, 10 pages.
- Shih, Yi-Chun et al., "An Inductorless DC-DC Converter for Energy Harvesting With a 1.2- μ W Bandgap-Referenced Output Controller," IEEE Transactions on Circuits and Systems—II: Express Briefs, Dec. 2011, pp. 832-836, vol. 58, No. 12.
- Shum et al., "Functional modular contact lens," Proc. of SPIE, 2009, pp. 73970K-1 to 73970K-8, vol. 7397.
- Singh, et al., "Novel Approaches in Formulation and Drug Delivery using Contact Lenses," Journal of Basic and Clinical Pharmacy, May 2011, pp. 87-101, vol. 2, Issue 2.
- Stauth et al., "Self-assembled single-crystal silicon circuits on plastic," PNAS, Sep. 19, 2006, pp. 13922-13927, vol. 103, No. 38.
- Yao, H. et al., "A contact lens with integrated telecommunication circuit and sensors for wireless and continuous tear glucose monitoring," J. Micromech. Microeng., 2012, pp. 1-10, vol. 22.
- Yao, H. et al., "A Dual Microsocal Glucose Sensor on a Contact Lens, Tested in Conditions Mimicking the Eye," Micro Electro Mechanical Systems (MEMS), 2011 IEEE 24th International Conference on. IEEE, 2011, pp. 25-28.
- Yao et al., "A contact lens with embedded sensor for monitoring tear glucose level," Biosensors and Bioelectronics, 2011, pp. 3290-3296, vol. 26.

(56)

References Cited

OTHER PUBLICATIONS

Yao, H. et al., "A Soft Hydrogel Contact Lens with an Encapsulated Sensor for Tear Glucose Monitoring," Micro Electro Mechanical Systems (MEMS), 2012 IEEE 25th International Conference on. IEEE, 2012, pp. 769-772.

Yeager et al., "A 9 μ A, Addressable Gen2 Sensor Tag for Biosignal Acquisition," IEEE Journal of Solid-State Circuits, Oct. 2010, pp. 2198-2209, vol. 45, No. 10.

Zhang et al., "Design for Ultra-Low Power Biopotential Amplifiers for Biosignal Acquisition Applications," IEEE Transactions on Biomedical Circuits and Systems, 2012, pp. 344-355, vol. 6, No. 4.

* cited by examiner

100




FIG. 1

200




FIG. 2

300




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

CONTACT LENS EMPLOYING OPTICAL SIGNALS FOR POWER AND/OR COMMUNICATION

TECHNICAL FIELD

This disclosure generally relates to a contact lens employing optical signals for power and/or communication.

SUMMARY

Apparatus, systems and methods disclosed herein relate to contact lenses employing optical signals for power and/or communication. In one or more aspects, a contact lens can include: a substrate that forms at least a portion of the body of the contact lens; an optical communication device disposed on or within the substrate; and a photodetector disposed on or within the substrate, wherein the photodetector harvests light emitted from a device and generates power from the harvested light, wherein the device is located external to the contact lens.

In one or more aspects, the disclosed subject matter relates to a system. The system can include: a contact lens and a device. The contact lens can include: a substrate; and a circuit disposed on or within the substrate. The circuit can include: one or more sensors that sense a feature of a wearer of the contact lens; a communication component that outputs information indicative of the sensed feature from the contact lens; a processor that processes the information indicative of the sensed feature; and one or more light sensors that sense light and power at least one of the component or the processor, based, at least, on the sensed light, wherein the component outputs the information in response to the sensed light. The device can have a transmitter that emits the light sensed by the one or more light sensors.

DESCRIPTION OF THE DRAWINGS

FIGS. 1, 2 and 3 are illustrations of diagrams of exemplary non-limiting systems that facilitate contact lenses employing optical signals for power and/or communication in accordance with aspects described herein.

FIG. 4 is an illustration of a block diagram of a tag for a contact lens facilitating optical communication in accordance with aspects described herein.

FIGS. 5, 6 and 7 are exemplary flow diagrams of methods that facilitate contact lenses employing optical signals for power and/or communication in accordance with aspects described herein.

FIG. 8 is an illustration of a schematic diagram of an exemplary networked or distributed computing environment with which one or more aspects described herein can be associated.

FIG. 9 is an illustration of a schematic diagram of an exemplary computing environment with which one or more aspects described herein can be associated.

DETAILED DESCRIPTION

Various aspects are now described with reference to the drawings, wherein like reference numerals are used to refer to like elements throughout. In the following description, for purposes of explanation, numerous specific details are set forth in order to provide a more thorough understanding of one or more aspects. It is to be evident, however, that such aspects can be practiced without these specific details. In

other instances, structures and devices are shown in block diagram form in order to facilitate describing one or more aspects.

As used in this application, the terms “component,” “component,” “system,” and the like are intended to refer to a computer-related entity, either hardware, software, firmware, a combination of hardware and software, software and/or software in execution. For example, a component can be, but is not limited to being, a process running on a processor, a processor, an object, an executable, a thread of execution, a program, and/or a computer. By way of illustration, both an application running on a computing device and/or the computing device can be a component. One or more components can reside within a process and/or thread of execution and a component can be localized on one computer and/or distributed between two or more computers. In addition, these components can execute from various computer-readable storage media having various data structures stored thereon. The components can communicate by way of local and/or remote processes such as in accordance with a signal having one or more data packets (e.g., data from one component interacting with another component in a local system, distributed system, and/or across a network such as the Internet with other systems by way of the signal).

The word “exemplary” is used herein to mean serving as an example, instance, or illustration. For the avoidance of doubt, the subject matter disclosed herein is not limited by such examples. In addition, any aspect or design described in this disclosure as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects or designs, nor is it meant to preclude equivalent exemplary structures and techniques known to those of ordinary skill in the art. Furthermore, to the extent that the terms “includes,” “has,” “contains,” and other similar words are used in either the detailed description or the claims, for the avoidance of doubt, such terms are intended to be inclusive in a manner similar to the term “comprising” as an open transition word without precluding any additional or other elements.

It is to be appreciated that in accordance with one or more aspects described in this disclosure, users can opt-in or opt-out of providing personal information, demographic information, location information, proprietary information, sensitive information, or the like in connection with data gathering aspects. Moreover, one or more aspects described herein can provide for anonymizing collected, received, or transmitted data.

Active contact lens systems generally do not include an on-board energy source due to space and power limitations on the contact lens. Accordingly, RF harvesting and corresponding backscatter can be used for powering the contact lens and, in some cases, communicating with the contact lens. However, specialized and dedicated RF electronics would typically be required to facilitate RF power and communication; and such electronics can be complex and expensive.

Optical communication is a form of telecommunication that employs light as a transmission medium. Optical signals can be advantageous for enabling power generation and/or communication on a small-scale, such as those areas typically required for active contact lenses. A light transmitter can emit a light signal, which can be received by a light detector.

Micro-fabrication techniques can be employed to provide components that can receive and/or transmit light from or to the contact lens. For example, optical waveguides can be designed and fabricated that incorporate two-dimensional (2-D) photonic crystal geometry for lateral confinement of light, and total internal reflection for vertical confinement. Square, triangular or other suitable photonic crystal lattices

can be utilized. In an aspect, a three-dimensional (3-D) finite-difference time-domain (FDTD) can be used to find design parameters of the photonic crystal and to calculate dispersion relations for guided modes in a waveguide structure. In an aspect, the waveguides can be fabricated so as to improve confinement in a particular direction and symmetry properties of the structure. High-resolution fabrication can provide for different types of bends and optical cavities within the waveguides. The optical waveguides can facilitate directing light to and from components of the contact lens, and facilitate mitigation of losses associated with dispersion of light.

Sensors can be employed on the contact lens to facilitate power generation from light. Photodetectors are one such type of sensor that can facilitate power generation. Photodetectors are typically made of a photodiode and circuitry that outputs a current in response to detected light. These types of detectors can harvest light emitted from the light source and generate power from the harvested light.

Optical communication devices (e.g., reflectors, light-emitting diodes (LEDs)) that utilize light can be employed to communicate in response to light received. Communication can be performed by modulation of optical data back to a receiver. For example, a modulating retro-reflector (MRR) system can modulate received light (thereby changing the intensity of the light) and reflect the received light back to a light source. Any number of well-known optical modulation techniques can be employed. Additionally, the small-scale of the MRR system can facilitate on-board power savings up to an order of magnitude over the power consumption of typical RF systems.

Multiple optical transmitters can be situated on the contact lens and multiplex and/or modulate multiple optical signals (e.g., using different sources as well as different colors, or wavelength frequencies) in order to enhance encoding of data (e.g., data sensed on the contact lens). For example, optical signals can be modulated with data whereby the modulation type is a function of the data being transmitted.

Further, an optical add-drop multiplexing device can multiplex different sources of light for transmission from the contact lens. In this case, more than one modulated light signal is transmitted on the same carrier, or channel. Different channels can be encoded with the same or different data, and multiplexed prior to transmission.

Apparatus, systems and methods disclosed herein relate to contact lenses employing optical signals for power and/or communication. In one or more aspects, a contact lens can include: a substrate that forms at least a portion of the body of the contact lens; an optical communication device disposed on or within the substrate; and a photodetector disposed on or within the substrate, wherein the photodetector harvests light emitted from a device and generates power from the harvested light, wherein the device is located external to the contact lens.

In one or more aspects, the disclosed subject matter relates to a system. The system can include: a contact lens and a device. The contact lens can include: a substrate; and a circuit disposed on or within the substrate. The circuit can include: one or more sensors that sense a feature of a wearer of the contact lens; a communication component that outputs information indicative of the sensed feature from the contact lens; a processor that processes the information indicative of the sensed feature; and one or more light sensors that sense light and power at least one of the component or the processor, based, at least, on the sensed light, wherein the component outputs the information in response to the sensed light. The device can have a transmitter that emits the light sensed by the one or more light sensors.

One or more aspects of the apparatus, systems and/or methods described herein can advantageously employ optical signals for power and/or communication on a contact lens. Accordingly, the aspects can reduce the space typically employed for components on the contact lens that utilize RF components for power and/or communication.

FIGS. 1, 2 and 3 are illustrations of diagrams of exemplary non-limiting systems that facilitate contact lenses employing optical signals for power and/or communication in accordance with aspects described herein.

Turning first to FIG. 1, system 100 can include a contact lens 102 and a device 116. The contact lens 102 can include a substrate 104, a photodetector 106, a sensor 108, an optical communication device 110, a microprocessor 112 and/or memory 113. In various aspects, one or more of the photodetector 106, sensor 108, optical communication device 110, microprocessor 112 and/or memory 113 can be optically, electrically and/or communicatively coupled to one another to perform one or more of the functions (e.g., generating power, sensing, communication) of the contact lens 102.

In some aspects, the substrate 104 can form at least a portion of the body of the contact lens 102. The substrate 104 can be flexible or semi-rigid in various aspects. Further, the substrate 104 can be transparent or translucent in various aspects.

In various aspects, the photodetector 106 can be any number of components that can detect and receive light. By way of example, but not limitation, the photodetector 106 can be a photovoltaic cell or a solar cell.

The photodetector 106 can be disposed on or within the substrate 104 in various aspects. For example, in some aspects, the photodetector 106 can be encapsulated within the substrate 104 while, in other aspects, the photodetector 106 is disposed on the surface of the substrate 104 or embedded within the surface of the substrate 104.

The photodetector 106 can harvest optical signals emitted from the device 116 and generate power from the harvested optical signals. For example, the photovoltaic cells or solar cells can receive the optical signals wirelessly. The received optical signals can be harvested, and power can be subsequently generated for use by the contact lens 102.

In various aspects, the photodetector 106 can detect modulated optical signals from the device 116 to receive data from the device 116. For example, the optical signals can be modulated with data in some embodiments. In these embodiments, the contact lens 102 can include circuitry that demodulates the optical signal. Upon receipt of the modulated optical signal, the contact lens 102 can demodulate the received optical signal and extract the data with which the optical signal is modulated. The data with which the optical signal is modulated can include, but is not limited to, data for adjustment of various parameters of the components of the contact lens 102, data to be stored in the memory 113 or the like.

In various aspects, irrespective of whether the optical signal is modulated with data, the optical signal 124 received can be employed, power can be generated from the receipt of the optical signal, and the power can be employed to power the sensor 108 of the contact lens 102.

The sensor 108 can sense one or more features of the wearer of the contact lens 102. For example, the sensor 108 can sense any number of biological features of the wearer of the contact lens 102 including, but not limited to, glucose, lactate or urea levels, internal body temperature and/or blood alcohol content of the wearer of the contact lens 102 as described in further detail below.

For example, in some aspects, the sensor 108 can detect fluid on the substrate 104 from the eye of the wearer of the

contact lens **102**. The sensor **108** can sense level of glucose, lactate and/or urea in the fluid. In some embodiments, the contact lens **102** can include circuitry for evaluating the level of the substance in the fluid. In some embodiments, the contact lens **102** can include circuitry for outputting the sensed information to a reader. In either aspect, the level of the biological matter can be compared to a threshold. A determination can be made as to whether the level is too high or too low based on the level detected.

In another aspect, retinal analysis of a user can be performed and an optical signal transmitted in response to an authentication request.

As another example, the fluid on the substrate **104** can be a particular temperature. The temperature of the fluid can be indicative of the internal temperature of the wearer of the contact lens **102**. The sensor **108** can be a temperature sensor that can sense the temperature of the fluid. For example, in some embodiments, the sensor **108** can be a resistance thermometer that detects the temperature based on an increase in resistance (which occurs with a rise in temperature) or a decrease in resistance (which occurs with a decrease in temperature). The sensor **108** can be employed in connection with a thermistor in some embodiments. As another example, the sensor **108** can sense a blood alcohol content of the wearer of the contact lens **102**. In particular, the sensor **108** can detect the fluid incident on the substrate **104**. For example, the tear film on the eye can be incident on the contact lens **102**. The alcohol concentration in the tear film can be sensed by sensor **108**.

In some aspects, the sensor **108** can sense one or more features in an environment outside of the wearer of the contact lens **102**. For example, the sensor **108** can sense any number of biological, chemical and/or microbiological features in an environment including, but not limited to, levels of hazardous materials, levels of allergens, the presence of various organisms or species or the like. For example, in various embodiments, the sensor **108** can sense a level of one or more different allergens (e.g., tree or grass pollen, pet dander, dust mite excretions) in the environment.

While the aspect shown illustrates a single sensor **108**, in various aspects, any number of sensors can be disposed on or within the substrate **104**. Further, the one or more sensors can be disposed in any number of configurations for sensing the features described herein. By way of example, but not limitation, the one or more sensors can be disposed in a circular or semi-circular configuration around the periphery of the contact lens **102**.

The optical communication device **110** can be disposed on or within the substrate **104**. In various aspects, the optical communication device **110** can be or include a light-emitting diode (LED) or a reflector. The LED and/or reflector can modulate in one or more different patterns to communicate specific information about the sensed features to a reader or to the device **116**. The reader or device **116** can be configured with components that are programmed to correlate particular modulated patterns with specific information and, as such, can determine the information based upon receipt of the pattern.

In various aspects, the contact lens **102** can include a communication device (not shown) that can output information (e.g., sensed features, information associated with sensed biological or chemical materials, information associated with internal temperature and/or blood alcohol concentration in the tear film of the eye) from the contact lens **102**. In some aspects, the contact lens **102** can include the communication

device in addition to or in lieu of the optical communication device **110**. The communication device can be optically-powered in various aspects.

The microprocessor **112** can include logic circuitry that can cause one or more components of the contact lens **102** to perform one or more functions and/or that can perform one or more functions of the contact lens **102**. For example, the microprocessor **112** can cause one or more of the power generation, sensing and/or communication functions to be performed via the contact lens **102**. In some aspects, the microprocessor **112** can employ computer-executable instructions and/or information stored in the memory **113** to perform the functions (or to cause the functions to be performed).

The memory **113** can include a computer-readable storage medium storing computer-executable instructions and/or information for performing the functions described in this disclosure with reference to the contact lens **102**. In various aspects, the memory **113** can store information including, but not limited to, the sensed features (or information indicative thereof) or data received via the optical signal (e.g., data with which the optical signal is modulated).

Accordingly, in summary, in some aspects, the photodetector **106** can receive an optical signal, the sensor **108** can be powered by power generated from the optical signal and the sensor **108** can output the sensed information. The optical communication device **110** can modulate in a particular pattern in a manner dictated by the output sensed information. As such, the modulation can be according to the particular sensed information sensed by the sensor **108**. The device **116** can receive the modulated signal generated by the optical communication device **110** and determine the information sensed by the sensor **108** based on the modulated signal received.

Although not shown, in various aspects, the contact lens **102** can include structure and/or functionality to convert the optical signal to an electrical signal. For example, in some aspects, the contact lens **102** can include a photodiode that converts optical signals to electrical current or voltage. The electrical signal can be employed to power one or more components of the contact lens **102** in various aspects.

Although also not shown, in various aspects, the contact lens **102** can include structure and/or functionality to receive and/or decode infrared (IR) light.

Turning now to the device **116**, in lieu of or in addition to receiving a modulated signal, in some aspects, the device **116** can include a light source **118** that can generate light. For example, the device **116** can generate light, in particular, or an optical signal, generally (e.g., a flash of a camera). The optical signal **124** can be emitted from an optical-signal emitting component **122** of the device **116** in various aspects. In some aspects, the optical-signal emitting component **122** can be a component that generates a flash in a camera, for example.

In some aspects, the device **116** can be positioned within a particular proximity to the contact lens **102** prior to generating the optical signal such that the optical signal **124** emitted from the device is received by the contact lens **102**. For example, the device **116** can be within one to two feet of the contact lens **102** when the optical signal is generated. As such, the photovoltaic cells and/or solar cells can receive the optical signal and convert the signal to power the components (e.g., the one or more sensors).

In some aspects, as described above, the device **116** can also be adapted to receive the modulated signal from the optical communication device **110**. For example, the device **116** can receive the modulated signal at optical-signal receiving component **120** of the device **116**. Optical-signal receiving component **120** can be any number of different types of

receivers that can receive optical signals. The device **116** can determine the information received based on the modulated signal generated by the optical communication device **110**.

In various aspects, the device **116** can be or include any of a number of different devices having hardware and/or software that transmits and/or receives an optical signal. In some aspects, the hardware that generates and/or transmits the optical signal can be general purpose hardware that currently exists on a mobile phone or camera. For example, in some aspects, the hardware can be hardware that generates a flash that is emitted from a camera with a flash feature or from a mobile phone (or other device) having a camera with a flash feature. In these aspects, the flash feature can function as an optical transmitter while the camera lens can function as an optical receiver.

Turning now to FIG. 2, another system that facilitates contact lenses employing optical signals for power and/or communication is shown. System **200** can include contact lens **102**, a light source **216** and a reader **222**.

The light source **216** can be any number of sources that can generate light (or optical signals generally). By way of example, but not limitation, the light source **216** can be the sun, a source of low-level background light or a device having an optical-signal emitting component such as one above embodiment of device **116** described with reference to FIG. 1. The light source **216** can emit an optical signal **218, 220** that can be received by the contact lens **102**. For example, the optical signal **218, 220** can be received by the photodetector **106** as described above with reference to FIG. 1.

The reader **222** can be adapted to receive the modulated signal from the optical communication device **110**. For example, the reader **222** can receive the modulated signal at optical-signal receiving component **224** of the reader **222**. Optical-signal receiving component **224** can be any number of different types of receivers that can receive and/or sense optical signals. In some aspects, for example, the optical-signal receiving component **224** can include an optical demodulator that is configured to demodulate the modulated signal. The reader **222** can determine the information received based on the pattern with which the signal is modulated by the optical communication device **110**.

In some aspects, the contact lens can include the structure and/or function described with reference to FIG. 1. In some aspects, the contact lens **102** can receive optical signal **218, 220** emitted from light source **216** and can output an optical signal **114, 226** to reader **222**. For example, the optical communication device **110** can output the optical signal **114, 226** to the reader **222** in response to the output from the sensor **108**. The sensor **108** can be powered optically via the optical signal **218, 220** received from the light source **216** as described with reference to FIG. 1.

Accordingly, in various aspects, the contact lens **102** can receive an optical signal **218, 220** from a first source (e.g., light source **216**) and output an optical signal **114, 226** to a second source (e.g., reader **222**).

Turning now to FIG. 3, another system that facilitates contact lenses employing optical signals for power and/or communication is shown. System **300** can include contact lens **102** and device **316**.

The device **316** can be any suitable device that can encode an optical signal **324** with data, and output the optical signal **324**. In some aspects, the device **316** can include a data encoder **320** that can encode the optical signal **324**, and a light source **318** that can emit the optical signal **324** encoded with the data.

In various aspects, the optical signal **324** can be encoded with data at a rate high enough to avoid detection by the

human eye and/or brain. For example, in some aspects, the optical signal **324** can be encoded with data at a rate of 100 bits per second (bps) or greater.

In various aspects, the data can include instructions or information for storage in the memory **113**. For example, the data can include instructions for particular features to be sensed by the sensor **108**.

The optical signal **324** can be output from the component **322** in some aspects. The optical signal **324** can be received by the contact lens **102**. For example, the optical signal **218, 220** can be received by the photodetector **106**.

The component **326** can be adapted to receive the modulated signal from the optical communication device **110**. Component **326** can be any number of different types of receivers that can receive and/or sense optical signals. The component **326** can determine the information received based on the modulated signal generated by the optical communication device **110**. In various aspects, the component **326** can be or include any of a number of different devices having hardware and/or software that transmits and receives an optical signal.

In various aspects, the contact lens can include the structure and/or function described with reference to FIG. 1. In some aspects, the contact lens **102** can receive optical signal **218, 220** emitted from device **316** and can output an optical signal **114** to the device **316**. The optical signal **114** can be output from the optical communication device **110** in some aspects. The optical communication device **110** can output the optical signal **114** to the device **316** in response to the output from the sensor **108**. The sensor **108** can be powered optically via the optical signal **324** received from the device **316**.

While not shown, in other aspects, the systems described herein can include those having contact lens **102**, a reader (e.g., reader **222**) and/or any device able to emit light (or an optical signal generally).

While not shown, the contact lens can include structure and/or functionality for multi-modal operation. In some aspects, multi-modal operation can mean operating intermittently between RF and optical power modes and/or RF and optical communication modes. For example, in some aspects, the contact lens can employ RF-based power and/or communication and, in other instances, the contact lens can employ optical-based power and/or communication. As another example, optical power and RF communication can be employed. For example, in some aspects, the contact lens can harvest optical energy to power the optical communication device on the contact lens, and harvest RF energy to power an RF device on the contact lens. For example, an RF device can communicate via RF reflection, or backscatter.

FIG. 4 is an illustration of a block diagram of a tag for a contact lens facilitating optical communication in accordance with aspects described herein. The tag **400** can be disposed on or within the contact lens in various aspects.

The tag **400** can include or be associated with a circuit **402** disposed on or within the tag **400**. In some aspects, the circuit **402** can include an optical communication device **404**, a photodetector **406**, a sensor **408**, a memory **410** and/or a microprocessor **412**. In various aspects, the optical communication device **404**, photodetector **406**, sensor **408**, memory **410** and/or microprocessor **412** can be optically, electrically and/or communicatively coupled to one another to perform one or more functions of the tag **400**. As such, in some aspects, the tag **400** can be configured to have a level of porosity such that fluids incident on the contact lens can be detected and sensing can be performed by the sensor **408**. In

some aspects, the tag **400** can be transparent or translucent such that the photodetector **406** can receive light for power generation.

In some aspects, the tag **400** can include information identifying the wearer of the contact lens, information stored and/or detailing features of the wearer of the contact lens or the like.

In some aspects, the tag **400** can be associated with an item (e.g., item of merchandise) and/or can be interrogated by a device (e.g., device **116**, device **316**, reader **222**) for merchandising and/or inventory purposes.

For example, in some aspects, a light source can be associated with or coupled to an item of merchandise. The optical signal can be received by the photodetector **406** to power the components of the tag **400**, and the tag **400** can output information via the optical communication device **404**. The information output by the tag **400** can be communicated via modulation of the optical communication device **404** as described in one or more of the embodiments.

In some aspects, the light source associated with or coupled to the item of merchandise can transmit information about the item to the tag **400** (e.g., by modulating the optical signal with data about the merchandise). For example, the tag **400** can receive information detailing electronic coupons, pricing, warranty information or the like. The information can be received by and/or stored at the memory **410** of the tag **400**.

In some aspects, an interrogator (e.g., device **116**, device **316**, reader **222**) at a point of sale can output an optical signal that can cause the tag **400** to responsively output information related to the merchandise. For example, the tag **400** can respond with information indicative of an electronic coupon for the item of merchandise. For example, the interrogator can be operated by a cashier or other point of sale personnel to cause the tag **400** to output an optical signal detailing the terms of the coupon (in response to the tag **400** of the contact lens receiving an optical signal from the interrogator).

In various aspects, the components of the circuit **402** can include the structure and/or functionality of the corresponding components of the contact lens **102** described with reference to FIG. 1. For example, the photodetector **406** can include the structure and/or functionality of photodetector **106** described with reference to FIG. 1.

FIGS. 5, 6 and 7 are exemplary flow diagrams of methods that facilitate contact lenses employing optical signals for power and/or communication in accordance with aspects described herein.

Turning first to FIG. 5, at **502**, method **500** can include receiving, at the contact lens, light (or an optical signal, generally) emitted from a device (e.g., using the contact lens **102** or the photodetector **106**).

In various aspects, the optical signal can be of a wavelength that is invisible or visible to the human eye. For example, the light can be invisible (e.g., IR light) or other light that is invisible to the human eye but that is detectable by the photodetector or other detector (not shown) on the contact lens **102**. For example, while not shown, the systems described herein can include those having a device able to emit IR light signals and a contact lens able to receive and decode IR light signals. The device can include circuitry (e.g., IR transmitter, LED) to emit pulses of IR light. The contact lens can include a receiver that can receive and decode the IR light. The microprocessor of the contact lens can decode data encoded in the IR light in some aspects. In these aspects, the contact lens can perform one or more functions based on the decoded data.

As another example, the light received could be visible light (e.g., a flash from a camera). As another example, the light can be low-level background light or ambient light.

As another example, the light can be modulated with data. The rate at which the light is modulated with the data can be approximately 100 bits per second (bps) or greater. In various aspects, the data with which the light is modulated can include information that can be stored at the contact lens. In various aspects, the data with which the light is modulated can include information that can be employed by the contact lens for one or more functions. For example, the data can be information identifying features for sensing by the sensor of the contact lens and/or information identifying a query for information (e.g., biographical information) to be output from the contact lens.

At **504**, method **500** can include generating power based, at least, on the light received (e.g., using the photodetector **106**). In various aspects, the power can be harvested by the photodetector and employed to power the sensor on the contact lens. As such, an optical signal can be employed for powering the contact lens.

At **506**, method **500** can include outputting the power to one or more sensors that sense a feature of a wearer of the contact lens (e.g., using the photodetector **106**).

At **508**, method **500** can include sensing the feature of the wearer of the contact lens (e.g., using the sensor **108**). The feature can include, but is not limited to, a biological and/or chemical feature of the wearer of the contact lens. In some aspects, although not shown, the method **500** can include sensing a feature of an environment outside of a wearer of the contact lens.

For example, the sensor **108** can sense any number of biological features of the wearer of the contact lens including, but not limited to, glucose, lactate or urea levels, internal body temperature and/or blood alcohol content of the wearer of the contact lens as described in further detail below.

For example, in some aspects, the sensor **108** can detect a fluid on the contact lens output from the eye of the wearer of the contact lens. The sensor **108** can sense a level of glucose, lactate and/or urea in the fluid. In some embodiments, the contact lens can include circuitry for evaluating the level of the substance in the fluid. In some embodiments, the contact lens can include circuitry for outputting the sensed information to a reader. In either aspect, the level of the biological matter can be compared to a threshold. A determination can be made as to whether the level is too high or too low based on the level detected.

As another example, the fluid on the contact lens can be a particular temperature. The temperature of the fluid can be indicative of the internal temperature of the wearer of the contact lens. The sensor **108** can be a temperature sensor that can sense the temperature of the fluid. For example, in some embodiments, the sensor **108** can be a resistance thermometer that detects the temperature based on an increase in resistance (which occurs with a rise in temperature) or a decrease in resistance (which occurs with a decrease in temperature). The sensor **108** can be employed in connection with a thermistor in some embodiments. As another example, the sensor **108** can sense a blood alcohol content of the wearer of the contact lens. In particular, the sensor **108** can detect the fluid incident on the contact lens. For example, the tear film of the eye can be incident on the contact lens. The alcohol concentration in the tear film can be sensed by sensor **108**.

In some aspects, the sensor **108** can sense one or more features in an environment outside of the wearer of the contact lens. For example, the sensor **108** can sense any number of biological, chemical and/or microbiological features in an environment including, but not limited to, levels of hazardous materials, levels of allergens, the presence of various organisms or species or the like. For example, in various embodi-

ments, the sensor **108** can sense a level of one or more different allergens (e.g., tree or grass pollen, pet dander, dust mite excretions) in the environment. At **510**, method **500** can include outputting information indicative of the sensed feature (e.g., using the optical communication device **110**). In various aspects, the information can be output from the optical communication device via modulation of the optical communication device. For example, the manner in which the optical communication device is modulated can communicate the details of the information sensed.

Turning now to FIG. 6, at **602**, method **600** can include receiving, at a contact lens, from a device, an optical signal that causes an optical communication device to output information (e.g., using the photodetector **106** of the contact lens **102**). In some aspects, the device can include a light-emitting source.

At **604**, method **600** can include outputting the information to the device (e.g., using the optical communication device **110** of the contact lens **102**).

Turning now to FIG. 7, at **702**, method **700** can include receiving, at a contact lens, from a light-emitting source, an optical signal that causes an optical communication device to output information (e.g., using the photodetector **106** of the contact lens **102**).

In various aspects, the light-emitting source can be a device that emits optical signals. For example, the light-emitting source can be a camera having a component that generates a flash of light. In some aspects, the light-emitting source can be a source of ambient light (e.g., sun) or a source of low-level background light. In some aspects, the light-emitting source can also include structure for modulating the light output with data. As such, the light emitted can include data.

At **704**, method **700** can include outputting the information to a light-receiving device (e.g., using the optical communication device **110** of the contact lens **102**). In various aspects, the light-receiving device can be a device that receives and reads optical signals. In some aspects, the light-emitting source is distinct from the light-receiving device. As such, the contact lens can receive an optical signal from a first source and emit optical signals to a second source.

Exemplary Networked and Distributed Environments

FIG. 8 provides a schematic diagram of an exemplary networked or distributed computing environment with which one or more aspects described in this disclosure can be associated. The distributed computing environment includes computing objects **810**, **812**, etc. and computing objects or devices **820**, **822**, **824**, **826**, **828**, etc., which can include programs, methods, data stores, programmable logic, etc., as represented by applications **830**, **832**, **834**, **836**, **838**. It can be appreciated that computing objects **810**, **812**, etc. and computing objects or devices **820**, **822**, **824**, **826**, **828**, etc. can include different devices, such as active contact lenses (and components thereof), personal digital assistants (PDAs), audio/video devices, mobile phones, MPEG-1 Audio Layer 3 (MP3) players, personal computers, laptops, tablets, etc.

Each computing object **810**, **812**, etc. and computing objects or devices **820**, **822**, **824**, **826**, **828**, etc. can communicate with one or more other computing objects **810**, **812**, etc. and computing objects or devices **820**, **822**, **824**, **826**, **828**, etc. by way of the communications network **840**, either directly or indirectly. Even though illustrated as a single element in FIG. 8, network **840** can include other computing objects and computing devices that provide services to the system of FIG. 8, and/or can represent multiple interconnected networks, which are not shown.

In a network environment in which the communications network/bus **840** can be the Internet, the computing objects

810, **812**, etc. can be Web servers, file servers, media servers, etc. with which the client computing objects or devices **820**, **822**, **824**, **826**, **828**, etc. communicate via any of a number of known protocols, such as the hypertext transfer protocol (HTTP).

Exemplary Computing Device

As mentioned, advantageously, the techniques described in this disclosure can be associated with any suitable device. It is to be understood, therefore, that handheld, portable and other computing devices (including active contact lens having circuitry or components that compute and/or perform various functions). As described, in some aspects, the device can be the contact lens (or components of the contact lens) and/or reader described herein. In various aspects, the data store can include or be included within, any of the memory described herein, any of the contact lenses described herein and/or the RF reader described herein. In various aspects, the data store can be any repository for storing information transmitted to or received from the contact lens.

FIG. 9 illustrates an example of a suitable computing system environment **900** in which one or aspects of the aspects described in this disclosure can be implemented. Components of computer **910** can include, but are not limited to, a processing unit **920**, a system memory **930**, and a system bus **922** that couples various system components including the system memory to the processing unit **920**.

Computer **910** typically includes a variety of computer readable media and can be any available media that can be accessed by computer **910**. The system memory **930** can include computer storage media in the form of volatile and/or nonvolatile memory such as read only memory (ROM) and/or random access memory (RAM). By way of example, and not limitation, memory **930** can also include an operating system, application programs, other program components, and program data.

A user can enter commands and information into the computer **910** through input devices **940** (e.g., keyboard, keypad, a pointing device, a mouse, stylus, touchpad, touch screen, motion detector, camera, microphone or any other device that allows the user to interact with the computer **910**). A monitor or other type of display device can be also connected to the system bus **922** via an interface, such as output interface **950**. In addition to a monitor, computers can also include other peripheral output devices such as speakers and a printer, which can be connected through output interface **950**.

The computer **910** can operate in a networked or distributed environment using logical connections to one or more other remote computers, such as remote computer **980**. The remote computer **980** can be a personal computer, a server, a router, a network PC, a peer device or other common network node, or any other remote media consumption or transmission device, and can include any or all of the elements described above relative to the computer **910**. The logical connections depicted in FIG. 9 include a network **982**, such local area network (LAN) or a wide area network (WAN), but can also include other networks/buses e.g., cellular networks.

Computing devices typically include a variety of media, which can include computer-readable storage media and/or communications media, in which these two terms are used herein differently from one another as follows. Computer-readable storage media can be any available storage media that can be accessed by the computer, can be typically of a non-transitory nature, and can include both volatile and non-volatile media, removable and non-removable media. By way of example, and not limitation, computer-readable storage media can be implemented in connection with any method or technology for storage of information such as computer-read-

able instructions, program components, structured data, or unstructured data. Computer-readable storage media can include, but are not limited to, RAM, ROM, electrically erasable programmable read only memory (EEPROM), flash memory or other memory technology, or other tangible and/or non-transitory media which can be used to store desired information. Computer-readable storage media can be accessed by one or more local or remote computing devices, e.g., via access requests, queries or other data retrieval protocols, for a variety of operations with respect to the information stored by the medium. In various aspects, the computer-readable storage media can be, or be included within, the memory, contact lens (or components thereof) or reader described herein.

On the other hand, communications media typically embody computer-readable instructions, data structures, program components or other structured or unstructured data in a data signal such as a modulated data signal, e.g., a carrier wave or other transport mechanism, and includes any information delivery or transport media. The term “modulated data signal” or signals refers to a signal that has one or more of its characteristics set or changed in such a manner as to encode information in one or more signals.

It is to be understood that the aspects described in this disclosure can be implemented in hardware, software, firmware, middleware, microcode, or any combination thereof. For a hardware aspect, the processing units can be implemented within one or more application specific integrated circuits (ASICs), digital signal processors (DSPs), digital signal processing devices (DSPDs), programmable logic devices (PLDs), field programmable gate arrays (FPGAs), processors, controllers, micro-controllers, microprocessors and/or other electronic units designed to perform the functions described in this disclosure, or a combination thereof.

For a software aspect, the techniques described in this disclosure can be implemented with components or components (e.g., procedures, functions, and so on) that perform the functions described in this disclosure. The software codes can be stored in memory units and executed by processors.

What has been described above includes examples of one or more aspects. It is, of course, not possible to describe every conceivable combination of components or methodologies for purposes of describing the aforementioned aspects, but one of ordinary skill in the art can recognize that many further combinations and permutations of various aspects are possible. Accordingly, the described aspects are intended to embrace all such alterations, modifications and variations that fall within the spirit and scope of the appended claims.

Moreover, the term “or” is intended to mean an inclusive “or” rather than an exclusive “or.” That is, unless specified otherwise, or clear from the context, the phrase “X employs A or B” is intended to mean any of the natural inclusive permutations. That is, the phrase “X employs A or B” is satisfied by any of the following instances: X employs A; X employs B; or X employs both A and B. In addition, the articles “a” and “an” as used in this application and the appended claims should generally be construed to mean “one or more” unless specified otherwise or clear from the context to be directed to a singular form.

The aforementioned systems have been described with respect to interaction between several components. It can be appreciated that such systems and components can include those components or specified sub-components. Sub-components can also be implemented as components communicatively coupled to other components rather than included within parent components (hierarchical). Additionally, it is to be noted that one or more components can be combined into

a single component providing aggregate functionality. Any components described in this disclosure can also interact with one or more other components not specifically described in this disclosure but generally known by those of skill in the art.

In view of the exemplary systems described above methodologies that can be implemented in accordance with the described subject matter will be better appreciated with reference to the flowcharts of the various figures. While for purposes of simplicity of explanation, the methodologies are shown and described as a series of blocks, it is to be understood and appreciated that the claimed subject matter is not limited by the order of the blocks, as some blocks can occur in different orders and/or concurrently with other blocks from what is depicted and described in this disclosure. Where non-sequential, or branched, flow is illustrated via flowchart, it can be appreciated that various other branches, flow paths, and orders of the blocks, can be implemented which achieve the same or a similar result. Moreover, not all illustrated blocks may be required to implement the methodologies described in this disclosure after.

In addition to the various aspects described in this disclosure, it is to be understood that other similar aspects can be used or modifications and additions can be made to the described aspect(s) for performing the same or equivalent function of the corresponding aspect(s) without deviating there from. Still further, multiple processing chips or multiple devices can share the performance of one or more functions described in this disclosure, and similarly, storage can be provided across a plurality of devices. The invention is not to be limited to any single aspect, but rather can be construed in breadth, spirit and scope in accordance with the appended claims.

What is claimed is:

1. A contact lens, comprising:

a substrate of the contact lens;

an optical communication device disposed on or within the substrate, wherein the optical communication device is configured to modulate light to communicate data to a device, and wherein the device is located external to the contact lens; and

a photodetector, disposed on or within the substrate, wherein the photodetector is configured to harvest light emitted from the device and to generate power from the harvested light, and wherein the photodetector is configured to detect a modulated optical signal from the device to receive data from the device.

2. The contact lens of claim 1, wherein the optical communication device is at least one of a reflector or a light-emitting diode.

3. The contact lens of claim 1, wherein the device is a mobile telephone having a camera with a light source.

4. The contact lens of the claim 1, further comprising one or more sensors that sense one or more features associated with the wearer of the contact lens.

5. The contact lens of claim 4, wherein the one or more features comprise at least one of: biological features associated with the wearer of the contact lens or chemical features associated with an environment outside of the wearer of the contact lens.

6. The contact lens of claim 1, wherein the light has a wavelength that is invisible to a human eye.

7. The contact lens of claim 1, wherein the modulated optical signal from the device is encoded with data at a rate of at least 100 bits per second.

15

8. The contact lens of claim 1, further comprising a radio frequency (RF) antenna, wherein the contact lens provides multi-modal information output of at least one of RF power or optical power.

9. The contact lens of claim 1, further comprising a radio frequency (RF) device that communicates by backscatter. 5

10. The contact lens of claim 9, wherein the RF device is an RF antenna.

11. A system, comprising:
a device having a transmitter configured to emit light; and 10
a contact lens, comprising:
a substrate; and

a circuit, disposed on or within the substrate, the circuit comprising:

one or more sensors configured to sense a feature of a 15
wearer of the contact lens;

a communication component configured to output information indicative of the sensed feature from the contact lens;

a processor configured to process the information indicative of the sensed feature; and

16

one or more light sensors, wherein the one or light sensors are configured to (i) harvest light emitted from the device, (ii) power at least one of the communication component or the processor using the harvested light, and (iii) detect a modulated optical signal from the device to receive data from the device.

12. The system of claim 11, wherein the device further comprises a receiver configured to receive the information indicative of the sensed feature output from the communication component.

13. The system of claim 11, further comprising a reader configured to receive the information output from the communication component, wherein the reader is distinct from the device.

14. The system of claim 11, wherein the communication component comprises at least one of a reflector or a light-emitting diode.

* * * * *