



US 20150345161A1



(19) **United States**(12) **Patent Application Publication**  
**Jacobs et al.**(10) **Pub. No.: US 2015/0345161 A1**(43) **Pub. Date: Dec. 3, 2015**(54) **RECONFIGURABLE SEATING SYSTEMS,  
SEAT ASSEMBLIES FOR USE WITHIN THE  
RECONFIGURABLE SEATING SYSTEMS,  
COMPONENTS FOR USE WITHIN THE SEAT  
ASSEMBLIES AND PARTS FOR USE WITHIN  
THE COMPONENTS**

on Jun. 30, 2014, provisional application No. 62/143,079, filed on Apr. 4, 2015, provisional application No. 62/149,596, filed on Apr. 19, 2015, provisional application No. 62/159,791, filed on May 11, 2015.

**Publication Classification**(71) Applicants: **Frederick Jacobs**, Holland, MI (US);  
**Matthew Jacobs**, Holland, MI (US);  
**Terry Plumert**, Grand Haven, MI (US)(51) **Int. Cl.**  
**E04H 3/12** (2006.01)  
**A47C 1/124** (2006.01)  
**A47C 1/121** (2006.01)(72) Inventors: **Frederick Jacobs**, Holland, MI (US);  
**Matthew Jacobs**, Holland, MI (US);  
**Terry Plumert**, Grand Haven, MI (US)(52) **U.S. Cl.**  
CPC ..... **E04H 3/126** (2013.01); **A47C 1/121**  
(2013.01); **A47C 1/124** (2013.01)(21) Appl. No.: **14/728,401**(57) **ABSTRACT**(22) Filed: **Jun. 2, 2015****Related U.S. Application Data**

(60) Provisional application No. 62/006,363, filed on Jun. 2, 2014, provisional application No. 62/018,854, filed

A reconfigurable seating system may include a bank of seating units disposed in rows. Associated chairs may be arranged in the seating units, supported on support beams by chair brackets. The reconfigurable seating systems may be installed on flat floors or sloped floors and may be arranged in linear-rows and/or arched-row configurations.






FIG. 1A




FIG. 1B





FIG. 1C







FIG. 1E






FIG. 1G



100h




FIG. 1H

100j







Fig. 15










FIG. 5C

FIG. 5B

FIG. 5A




Fig. 6A




FIG. 6B






FIG. 6C




Fig. 7








FIG. 8











4. 12






1300b



**Fig. 13B**






FIG. 13D




FIG. 14






FIG. 15











FIG. 18












Fig. 21






Fig. 24A




Fig. 24B




Fig. 24C




Fig. 25A




Fig. 25B




Fig. 25C






Fig. 25D

**RECONFIGURABLE SEATING SYSTEMS,  
SEAT ASSEMBLIES FOR USE WITHIN THE  
RECONFIGURABLE SEATING SYSTEMS,  
COMPONENTS FOR USE WITHIN THE SEAT  
ASSEMBLIES AND PARTS FOR USE WITHIN  
THE COMPONENTS**

**CROSS REFERENCE TO RELATED  
APPLICATIONS**

**[0001]** The present application claims the benefit of priority under 35 U.S.C. §119, to U.S. provisional patent applications Ser. No. 62/006,363, entitled RECONFIGURABLE SEATING SYSTEMS, SEAT ASSEMBLIES FOR USE WITHIN THE RECONFIGURABLE SEATING SYSTEMS, COMPONENTS FOR USE WITHIN THE SEAT ASSEMBLIES AND PARTS FOR USE WITHIN THE COMPONENTS, as filed on Jun. 2, 2014; Ser. No. 62/018,854, entitled BEAM MOUNTED CHAIR ASSEMBLIES, CHAIR ASSEMBLIES FOR USE WITHIN THE BEAM MOUNTED CHAIR ASSEMBLIES, COMPONENTS FOR USE WITHIN THE CHAIR ASSEMBLIES AND PARTS FOR USE WITHIN THE COMPONENTS, as filed on Jun. 30, 2014; Ser. No. 62/143,079, entitled POWERED CHAIRS FOR PUBLIC VENUES, ASSEMBLIES FOR USE IN POWERED CHAIRS, AND COMPONENTS FOR USE IN ASSEMBLIES FOR USE IN POWERED CHAIRS, as filed on Apr. 4, 2015; Ser. No. 62/149,596, entitled POWERED CHAIRS FOR PUBLIC VENUES, ASSEMBLIES FOR USE IN POWERED CHAIRS, AND COMPONENTS FOR USE IN ASSEMBLIES FOR USE IN POWERED CHAIRS, as filed on Apr. 19, 2015; Ser. No. 62/159,791, entitled POWERED CHAIRS FOR PUBLIC VENUES, ASSEMBLIES FOR USE IN POWERED CHAIRS, AND COMPONENTS FOR USE IN ASSEMBLIES FOR USE IN POWERED CHAIRS, as filed on May 11, 2015; the disclosures of which are incorporated herein in their entireties by reference.

**[0002]** The present disclosure relates to commonly assigned provisional patent applications Ser. No. 61/856,013, entitled TELESCOPIC SEATING SYSTEMS, AND FOLDABLE CHAIRS AND RELATED COMPONENTS FOR USE WITHIN TELESCOPIC SEATING SYSTEMS, filed Jul. 18, 2013; Ser. No. 61/868,547, entitled TELESCOPIC SEATING SYSTEMS, AND FOLDABLE CHAIRS AND RELATED COMPONENTS FOR USE WITHIN TELESCOPIC SEATING SYSTEMS, filed Aug. 21, 2013; and Ser. No. 61/946,824, entitled ROCKER STYLE CHAIRS, MODULAR COMPONENTS FOR USE WITHIN ROCKER STYLE CHAIRS AND PARTS FOR USE WITHIN THE MODULAR COMPONENTS, filed Mar. 2, 2014; and U.S. patent applications Ser. No. 14/465,791, entitled TELESCOPIC SEATING SYSTEMS, AND FOLDABLE CHAIRS AND RELATED COMPONENTS FOR USE WITHIN TELESCOPIC SEATING SYSTEMS, filed Aug. 11, 2014; and Ser. No. 14/636,045, entitled ROCKER STYLE CHAIRS, MODULAR COMPONENTS FOR USE WITHIN ROCKER STYLE CHAIRS AND PARTS FOR USE WITHIN THE MODULAR COMPONENTS, filed Mar. 2, 2015, the disclosures of which are incorporated herein in their entireties by reference.

**FIELD OF THE INVENTION**

**[0003]** The present disclosure relates to reconfigurable seating assemblies. More particularly, the present disclosure

relates to reconfigurable seating for auditoriums, cinemas, concert halls, arenas, gymnasiums, theaters and various other venues, and to seat assemblies for use within the reconfigurable seating systems, components for use within the seat assemblies and parts for use within the components.

**BACKGROUND OF THE INVENTION**

**[0004]** In the past, buildings such as cinemas, theaters, concert halls, arenas and other areas of public entertainment have been provided with seating which is permanently fixed to the floor. Indeed, related building codes require that venues, having more than 200 seats, incorporate anchors that secure the seats in place.

**[0005]** More recently there has been a tendency for such buildings to serve more than one purpose. For example, a building for public entertainment may be required, on one occasion, to serve as a sports hall, and on another occasion to serve as a concert hall or theatre. Similarly, seating arrangements in concert halls, theatres or arenas may need to be reconfigurable to suit the requirements of a particular production being staged.

**[0006]** Tiered seating systems have been devised which, when not in use, can be folded or otherwise collapsed against a wall of the building in which they are situated (e.g. telescopic seating systems such as those disclosed in commonly assigned patent applications Ser. No. 61/856,013, entitled Telescopic Seating Systems, and Foldable Chairs and Related Components for use within Telescopic Seating Systems, filed Jul. 18, 2013 and Ser. No. 61/868,547, entitled Telescopic Seating Systems, and Foldable Chairs and Related Components for use within Telescopic Seating Systems, filed Aug. 21, 2013), thus freeing the floor area for other purposes. However, there has, so far, been no satisfactory solution to the problem of installing reconfigurable seating on a sloped floor.

**[0007]** Seating for an audience in a public building or arena must comply with statutory regulations. These regulations are principally intended to ensure that the building or arena can be evacuated rapidly in the event of an emergency. Thus, there is a minimum spacing which must be observed between adjacent rows of seats, and provision must be made for preventing the rows of seats from moving relatively to one another in a way which would reduce the spacing below this minimum. Also, adjacent seats in a row must be secured together to ensure that they cannot move independently when in use.

**[0008]** One way of meeting the statutory requirements is to secure the seats individually to the floor, but this is unsatisfactory. However, installation and removal of the seats are very time consuming when the individual chairs are secured to the floor. Furthermore, it is not acceptable for the seats to be individually fastened to the floor when the condition of the floor is important, for example if the floor is to be used, on other occasions, as a dance floor or a playing surface for sports.

**SUMMARY**

**[0009]** A reconfigurable seating system may include at least one seating unit having at least two mounting feet, at least two floor plates, wherein a first one of the at least two floor plates includes at least one first mounting foot receptacle for releasably receiving a first mounting foot of the at least two mounting feet, wherein a second one of the at least two floor plates includes at least one second mounting foot receptacle for releasably receiving a second mounting foot of the at

least two mounting feet, and wherein the at least one seating unit is adjustable between a flat floor orientation and a sloped floor orientation, and at least one floor plate attachment, wherein the at least one floor plate attachment is configured to secure the at least one seating unit, to an associated floor, in a predetermined located.

**[0010]** In another embodiment, a reconfigurable seating system may include at least one seating unit having at least two mounting feet, at least two floor plates, wherein a first one of the at least two floor plates includes at least one first mounting foot receptacle for releasably receiving a first mounting foot of the at least two mounting feet, wherein a second one of the at least two floor plates includes at least one second mounting foot receptacle for releasably receiving a second mounting foot of the at least two mounting feet, and wherein the at least one seating unit is pivotally adjustable between a substantially straight row orientation and a curved row orientation, and at least one floor plate attachment, wherein the at least one floor plate attachment is configured to secure the at least one seating unit, to an associated floor, in a predetermined located.

**[0011]** In a further embodiment, a reconfigurable seating system may include a plurality of seating units arranged in at least two rows, at least one floor plate, wherein the at least one floor plate includes at least one first mounting foot receptacle for releasably receiving a first mounting foot of a first seating unit in a first row and a second mounting foot receptacle for releasably receiving a second mounting foot of a second seating unit in a second row, wherein the plurality of seating units adjustable between a flat floor orientation and a sloped floor orientation, and at least one floor plate attachment, wherein the at least one floor plate attachment is configured to secure the at least one seating unit, to an associated floor, in a predetermined located.

#### BRIEF DESCRIPTION OF THE FIGURES

**[0012]** The figures described below depict various aspects of the systems and methods disclosed herein. It should be understood that each figure depicts an embodiment of a particular aspect of the disclosed systems and methods, and that each of the figures is intended to accord with a possible embodiment thereof. Further, wherever possible, the following description refers to the reference numerals included in the following figures, in which features depicted in multiple figures are designated with consistent reference numerals.

**[0013]** FIG. 1A depicts a top, front, perspective view of an example reconfigurable seating system having foldable chairs in a closed position;

**[0014]** FIG. 1B depicts a top plan view of the example reconfigurable seating system of FIG. 1A;

**[0015]** FIG. 1C depicts a top perspective view of the example reconfigurable seating system of FIG. 1A having the foldable chairs in an open position;

**[0016]** FIG. 1D depicts a top plant view of the example reconfigurable seating system of FIG. 1C;

**[0017]** FIG. 1E depicts a left-side profile view of the example reconfigurable seating system of FIG. 1A;

**[0018]** FIG. 1F depicts a left-side profile view of the example reconfigurable seating system of FIG. 1C;

**[0019]** FIG. 1G depicts a front profile view of the example reconfigurable seating system of FIG. 1C;

**[0020]** FIG. 1H depicts a front profile view of the example reconfigurable seating system of FIG. 1A;

**[0021]** FIG. 1J depicts a rear profile view of the example reconfigurable seating system of FIG. 1A;

**[0022]** FIG. 2 depicts a top, front, perspective view of a portion of the chairs within the example reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D;

**[0023]** FIG. 3 depicts a top, front perspective view of an example seating unit for use within the example reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D;

**[0024]** FIG. 4 depicts a top, front, exploded perspective view of a portion of the example reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D;

**[0025]** FIGS. 5A-C depict example chairs for use within the example reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D for use with flat to increasing sloped floors;

**[0026]** FIGS. 6A-6C depict various views of an example structures for use within the reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D;

**[0027]** FIG. 7 depicts a portion of an example mounting configuration for mounting two seating units to a common floor plate for use in the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D;

**[0028]** FIG. 8 depicts a portion of an example standard for supporting two seating units on a common floor plate for use within the reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D;

**[0029]** FIG. 9 depicts a portion of an example floor plate with side-by-side mounting feet for use within the reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D;

**[0030]** FIG. 10 depicts a portion of an example floor plate with side-by-side mounting feet receptacles for use within the reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D;

**[0031]** FIG. 11 depicts a portion of example standards for use in the seating units depicted in FIG. 3;

**[0032]** FIG. 12 depicts a portion of example seating units secured to respective floor plates for use within the reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D;

**[0033]** FIGS. 13A-D depict various views of example reconfigurable seating systems and components arranged in an arched-row configuration;

**[0034]** FIG. 14 depicts a portion of example standards for use in the seating units depicted in FIG. 3;

**[0035]** FIG. 15 depicts a portion of example seating units secured to respective floor plates for use within the reconfigurable seating systems of FIGS. 13A-D;

**[0036]** FIG. 16 depicts an example floor plate with a mounting foot receptacle for use within the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D;

**[0037]** FIG. 17 depicts an example floor plate with a mounting foot receptacle for use within the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D;

**[0038]** FIG. 18 depicts an example standard and mounting foot for use in the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D;

**[0039]** FIGS. 19A and 19B depict an example mounting foot and receptacle for use within the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D;

**[0040]** FIGS. 20A-20D depict an example mounting foot and receptacle for use within the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D;

**[0041]** FIGS. 21-23 depict various stillages for moving and storing seating units and floor plates of the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D;

[0042] FIGS. 24A-C depict an example hinged floor plate; and

[0043] FIGS. 25A-25D depict various views of an example beam mounted seating unit.

#### DETAIL DESCRIPTION

[0044] Reconfigurable seating systems are provided having a link system with beam mounted chairs, that may join adjacent chairs within a respective seating unit. A reconfigurable seating system may include: 1) chairs that may be easily reconfigurable on flat or sloped floors; and 2) independent link plates of sufficient thickness (e.g.,  $\frac{1}{16}$ " thick,  $\frac{1}{8}$ " thick,  $\frac{3}{16}$ " thick,  $\frac{1}{4}$ " thick,  $\frac{1}{2}$ " thick, or beveled to less than  $\frac{1}{2}$ " thick sides, etc.) and width to restrain the chairs in a predetermined location, and which may have the following advantages, a. do not pose a tripping hazard because of their low profile, b. join the chairs between rows so the chairs cannot be tipped over in a panic situation and pose an egress hazard (fire code violation), c. simple to manufacture, d. allow chairs to be set up into different configurations, e. anchored to a floor if desired, f. accommodate straight or radius row layouts (e.g., may interlock or have multiple locking features to accommodate differing row to row spacing), and g. simple chair attachment to floor plates.

[0045] A single fastener, or multiple fasteners, may be used to attach each seating unit standard to a respective floor plate. Alternatively, a "ski boot binding" or other quick connect arrangement may be used to releasably secure each seating unit to a respective floor plate. A mounting foot may be used to secure each seating unit to a floor plate. The mounting foot may be configured to ensure each seating unit is stable during storage and transport, and when not attached to the floor plate. Individual chairs may be joined within a row in a single, double, triple or more chair seating unit.

[0046] With reference to FIG. 1A a top, front, perspective view of an example reconfigurable seating system 100a having foldable chairs 125a, 130a, 135a in a closed position is depicted. The reconfigurable seating system 100a may include rows 105a of seating units 115a arranged in columns 110a. Each seating unit 115a may be mounted include a standard 145a, 150a with a mounting foot 140a releasably connected to a floor plate 135a.

[0047] Turning to FIG. 1B a top plan view of an example reconfigurable seating system 100b is depicted. The reconfigurable seating system 100b may be similar to the reconfigurable seating system 100a of FIG. 1A. The reconfigurable seating system 100b may include rows 105b of seating units 115b arranged in columns 110b. Each seating unit 115b may be mounted include a standard 145b, 150b with a mounting foot 140b releasably connected to a floor plate 135b, 136b.

[0048] With reference to FIG. 1C a top perspective view of an example reconfigurable seating system 100c is depicted. The reconfigurable seating system 100c may be similar to the reconfigurable seating system 100a of FIG. 1A. The reconfigurable seating system 100c may include rows 105c of seating units 115c arranged in columns 110c. Each seating unit 115c may be mounted include a standard 145c, 150c with a mounting foot 140c releasably connected to a floor plate 135c.

[0049] Turning to FIG. 1D a top plan view of an example reconfigurable seating system 100d is depicted. The reconfigurable seating system 100d may be similar to the reconfigurable seating system 100c of FIG. 1C. The reconfigurable seating system may include rows 105d of seating units 115d

arranged in columns 110d. Each seating unit 115d may be mounted include a standard 145d, 150d with a mounting foot 140d releasably connected to a floor plate 135d.

[0050] With reference to FIG. 1E a left-side profile view of an example reconfigurable seating system 100e is depicted. The reconfigurable seating system 100e may be similar to the reconfigurable seating system 100a of FIG. 1A. The reconfigurable seating system 100e may include rows 105a of seating units. Each seating unit may include a standard 145e with a mounting foot 140e releasably connected to a floor plate 135e.

[0051] Turning to FIG. 1F a left-side profile view of an example reconfigurable seating system 100f is depicted. The reconfigurable seating system 100f may be similar to the reconfigurable seating system 100c of FIG. 1C. The reconfigurable seating system 100f may include rows 105a of seating units 115a. Each seating unit may include a standard 145f with a mounting foot 140f releasably connected to a floor plate 135f.

[0052] With reference to FIG. 1G a front profile view of an example reconfigurable seating system 100g is depicted. The reconfigurable seating system 100g may be similar to the reconfigurable seating system 100c of FIG. 1C. The reconfigurable seating system 100g may include columns 110g of seating units 115g having a plurality of chairs 120g, 125g, 130g. Each seating unit 115g may include a standard 145g, 150g with a respective mounting foot 140g releasably connected to a floor plate.

[0053] With reference to FIG. 1H a front profile view of an example reconfigurable seating system 100h is depicted. The reconfigurable seating system 100h may be similar to the reconfigurable seating system 100a of FIG. 1A. The reconfigurable seating system 100h may include columns 110h of seating units 115h having a plurality of chairs 120h, 125h, 130h. Each seating unit 115h may include a standard 145h, 150h with a respective mounting foot 140h releasably connected to a floor plate.

[0054] With reference to FIG. 1J a front profile view of an example reconfigurable seating system 100j is depicted. The reconfigurable seating system 100j may be similar to the reconfigurable seating system 100a of FIG. 1A. The reconfigurable seating system 100j may include columns 110j of seating units 115j having a plurality of chairs 120j, 125j, 130j. Each seating unit 115j may include a standard 145j, 150j with a respective mounting foot 140j releasably connected to a floor plate.

[0055] Turning to FIG. 2 a top, front, perspective view of a portion of the chairs 200. Each chair 200 may be similar to the chairs 120a, 125a, 130a within the example reconfigurable seating system 100a-j and 1300a-d of FIGS. 1A-H and J and FIGS. 13A-D is depicted. Associated seating units may include standard 245 with a mounting foot 240 releasably secured to a floor plate 235.

[0056] With reference to FIG. 3 a top, front perspective view of an example seating unit 300 for use within the example reconfigurable seating systems 100a-j and 1300a-d of FIGS. 1A-H and J and FIGS. 13A-D is depicted. The seating unit 300 may include three chairs 320, 325, 330. While the seating unit 300 is depicted as having three chairs, it should be understood that any given seating unit 300 may include one, two, three, four, five or more chairs. Any one of the chairs 320, 325, 330 may be similar to the chairs as described in the commonly assigned applications that are incorporated herein by reference above. In any event, the

seating unit **300** may include a right-end seat bracket **360**, two center seat bracket **370** and a left-end seat bracket secured to a support beam **355**. The support beam **355** may be secured to a first standard **345** having a first mounting foot **340** and to a second standard **350** having a second mounting foot **340**.

[0057] Turning to FIG. 4 a top, front, exploded perspective view of a portion of an example reconfigurable seating system **400** is depicted. The portion of the reconfigurable seating system **400** may be similar to any portion of the reconfigurable seating systems **100a-j** and **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D. The portion of the reconfigurable seating system **400** may include mounting foot receptacles **438** secured to a floor plate **435** using tapered head **437** bolts **436**. Alternately the mounting foot receptacles may be otherwise attached to the floor plate **435** by welding or other means or the receptacle may be an integral part of the floor plate. The portion of the reconfigurable seating system **400** may further include a seat bracket **480** supported by a standard **445** and a mounting foot **440**. A bushing **481** and a top plate **482** may be secured between the seat bracket **480** and the standard **445** by a first bolt **483**, a first washer **484**, second bolt **485** and a second washer **486**.

[0058] With reference to FIGS. 5A-C example chairs **530a**, **530b**, **530c** for use within a respective example reconfigurable seating system **500a**, **500b**, **500c** are depicted. The reconfigurable seating systems **500a**, **500b**, **500c** may be similar to the reconfigurable seating systems **100a-j** or **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D. The chair **530a** may be for use in a reconfigurable seating system to be installed on a flat floor. The chair **530a** may include a standard **545a** secured substantially parallel to a mounting foot **547a** such that the chair seat is located a distance **531a** from the floor.

[0059] The chair **530b** may be for use in a reconfigurable seating system to be installed on a slightly sloped floor (e.g., a class A or B slope). The chair **530b** may include a standard **545b** secured to a mounting foot **547b** at an angle **501b** (e.g., 1 to 10 degree angle) approximately equal to the slightly slope of the floor such that the chair seat is located a distance **531b** from the floor. The standard **545b** may be shorter than the standard **545a** such that the distance **531b** is substantially equal to the distance **531a**.

[0060] The chair **530c** may be for use in a reconfigurable seating system to be installed on a moderately sloped floor (e.g., a class C or D slope). The chair **530c** may include a standard **545c** secured to a mounting foot **547c** at an angle **501c** (e.g., 10 to 20 degree angle) approximately equal to the slope of the moderately sloped floor such that the chair seat is located a distance **531c** from the floor. The standard **545c** may be shorter than the standard **545a**, **545b** such that the distance **531c** is substantially equal to the distance **531a**, **531b**.

[0061] While the chairs **530a**, **530b**, **530c** are described with regard to a flat floor, a slightly sloped floor, and a moderately sloped floor, respectively, any one of the chairs **530a**, **530b**, **530c** may be configured to be adjustably installed on any flat or sloped floor. Furthermore, a sloped floor may be any angle, including being negatively sloped with respect to an associated stage.

[0062] Turning to FIGS. 6A-6C various views of an example structures **600a**, **600b**, **600c**, for use within the reconfigurable seating system **100a-j** or **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D, are depicted. The structure **600a** may include a top plate **682a** and a bushing **681a** secured to a seat bracket **680a** by a first bolt **683a**, a first

washer **684a** and a second bolt **685a**, and supported by a standard **645a** and a mounting foot **640a**. The structure **600b** may include a top plate **682b** and a bushing **681b** secured to a seat bracket **680b** by a first bolt **683b**, a first washer **684b**, a second bolt **685b** and a second washer **686b**, and supported by a standard **645b** and a mounting foot **640b**. The structure **600c** may include a top plate **682c** and a bushing **681c** secured to a seat bracket **680c** by a first bolt **683c**, a first washer **684c**, a second bolt and a second washer, and supported by a standard **645c** and a mounting foot **640c**. The mounting foot **640c** may include a mounting foot receptacle hole **643c**, a first bolt hole **641c** and a second bolt hole **642c**. The function of bracket **681c** may be incorporated into bracket **682c**. Bracket **682c** may also incorporate features to lock it to a seat assembly beam and cooperate with fasteners.

[0063] With reference to FIG. 7 a portion of an example mounting configuration **700** for mounting two seating units to a common floor plate **735** for use in reconfigurable seating systems **100a-h** and **j** and **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D. The mounting configuration **700** may include mounting foot receptacle **738** pivotally attached to a floor plate pivot bracket **739**. The mounting configuration **700** may further include a standard securing bolt **746** engaged securing a mounting foot **740** to the floor plate **735** via a standard/mounting foot intersection **743**. The mounting foot **740** may include a first bolt hole **741** and a second bolt hole **742**. Individual components of the example mounting configurations **700** may cooperate to adjust for different floor slopes.

[0064] Turning to FIG. 8 a portion **800** of example standards **845** for supporting two seating units on a common floor plate for use within a reconfigurable seating system **100a-h** and **j** or **13a-d** of FIGS. 1A-H and J and FIGS. 13A-D is depicted. The portion **800** may include a right-hand chair bracket **860**, a left-hand chair bracket **880**, a support beam **855**, a mounting foot **840**, top plates **862**, **882** and standard securing bolts **846**. The portion **800** illustrates, for example, how adjacent seating units are not required to be co-linear do to the cooperation between the seating units and the floor plates. While the foot on the seating unit is illustrated for convenience at right angles to the seating unit the invention includes variation in the mounting foot angle. While the securing bolt **846** is shown in FIG. 8 as going inside the leg of the foot and being of sufficient length to reach to the top of the plate, any given securing bolt **846** may be external to the foot. Any given securing bolt **846** may be either longer or shorter, and the mounting foot may include alternate materials, such as a casting having alignment features, fastener retaining features or other features to aid in assembly of the associated reconfigurable seating system.

[0065] With reference to FIG. 9 a portion **900** of an example floor plate **935** with side-by-side mounting feet **940** for use within reconfigurable seating systems **100a-h** and **j** or **13a-d** of FIGS. 1A-H and J and FIGS. 13A-D is depicted. The portion **900** may include mounting foot receptacles **938** and the mounting feet may include a respective first bolt hole **941**. While the mounting foot receptacle **938** is shown by convenience as a what is commonly called a coupling nut, the mounting foot receptacle **938** may be replaced by a unit which aids in foot location, aids in alignment of an associated fastening system, reduces time to fasten (e.g., 1/4-turn fasteners), and/or automatically accommodates variation in floor slope and/or relative seat position.

[0066] Turning to FIG. 10 a portion **1000** of an example floor plate **1035** with side-by-side mounting feet receptacles

**1038** for use within the reconfigurable seating system of FIGS. 1A-H and J and FIGS. 13A-D is depicted. The mounting feet receptacles may be secured to the floor plate **1035** with bolts **1037**.

[0067] With reference to FIG. 11 a portion **1100** of example standards **1145** for use in seating units **300** depicted in FIG. 3 is depicted. The portion **1100** may include top plates **1162**, **1182**, a right-hand chair bracket **1160** and a left-hand chair bracket **1180**.

[0068] Turning to FIG. 12 a portion **1200** of example seating units secured to respective floor plates **125** for use within reconfigurable seating system **100a-h** and **j** or **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D is depicted. The portion **1200** may include right-hand chair brackets **1260**, center chair brackets **1270**, left-hand chair brackets **1280**, standards **1245**, support beams **1255** and standards **1245**, **1250**.

[0069] With reference to FIGS. 13A-D various views of example reconfigurable seating systems and components arranged in an arched-row configuration **1300a-d** are depicted. The reconfigurable seating systems **1300a-d** may include rows **1305a-c** of seating units arranged in columns **1310a-c**, floor plates **1335a-d**, support beams **1355a-d**, right-hand chair brackets **1360a-d**, center chair brackets **1370a-d**, left-hand chair brackets **1380a-d** and mounting feet **1340d**. The mounting feet **1340d** may be secured to the floor plate **1335d** at an angle **1339d**, **1344d** to define the arched-row configuration.

[0070] Turning to FIG. 14 a portion **1400** of example standards **1445** for use in seating units **300** depicted in FIG. 3 is depicted. The portion **1400** may include top plates **1462**, **1482**, a right-hand chair bracket **1460** and a left-hand chair bracket **1480**.

[0071] With reference to FIG. 15 a portion of example seating units **1500** secured to respective floor plates **1535** for use within reconfigurable seating systems **1300a-d** of FIGS. 13A-D is depicted. The seating units **1500** may include right-hand chair brackets **1560**, center chair brackets **1570** and left-hand chair brackets **1580**.

[0072] Turning to FIG. 16 an example floor plate **1635** with a mounting foot receptacle **1638** for use within the reconfigurable seating system **100a-h** and **j** or **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D is depicted.

[0073] With reference to FIG. 17 an example floor plate **1735** with a mounting foot receptacle **1738** having a tapered interior end **1737** for use within the reconfigurable seating systems **100a-h** and **j** or **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D is depicted.

[0074] Turning to FIG. 18 an example **1800** standard **1845** and mounting foot **1840** for use in reconfigurable seating systems **100a-h** and **j** or **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D is depicted. The example **1800** may include a right-hand chair bracket **1880**, a support beam **1855** and a top plate **1882**. The mounting foot **1840** may include a first bolt hole **1841**, a second bolt hole **1842** and a mount foot receptacle hole **1843**.

[0075] With reference to FIGS. 19A and 19B an example mounting foot **1940b** and receptacle **1935a**, **1935b** for use within reconfigurable seating systems **100a-h** and **j** or **1300a-d** of FIGS. 1A-H and J and FIGS. 13A-D are depicted. The receptacle **1935a**, **1935b** may include a fixed latch **1936a**, **1936b**, a pivotable latch **1937a** and a latch release mechanism **1938a**. The pivotable latch **1937a** and the latch release mechanism **1938a** may be combined into a combination pivotable latch/latch release **1943b**. The mounting foot **1940b**

may include a first hook **1941b** to engage the fixed latch **1936a**, **1936b** and a second hook **1942b** to engage the pivotable latch **1937a**, **1943b**.

[0076] Turning to FIGS. 20A-20D example mounting foot **2045a-d** and receptacle **2040a-d** are depicted for use within the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D. Each mounting foot **2045a-d** cooperates with its receptacle **2040a-d**. It will be appreciated from FIGS. 20A-20D that the mounting foot **2045a-d** includes an attachment portion which may be permanently fixed within a respective seating unit.

[0077] With reference to FIGS. 21-23 various stillages for moving and storing seating units and floor plates of the reconfigurable seating systems of FIGS. 1A-H and J and FIGS. 13A-D are depicted. The stillage **2100** may include a frame **2195** supported on wheels **2196** and may be configured to store and transport seating units **2115**. The stillage **2200** may include a frame **2290** and wheels **2291** and may be configured to store and transport floor plates **2235**. The stillage **2200** may alternatively be configured to store and transport floor plates **2235** with mounting feet **2240** and/or standards **2245** attached to the floor plates **2235**. The stillage **2300** may include a frame **2395** supported on wheels **2396** and may be configured to store and transport seating units **2315**.

[0078] Turning to FIGS. 24A-C, various assembly views **2400a-c** are depicted of an example hinged floor plate **2435a-c**. The assemblies **2400a-c** may include a standard **2445a-c** that may be, for example, removably secured to a mounting foot **2440a-c** that may be, for example, removably secured to a floor plate **2435a**. The standard **2445a-c** may include a chair bracket **2480a**, **2480b**, a bushing **2481a**, **2481b** and a top plate **2482a**, **2482b**. The floor plate **2435a** may include a first section **2436a-c** pivotally attached to a second section **2437a-c** via a hinge **2438a-c**. Any given assembly **2400a-c** may further include a latch **2401c** having a pin **2404c** slidably arranged within a first receptacle **2402c**. When the first section **2436a-c** of the floor plate **2435a** is aligned with the second section **2437a-c** of the floor plate **2435a**, the pin **2404c** may be slid to engage the second receptacle **2403c** to, for example, secure the first section **2436a-c** relative to the second section **2437a-c** of the floor plate **2435a**. While the first receptacle **2402c** is depicted as being attached to the first section **2436a-c** and the second receptacle **2403c** is depicted as being attached to the second section **2437a-c**, the first receptacle **2402c** may be attached to the second section **2437a-c** and the second receptacle **2403c** may be attached to the first section **2436a-c**. Thus, the floor plate **2435a** may facilitate flexibility in floor slope, movement and storage.

[0079] With referenced to FIGS. 25A-25D, an example beam mounted seating unit **2500a-d** may include at least one chair (i.e., chair back **2581a-d**, chair seat **2532a-d**, and related beam mounting/seat pivot structure) mounted to a beam **2538a-d**. Any given beam mounted seating unit may be as described in U.S. provisional application Ser. No. 62/018, 854, entitled BEAM MOUNTED CHAIR ASSEMBLIES, CHAIR ASSEMBLIES FOR USE WITHIN THE BEAM MOUNTED CHAIR ASSEMBLIES, COMPONENTS FOR USE WITHIN THE CHAIR ASSEMBLIES AND PARTS FOR USE WITHIN THE COMPONENTS, as filed on Jun. 30, 2014, the entire disclosure of which is incorporated by reference herein. While only one chair is illustrated in FIGS. 25A-25C, it should be understood that any given beam mounted seating unit **2500a-c** may include any number of chairs such as, for example, that shown in FIG. 25D. While

the chair of FIGS. 25A-25C is depicted as including only one arm 2580a-c, it should be understood that any given chair may include two arms 2580a-d (i.e., one arm on either side of the chair) as shown in FIG. 25D. For example, a beam mounted seating unit 2500d may include at least three chairs, at least two of the at least three chairs may include one arm 2580d, and one of the at least three chairs may include two arms 2580d.

[0080] A beam mounted seating unit 2500a-d may be configured such that a beam 2538a-d is supported by a support structure 2537a-d. While only one support structure is shown in FIGS. 25A-25C, it should be understood that any given beam mounted seating unit may include any number of support structures 2537a-c, for example, two support structures 2537d of FIG. 25D. A support structure 2538a-d may include a front mounting foot 2536a-d having a front slotted hole 2540a-d and a rear mounting foot 2545a-d having a rear slotted hole 2582a-d. As depicted in FIG. 25D, any given support structure 2537d may include a middle slotted hole 2542d, such that the associated seating unit 2500d may be configured within a curved row as illustrated, for example, in FIG. 15. The front slotted hole 2582a-d and/or the rear slotted hole 2582a-d may include a raised rib to engage an associated fastener (e.g., a bolt head or a nut). The front slotted hole 2582a-d and/or the rear slotted hole 2582a-d, and associated fasteners, may be configured such that the given beam mounted seating unit 2500a-d may be removably secured to a floor plate 2539d, for example, without using any hand tools.

[0081] It will be appreciated that the seating arrangements shown in the Figures are highly adaptable, and can be used to provide a variety of seating plans, ranging from a single unit of three seats, as shown in FIG. 1, to a block of several hundred interlinked seats. The use of relatively thin floor plates (e.g., less than 1/2" thick), and with the chair seats tipped up as shown in FIG. 1, the seating units themselves offer very little obstruction to people walking past them, or between adjacent rows. Furthermore, when the seating units are separated from the floor plates, the seating units can be packed closely, for example in stillages, in a manner requiring very little storage space. Because each seating unit comprises more than one chair, deployment and clearance of the seating can be performed quickly, with one person able to deal with three seats, for example, at a time, rather than with only one chair as in the case of known systems.

[0082] This detailed description is to be construed as exemplary only and does not describe every possible embodiment, as describing every possible embodiment would be impractical, if not impossible. One could implement numerous alternate embodiments, using either current technology or technology developed after the filing date of this application.

What is claimed is:

1. A reconfigurable seating system, comprising:

at least one seating unit having at least two mounting feet;

at least two floor plates, wherein a first one of the at least two floor plates includes at least one first mounting foot receptacle for releasably receiving a first mounting foot of the at least two mounting feet, wherein a second one of the at least two floor plates includes at least one second mounting foot receptacle for releasably receiving a second mounting foot of the at least two mounting feet, and wherein the at least one seating unit is adjustable between a flat floor orientation and a sloped floor orientation; and

at least one floor plate attachment, wherein the at least one floor plate attachment is configured to secure the at least one seating unit, to an associated floor, in a predetermined located.

2. A reconfigurable seating system as in claim 1, wherein the at least one seating unit is adjustable between a first height and a second height.

3. A reconfigurable seating system as in claim 1, wherein the at least one seating unit includes a plurality of individual chairs.

4. A reconfigurable seating system as in claim 3, wherein at least one of the chairs, of the at least one seating unit, is foldable.

5. A reconfigurable seating system as in claim 1, further comprising a plurality of seating units arranged in a row, wherein the rows may define a substantially straight row or a curved row.

6. A reconfigurable seating system as in claim 1, wherein the at least one seating unit includes at least three chairs disposed side-by-side on a beam, wherein at least two of the at least three chairs includes a single arm, and wherein at least one of the at least three chairs includes two arms.

7. A reconfigurable seating system as in claim 1, further comprising a plurality of seating units arranged in at least two rows, wherein at least one of the at least two floor plates includes at least one third mounting foot receptacle for releasably receiving a third mounting foot, and wherein the third mounting foot is located in a second row different than a first row where the first and second mounting foot are located.

8. A reconfigurable seating system, comprising:

at least one seating unit having at least two mounting feet;

at least two floor plates, wherein a first one of the at least two floor plates includes at least one first mounting foot receptacle for releasably receiving a first mounting foot of the at least two mounting feet, wherein a second one of the at least two floor plates includes at least one second mounting foot receptacle for releasably receiving a second mounting foot of the at least two mounting feet, and wherein the at least one seating unit is pivotally adjustable between a substantially straight row orientation and a curved row orientation; and

at least one floor plate attachment, wherein the at least one floor plate attachment is configured to secure the at least one seating unit, to an associated floor, in a predetermined located.

9. A reconfigurable seating system as in claim 8, wherein the at least one seating unit is adjustable between a first height and a second height.

10. A reconfigurable seating system as in claim 8, wherein the at least one seating unit includes a plurality of individual chairs.

11. A reconfigurable seating system as in claim 10, wherein at least one of the chairs, of the at least one seating unit, is foldable.

12. A reconfigurable seating system as in claim 8, wherein the at least one seating unit is adjustable between a flat floor orientation and a sloped floor orientation.

13. A reconfigurable seating system as in claim 8, wherein the at least one seating unit includes at least three chairs disposed side-by-side on a beam, wherein at least two of the at least three chairs includes a single arm, and wherein at least one of the at least three chairs includes two arms.

14. A reconfigurable seating system as in claim 8, further comprising a plurality of seating units arranged in at least two

rows, wherein at least one of the at least two floor plates includes at least one third mounting foot receptacle for releasably receiving a third mounting foot, and wherein the third mounting foot is located in a second row different than a first row where the first and second mounting foot are located.

**15.** A reconfigurable seating system, comprising:

a plurality of seating units arranged in at least two rows;

at least one floor plate, wherein the at least one floor plate includes at least one first mounting foot receptacle for releasably receiving a first mounting foot of a first seating unit in a first row and a second mounting foot receptacle for releasably receiving a second mounting foot of a second seating unit in a second row, wherein the plurality of seating units adjustable between a flat floor orientation and a sloped floor orientation; and

at least one floor plate attachment, wherein the at least one floor plate attachment is configured to secure the at least one seating unit, to an associated floor, in a predetermined located.

**16.** A reconfigurable seating system as in claim **15**, wherein the plurality of seating units are adjustable between a first height and a second height.

**17.** A reconfigurable seating system as in claim **15**, wherein at least one of the plurality of seating units includes a plurality of individual chairs.

**18.** A reconfigurable seating system as in claim **17**, wherein at least one of the chairs, of at least one seating unit, is foldable.

**19.** A reconfigurable seating system as in claim **15**, wherein at least one of the plurality of seating units is pivotally adjustable between a substantially straight row orientation and a curved row orientation.

**20.** A reconfigurable seating system as in claim **15**, wherein at least one seating unit of the plurality of seating units includes at least three chairs disposed side-by-side on a beam, wherein at least two of the at least three chairs includes a single arm, and wherein at least one of the at least three chairs includes two arms.

\* \* \* \* \*