

(12) **United States Patent**
Duffy et al.

(10) **Patent No.:** **US 9,457,899 B2**
(45) **Date of Patent:** **Oct. 4, 2016**

(54) **MODULAR VEHICLE LIFT SYSTEM**

(71) Applicant: **The Boeing Company**, Chicago, IL
(US)

(72) Inventors: **Michael J. Duffy**, Prospect Park, PA
(US); **Scott H. Bouwer**, Wilmington,
DE (US); **John J. Mattero**, Media, PA
(US)

(73) Assignee: **The Boeing Company**, Chicago, IL
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 68 days.

(21) Appl. No.: **13/925,305**

(22) Filed: **Jun. 24, 2013**

(65) **Prior Publication Data**

US 2014/0374532 A1 Dec. 25, 2014

(51) **Int. Cl.**

G01C 23/00 (2006.01)

B64C 37/02 (2006.01)

B64C 39/02 (2006.01)

(52) **U.S. Cl.**

CPC **B64C 37/02** (2013.01); **B64C 39/02A**
(2013.01); **B64C 2201/027** (2013.01); **B64C**
2201/108 (2013.01); **B64C 2201/128**
(2013.01); **B64C 2201/146** (2013.01)

(58) **Field of Classification Search**

None

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,013,743 A * 12/1961 Keeney 244/3
3,332,643 A * 7/1967 Toner 244/7 R
3,656,723 A * 4/1972 Piasecki et al. 244/2
3,743,214 A * 7/1973 Maciolek 244/2

4,591,112 A * 5/1986 Piasecki et al. 244/26
4,601,444 A * 7/1986 Lindenbaum 244/26
5,082,205 A * 1/1992 Cauffman 244/25
7,357,352 B2 * 4/2008 Speer et al. 244/2
7,699,260 B2 * 4/2010 Hughey 244/17.23
7,959,104 B2 * 6/2011 Kuntz 244/2
8,322,648 B2 * 12/2012 Kroetsch et al. 244/17.23
8,886,371 B2 * 11/2014 Peters 701/13
2006/0198713 A1 * 9/2006 Azzalin et al. 411/8
2007/0023581 A1 * 2/2007 La 244/165
2007/0102565 A1 * 5/2007 Speer et al. 244/2
2009/0194634 A1 * 8/2009 Stelte 244/1 R
2009/0250549 A1 * 10/2009 Wiggerich 244/17.11
2009/0283629 A1 * 11/2009 Kroetsch et al. 244/17.23

(Continued)

FOREIGN PATENT DOCUMENTS

GB 2 455 374 6/2009
WO WO 2008/018857 2/2008

OTHER PUBLICATIONS

Extended European Search Report dated Oct. 30, 2014 from Euro-
pean Application No. 14167622.1.

(Continued)

Primary Examiner — Medhat Badawi



(74) *Attorney, Agent, or Firm* — Baldauff IP, LLC;
Michael J. Baldauff, Jr.

(57)

ABSTRACT

Apparatus, systems, and methods provide for a modular
vehicle system utilized for lifting and maneuvering pay-
loads. According to aspects of the disclosure, any number of
individual lift vehicles may be connected to create a unified
lift vehicle. The individual lift vehicles may be placed
adjacent to one another according to a determined lifting
array formation and coupled together using connection
mechanisms. The connection mechanisms rigidly and com-
municatively connect the individual lift vehicles to create
the unified lift vehicle suitable for lifting and maneuvering
a payload.

23 Claims, 27 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2010/0193625 A1* 8/2010 Sommer 244/2
 2010/0193651 A1* 8/2010 Railsback et al. 248/229.24
 2011/0144834 A1* 6/2011 Sommer 701/3
 2011/0202205 A1* 8/2011 Pepitone et al. 701/3
 2012/0048990 A1* 3/2012 Sommer 244/3
 2012/0056040 A1* 3/2012 Brotherton-Ratcliffe
 et al. 244/23 A
 2012/0132744 A1* 5/2012 Huber et al. 244/118.1
 2012/0158215 A1* 6/2012 Sun et al. 701/3
 2013/0105635 A1* 5/2013 Alzu'bi et al. 244/23 A
 2013/0110325 A1* 5/2013 Sapp et al. 701/3

2014/0025238 A1* 1/2014 So et al. 701/3
 2014/0371956 A1* 12/2014 Jenkins 701/3
 2014/0374532 A1* 12/2014 Duffy et al. 244/2

OTHER PUBLICATIONS

Mellinger, Daniel, Shomin, Michael, Michael, Nathan and Kumar, Vijay, "Cooperative Grasping and Transport Using Multiple Quadrotors", GRASP Laboratory, University of Pennsylvania, Philadelphia, PA, Nov. 2010, pp. 1-12.
 e-volvo; <http://www.e-volo.com> , dated Feb. 14, 2013, pp. 1-2.

* cited by examiner




FIG. 1A




FIG. 1A

FIG. 1B




FIG. 2A

FIG. 2B

FIG. 2C




FIG. 3A

FIG. 3B




FIG. 3C




FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20






FIG. 21A

FIG. 21B

**FIG. 22****FIG. 23**




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28








FIG. 29

**FIG. 30****FIG. 31**

**FIG. 32****FIG. 33**





FIG. 34

**FIG. 35**

MODULAR VEHICLE LIFT SYSTEM**BACKGROUND**

Helicopters are commonly used to lift payloads and transport them from one location to another. Remotely piloted lift vehicles may also be used to vertically lift a payload in a similar manner as conventional helicopters while being controlled by one or more operators that are not within the vehicle. With respect to helicopters and remotely piloted lift vehicles (generally referred to as "lift vehicles"), the weight of the payload is limited by the capabilities of the corresponding lift vehicle.

In a typical scenario in which a payload larger than the capacity of the lift vehicle is to be lifted, the entire payload may be divided or reconfigured into multiple payload portions, each being a size and weight that is within the safe allowable lifting capacity of the lift vehicle to be used during the operation. In doing so, the lift vehicle makes multiple trips to lift and move all of the payload portions from point A to point B until the entire payload has been moved. By dividing the payload into multiple portions, the cost and risk associated with the operation is increased, potentially significantly, due to the increased amount of time involved with making multiple flights between points A and B.

Alternatively, when the payload cannot be reconfigured or divided into multiple portions, multiple lift vehicles may be coupled to the entire payload to increase the lifting capabilities as compared to a single lift vehicle. When utilizing multiple lift vehicles to lift a payload, traditional lifting configurations include at least one pilot or remote operator per lift vehicle, with each vehicle operating independently, but in coordination with, other vehicles to maneuver the payload. This lifting configuration requires skilled pilots or remote operators. Moreover, the cost and risk associated with the operation may be significant due to the use of multiple vehicles and corresponding operators, as well as the risk associated with coordinated operation of multiple lift vehicles that are in close proximity to one another and are coupled to a single payload.

A straightforward approach to moving a payload is to select and utilize a lift vehicle that is capable of lifting and transporting the entire payload in one flight. Doing so may reduce the cost and risk associated with multiple flights or multiple vehicles, but may not be feasible due to availability of a lift vehicle capable with handling the entire payload, cost associated with acquiring a capable lift vehicle, environmental or operational considerations that prevent the use of the capable lift vehicle, or other considerations.

One conventional approach to ensuring a capability to lift large payloads may be to maintain a lift vehicle having the capacity to lift large payloads that may be encountered in a particular business or industry. A problem with doing so is that the cost of maintaining the lift vehicle with significant capacity may be substantial. If the lift vehicle is used to lift smaller payloads in addition to the large payloads, then a cost penalty is incurred in using the oversized lift vehicle for the mission.

It is with respect to these considerations and others that the disclosure made herein is presented.

SUMMARY

It should be appreciated that this Summary is provided to introduce a selection of concepts in a simplified form that are

further described below in the Detailed Description. This Summary is not intended to be used to limit the scope of the claimed subject matter.

Apparatus, systems, and methods described herein provide for a modular vehicle lift system that may be configured according to the particular lift mission and controlled autonomously and remotely. According to one aspect, a unified lift vehicle is provided for maneuvering a payload. The unified lift vehicle may include a number of individual lift vehicles and a number of connection mechanisms. The individual lift vehicles are each operative to perform controlled three-axis flight. They may be positioned adjacent to one another according to a lifting array formation and connected via the connection mechanisms. The connection mechanisms may rigidly and communicatively connect the individual lift vehicles in the lifting array formation to create the unified lifting vehicle. The unified lift vehicle may be operative to perform three-axis flight to lift and maneuver the payload.

According to another aspect, a modular vehicle lift system may include a number of individual lift vehicles, connection mechanisms, and a remote control device. The individual lift vehicles may each include four drive units and a controller. The four drive units may be coupled to one another to create a four-rotor configuration, with each drive unit including a motor and an attached rotor. The controller may be in communication with the four drive units and operable to control the four drive units according to control data received from the remote control device. The connection mechanisms may rigidly and communicatively connect the individual lift vehicles in the lifting array formation to create the unified lifting vehicle. The unified lift vehicle may be operative to perform three-axis flight to lift and maneuver the payload in response to input from the remote control device via the controller.

According to yet another aspect, a method for maneuvering a payload utilizing a modular vehicle lift system may include rigidly and communicatively coupling a number of individual lift vehicles that are each operative to perform three-axis flight. The individual lift vehicles may be coupled together using connection mechanisms to create a unified lift vehicle. The payload may be coupled to the unified lift vehicle and flight commands provided to maneuver the unified lift vehicle and payload in three-axis flight.

The features, functions, and advantages that have been discussed can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments, further details of which can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIGS. 1A-1C are perspective, side, and top views, respectively, of an individual lift vehicle utilizing a four-rotor configuration according to various embodiments presented herein;

FIGS. 2A-2C are perspective, side, and top views, respectively, of a unified lift vehicle comprised of two individual lift vehicles according to various embodiments presented herein;

FIGS. 3A-3C are perspective, side, and top views, respectively, of a unified lift vehicle comprised of four individual lift vehicles according to various embodiments presented herein;

FIG. 4 is a top view of a positioning diagram showing an individual lift vehicle having a four-rotor configuration

positioned within an array of available positions for a unified lift vehicle according to various embodiments presented herein;

FIG. 5 is a top view of a positioning diagram showing a unified lift vehicle having two individual lift vehicles with four-rotor configurations according to various embodiments presented herein;

FIGS. 6A-6C are top views a positioning diagram showing a unified lift vehicle having four individual lift vehicles with four-rotor configurations arranged in various lifting array formations according to various embodiments presented herein;

FIG. 7 is a perspective view of an individual lift vehicle utilizing a six-rotor configuration according to various embodiments presented herein;

FIG. 8 is a top view of a positioning diagram showing an individual lift vehicle having a six-rotor configuration positioned within an array of available positions for a unified lift vehicle according to various embodiments presented herein;

FIG. 9 is a top view of a positioning diagram showing a unified lift vehicle having two individual lift vehicles with six-rotor configurations according to various embodiments presented herein;

FIG. 10 is a top view of a positioning diagram showing a unified lift vehicle having three individual lift vehicles with six-rotor configurations according to various embodiments presented herein;

FIG. 11 is a perspective view of an individual lift vehicle utilizing an alternative six-rotor configuration according to various embodiments presented herein;

FIG. 12 is a top view of a positioning diagram showing an individual lift vehicle having an alternative six-rotor configuration positioned within an array of available positions for a unified lift vehicle according to various embodiments presented herein;

FIG. 13 is a top view of a positioning diagram showing a unified lift vehicle having two individual lift vehicles with alternative six-rotor configurations according to various embodiments presented herein;

FIG. 14 is a top view of a positioning diagram showing a unified lift vehicle having six individual lift vehicles with alternative six-rotor configurations according to various embodiments presented herein;

FIGS. 15 and 16 are perspective and exploded views, respectively, of an edge connector according to various embodiments presented herein;

FIG. 17 is a perspective view of the coupling of two individual lift vehicles using an edge connector according to various embodiments presented herein;

FIGS. 18 and 19 are perspective and exploded views, respectively, of a central connector according to various embodiments presented herein;

FIG. 20 is a perspective view of the coupling of four individual lift vehicles using a central connector according to various embodiments presented herein;

FIG. 21A is a top view of a unified lift vehicle illustrating electrical and data circuits throughout the individual lift vehicles and corresponding connection mechanisms according to various embodiments presented herein;

FIG. 21B is an expanded view of a central connector of the unified lift vehicle of FIG. 21A, showing representations of positive and negative wiring polarities associated with the central connector, according to various embodiments presented herein;

FIG. 22 is a screen diagram of a user interface for a modular vehicle lift system according to various embodiments presented herein;

FIG. 23 is a screen diagram of a user interface for a modular vehicle lift system showing the initiation of an example procedure for configuring a lift mission according to various embodiments presented herein;

FIG. 24 is a screen diagram of a user interface for a modular vehicle lift system showing a payload definition example according to various embodiments presented herein;

FIG. 25 is a screen diagram of a user interface for a modular vehicle lift system showing the initiation of an example procedure for defining a lifting array formation according to various embodiments presented herein;

FIGS. 26-29 are screen diagrams of a user interface and a unified lift vehicle of a modular vehicle lift system showing portions of an example procedure for registering individual lift vehicles of the unified lift vehicle according to various embodiments presented herein;

FIG. 30 is a screen diagram of a user interface for a modular vehicle lift system showing the initiation of an example procedure for defining waypoints for a lift mission according to various embodiments presented herein;

FIG. 31 is a screen diagram of a map interface showing defined waypoints for a lift mission according to various embodiments presented herein;

FIG. 32 is a screen diagram of a user interface for a modular vehicle lift system showing the initiation of an example validation procedure according to various embodiments presented herein;

FIG. 33 is a screen diagram of a user interface for a modular vehicle lift system showing the initiation of the lift mission according to various embodiments presented herein;

FIG. 34 is a screen diagram of a user interface for a modular vehicle lift system showing example controls for manual operation of the unified lift vehicle according to various embodiments presented herein; and

FIG. 35 is a flow diagram showing a method of maneuvering a payload according to various embodiments presented herein.

DETAILED DESCRIPTION

The following detailed description is directed to a modular lift system and method that utilizes any number of individual lift vehicles coupled together to provide a remotely or autonomously controlled unified lift vehicle according to the payload being lifted and other appropriate characteristics of the mission. As discussed above, traditional helicopters and other lift vehicles are limited to lifting and maneuvering a payload having a size and weight that falls within the safe operating parameters associated with the particular lift vehicle. If a lift vehicle with an adequate payload capacity is not available, the mission may not be possible. Alternatively, to maneuver payloads outside of the capabilities of the lift vehicle, a different lift vehicle may be acquired, or if possible, the payload may be apportioned into smaller sections that are capable of being maneuvered by the lift vehicle in multiple lift operations. These options may significantly increase the time and cost associated with the lift mission.

Another option may be to utilize multiple lift vehicles that are independently coupled to the payload to spread the weight of the payload amongst the multiple lift vehicles. This option may not only increase the cost of the operation, but the risk of the lift operation significantly increases. The pilots or operators of each lift vehicle must coordinate their actions to not only lift the payload, but to work with the

others to successfully maneuver the payload while maintaining safe separation from other lift vehicles.

Utilizing the concepts and technologies described herein, a modular vehicle lift system utilizes a number of individual lift vehicles that may be rigidly connected together in an appropriate formation and remotely operated as a single, unified lift vehicle to lift and maneuver a payload. Embodiments encompass an individual lift vehicle that includes a number of rotors and a control system that enables the individual lift vehicle to be remotely controlled to lift and maneuver a payload according to the lifting capabilities of the vehicle. Depending on the characteristics of the payload to be lifted, as well as criteria specific to the particular lift mission for delivering the payload, the appropriate number of individual lift vehicles and the formation in which the individual lift vehicles are to be attached to one another may be determined. The determined number of individual lift vehicles may then be rigidly and communicatively attached to one another in the determined formation via connection mechanisms to create a unified lift vehicle. The unified lift vehicle may then be controlled by a single operator via a remote control device to lift the payload and deliver the payload to a desired location. The operation may be manually controlled by the operator throughout the mission, may be autonomously controlled via a programmed control system, or a combination of manual and autonomous control depending on the particular portion of the lift mission or according to user preference.

In the following detailed description, references are made to the accompanying drawings that form a part hereof, and which are shown by way of illustration, specific embodiments, or examples. Referring now to the drawings, in which like numerals represent like elements through the several figures, a modular vehicle lift system and method for employing the same according to the various embodiments will be described.

FIGS. 1A-1C show perspective, side, and top views, respectively, of an individual lift vehicle **100** having a four-rotor configuration **101** according to various embodiments. For the purposes of this disclosure, an individual lift vehicle **100** may be considered to be the base, or core, unit of a unified lift vehicle described below. According to various embodiments, an individual lift vehicle **100** may be a remote controlled rotor-based aircraft or drone. The individual lift vehicle **100** may be controlled remotely by a user to perform a lift mission according to the lift capabilities of the individual lift vehicle **100**. In other words, a single individual lift vehicle **100**, such as the individual lift vehicle **100** shown in FIGS. 1A-1C, may be used to lift a payload **130** up to a weight that the individual lift vehicle **100** is safely capable of lifting and maneuvering. The precise lift capabilities of the individual lift vehicle **100** and the corresponding weight that it is able to lift is dependent upon a number of factors, including but not limited to, the weight of the individual lift vehicle **100** and thrust that the individual lift vehicle **100** is able to produce, as well as whether redundancy is provided in order to account for rotor failure. For comparative purposes when later discussing the benefits of coupling individual lift vehicles **100** together, the payload **130** shown in FIG. 1B is marked "1x" to indicate a payload of weight "X," multiplied by a factor of 1 in this example.

Each individual lift vehicle **100** may be operative to perform controlled three-axis flight when not connected to other individual lift vehicles **100** as described below. For the purposes of this disclosure, being operative to perform controlled three-axis flight may include responding to

remote control input to maneuver in three dimensions or along three axes. So, a remote pilot may provide input that causes the individual lift vehicle **100** to fly up, down, forward, back, and side to side, as well as fluidly to and between these directions.

The individual lift vehicle **100** of the example shown in FIG. 1 is arranged in a four-rotor configuration **101**, which includes four drive units **102** with corresponding rotors **104**. The drive units **102** are arranged in substantially a square pattern, or in a two-by-two array. As will be described in greater detail below with respect to FIGS. 7-14, additional configurations are contemplated. It should be appreciated that an individual lift vehicle **100** having any number of drive units **102** is within the scope of this disclosure.

Each drive unit **102** may include a rotor **104** coupled to a motor **106**. A power source **124** may include a battery stored within a hub **126** or other portion of the individual lift vehicle **100**. Power may be routed from the power source **124** to each individual motor **106** via distribution lines **122**, or alternatively, each drive unit **102** may include a separate power source dedicated to that particular drive unit **102**. Each motor **106** may be electrically driven and sized according to the desired performance capabilities of the individual lift vehicle **100**. A speed controller **114** may be used to provide control to the motor **106** within each drive unit **102** in response to signals provided from a control and sensor suite **118**, which is described in greater detail below.

The distribution lines **122** may include any type of power and/or data wires or signal transfer mechanisms suitable for transferring power or data between the drive units and the control and sensor suite **118**, as well as between individual lift vehicles **100** when coupled together as described below. Power and data may be distributed through the same distribution lines **122** or through separate distribution lines **122**. The distribution lines **122** are represented in FIG. 1A with a broken line through along the frame **108** of only one drive unit **102** for clarity purposes, however, it should be appreciated that the distribution lines **122** may be routed through or incorporated into any portions of the frame **108** for all drive units **102**. The ends of the frame **108** of each drive unit **102** creates a connector junction **110** for securely coupling each individual lift vehicle **100** to an adjacent individual lift vehicle **100** as will be described in detail below. Also as discussed further below, the distribution lines **122** may extend to each connector junction **110** in order to provide a mechanism to allow for the transfer of power and data between individual lift vehicles **100** that are coupled together.

According to one embodiment, the frame **108** includes modular tubing manufactured from any suitable materials including, but not limited to, aluminum, carbon composites, glass composites, titanium, wood, and any combinations thereof. The modular tubing of the frame **108** is centrally secured together at the hub **126** and extends outward to create a stable mounting location for each drive unit **102**. Tension wires **112** may additionally be used to provide structural support and stability to the frame **108**. Each individual lift vehicle **100** may have landing gear **116** extending from the frame **108** that provide stable contact points on which the individual lift vehicle **100** rests. Moreover, protective ducts **120** may optionally be used to encircle each rotor **104** with a material that provides some protection against contact with objects or people. Suitable materials for the protective ducts **120** include, but are not limited to, aluminum, carbon composites, glass composites, titanium, Styrofoam, plastic, compressed cardboard, wood, and any combinations thereof.

According to one embodiment, the control and sensor suite **118** may include any type of sensors and components used for control of the individual lift vehicle **100**. As an example, the control and sensor suite **118** may include a signal receiver for receiving remote controls from a remote control device, which is shown and described below with respect to FIGS. 22-33. Moreover, the control and sensor suite **118** may include a controller **140** operative for implementing stored or received instructions for autonomous flight from one location to another via pre-programmed waypoints according to pre-programmed flight characteristics such as altitude, velocity, climb and descent locations and rates, and the like. The control and sensor suite **118** may include an inertial measurement unit and global positioning system components to aid in navigation and flight controls. The control and sensor suite **118** may additionally include any type of sensors or feedback mechanisms corresponding to the individual lift vehicle **100** or the ambient environment. It should be understood that the present disclosure contemplates any type of sensors and components that may be beneficial to operation of the individual lift vehicle **100** and corresponding modular lift system described herein.

FIGS. 2A-2C show perspective, side, and top views, respectively, of a unified lift vehicle **200**, created by coupling two individual lift vehicles **100**. Utilizing the concepts described herein, a unified lift vehicle **200** may be created using any appropriate number of individual lift vehicles **100** to lift a payload **130** according to the criteria of any specific lift mission. As shown in FIGS. 2A-2C, the unified lift vehicle **200** of this example utilizes two individual lift vehicles **100** rigidly coupled together along axis **204** via connection mechanisms **202**. The connection mechanisms **202** will be described in detail below with respect to FIGS. 15-20. For the purposes of this disclosure, "rigidly coupled" or "rigidly connected" means physically attached to one another via a substantially inflexible connection mechanism or means.

By rigidly coupling the individual lift vehicles **100**, the unified lift vehicle **200** is created. The unified lift vehicle **200** operates as a single remotely controlled vehicle in much the same manner as the individual lift vehicles **100** operate. In other words, the individual lift vehicles **100** of the unified lift vehicle **200** work together when coupled to provide the unified lift vehicle **200** with the capability for controlled three-axis flight. In doing so, as shown in FIG. 2B, the unified lift vehicle **200** of this example that is created from coupling two individual lift vehicles **100** is capable of lifting a payload **130** having a weight of approximately "2x," or two times the weight of the payload **130** that a single individual lift vehicle **100** is capable of lifting. It should be appreciated that due to the weight associated with the connection mechanisms **202**, the actual increase in payload capacity attributed to connecting two individual lift vehicles **100** together to create a unified lift vehicle **200** may be less than two times the payload capacity of a single individual lift vehicle **100**.

FIGS. 3A-3C show perspective, side, and top views, respectively, of a unified lift vehicle **200**, created by coupling four individual lift vehicles **100**. The unified lift vehicle **200** of this example that is created from coupling four individual lift vehicles **100** is capable of lifting a payload **130** having a weight of "4x," or four times the weight of the payload **130** that a single individual lift vehicle **100** is capable of lifting. It should be clear from these examples that according to various embodiments presented herein, a unified lift vehicle **200** comprised of N number of individual lift vehicles **100** may be capable of lifting N times

the weight of the payload **130** that a single individual lift vehicle **100** may lift. As seen in FIG. 3C, the unified lift vehicle **200** may be arranged according to any appropriate formation using a given number of individual lift vehicles **100**. For example, 2x2 formation **301** includes four individual lift vehicles **100** positioned and secured adjacent to one another in two columns and two rows to form the unified lift vehicle **200** having a generally square or diamond shape. Alternatively, 4x1 formation **303** includes four individual lift vehicles **100** positioned and secured adjacent to one another in four columns and one row to create a unified lift vehicle **200** having a generally rectangular shape.

FIGS. 4-6C will now be described to illustrate various concepts with respect to the arrangement of individual lift vehicles **100** to create unified lift vehicles **200** of varying formations. FIG. 4 shows an individual lift vehicle **100** in solid lines positioned within an array of available positions within a positioning diagram **400** for a unified lift vehicle **200**. The positioning diagram **400** is for illustrative purposes only to show the available positions for individual lift vehicles **100** in the creation of a unified lift vehicle **200**. The available positions for individual lift vehicles **100** are drawn with broken lines within columns A-C and rows 1-4. This example is shown with respect to a positioning diagram **400** for a unified lift vehicle **200** having an array of three columns and four rows of potential individual lift vehicle **100** positions. It should be appreciated that any number of columns and rows may be utilized according to the particular implementation.

Turning to FIG. 5, a unified lift vehicle **200** created from two individual lift vehicles **100** is shown. The individual lift vehicles **100** are rigidly connected via connection mechanisms **202** in positions within column B, row 2 and column C, row 2 to form a 2x1 formation **501**. Although the connection mechanisms **202** are shown as being circular, or even omitted for clarity such that the frames **108** of the individual lift vehicles **100** abut or intersect, the connection mechanisms **202** may be any appropriate shape and size as will be described in greater detail below with respect to FIGS. 15-20.

FIGS. 6A-6C show three examples of alternative formations of a unified lift vehicle **200** having four individual lift vehicles **100** rigidly connected together. FIG. 6A shows the positioning diagram **400** having a unified lift vehicle **200** created from arranging the individual lift vehicles **100** according to the 2x2 formation **301** shown and described above. FIG. 6B shows the positioning diagram **400** having a unified lift vehicle **200** created from arranging the individual lift vehicles **100** according to a 1x4 formation **601** in which the individual lift vehicles **100** are linearly arranged in a single column. FIG. 6C shows the positioning diagram **400** having a unified lift vehicle **200** created from arranging the individual lift vehicles **100** according to an asymmetric formation **603**. The asymmetric formation **603** of this example is generally "L" shaped, although any shape may be appropriate depending on the criteria of the particular lift mission for which the unified lift vehicle **200** will be used, such as the geometry of the payload **120** or the characteristics of the location to which the payload **120** is to be delivered.

These examples discussed with respect to FIGS. 4-6C have been shown in the context of a positioning diagram containing an array of individual lift vehicles **100**. Doing so illustrates the potential placement of any appropriate number of individual lift vehicles **100** according to any specific implementation. The precise number and placement of the individual lift vehicles **100**, as well as the coupling and

communication linkage between the individual lift vehicles **100** and a remote control system will be described in detail below.

Prior to discussing the coupling of the individual lift vehicles **100** and the corresponding electrical and data linkages that facilitate control of the unified lift vehicle **200**, examples of alternative configurations of an individual lift vehicle **100** will be shown and described. FIG. 7 shows an individual lift vehicle **100** having a six-rotor configuration **701** according to various embodiments. The individual lift vehicle **100** having the six-rotor configuration **701** is similar to the individual lift vehicle **100** having the four-rotor configuration **101** described above, with the primary exception being that the six-rotor configuration **701** utilizes six drive units **102** rather than four. The frame **108** may be configured accordingly to accommodate the six drive units **102** with corresponding rotors **104**, motors **106**, and speed controllers **114**. The individual lift vehicle **100** may additionally include a control and sensor suite **118** and other applicable components. While the drive units **102** are spaced and positioned to create a substantially hexagonal perimeter **702**, any suitable arrangement may be used, including arranging the drive units **102** in an array to create a substantially rectangular perimeter (not shown).

FIGS. 8-10 show examples of a positioning diagram **800** with arrangements of one, two, and three individual lift vehicles **100**, respectively, each with a six-rotor configuration **701**. FIG. 8 shows a single individual lift vehicle **100** with a six-rotor configuration **701** placed within the positioning diagram **800**. The positioning diagram **800** illustrates how the edges of hexagonally shaped individual lift vehicles **100** may be placed adjacent to, and potentially abutting, one another when creating a unified lift vehicle **200**. FIG. 9 shows the potential placement of two individual lift vehicles **100**, each with a six-rotor configuration **701**, in creating a unified lift vehicle **200**. FIG. 10 similarly shows a unified lift vehicle **200** having three individual lift vehicles **100** with six-rotor configurations **701**.

FIG. 11 shows an individual lift vehicle **100** having an alternative six-rotor configuration **1101** according to various embodiments. In this embodiment, the alternative six-rotor configuration **1101** includes three drive units **102** with corresponding rotors **104**, motors **106**, and speed controllers **114** mounted on a top side **1104** of the frame **108** and facing upwards. Three additional drive units **102** with corresponding rotors **104**, motors **106**, and speed controllers **114** are mounted on a bottom side **1106** of the frame **108** facing downwards, opposite the drive units **102** on the top side **1104**. The drive units **102** on the bottom side **1106** may be counter-rotating such that they rotate in opposite directions as the drive units **102** on the top side **1104**. In this manner, the drive units **102** on the top side **1104** may be described as being operative to pull the individual lift vehicle **100** upwards, while the drive units **102** on the bottom side **1106** may be described as being operative to push the individual lift vehicle **100** upwards.

As with other individual lift vehicles **100** described herein, the speed controllers **114** may be responsive to remote control inputs to vary the rotational speeds of the motors **106** and corresponding rotors **104** in an appropriate manner to maneuver the individual lift vehicle **100** in a desired direction and speed. The individual lift vehicle **100** may additionally include a control and sensor suite **118** and other applicable components. While the drive units **102** are spaced and positioned to create a substantially triangular perimeter **1102**, other arrangements may be used without departing from the scope of this disclosure.

FIGS. 12-14 show examples of a positioning diagram **1200** with arrangements of one, two, and six individual lift vehicles **100**, respectively, each with an alternative six-rotor configuration **1101**. FIG. 12 shows a single individual lift vehicle **100** with an alternative six-rotor configuration **1101** placed within the positioning diagram **1200**. The positioning diagram **1200** illustrates how the edges of triangular shaped individual lift vehicles **100** may be placed adjacent to, and potentially abutting, one another when creating a unified lift vehicle **200**. FIG. 13 shows the potential placement of two individual lift vehicles **100**, each with the alternative six-rotor configuration **1101**, in creating a unified lift vehicle **200** via connection mechanisms **202**. FIG. 14 similarly shows a unified lift vehicle **200** having six individual lift vehicles **100** with alternative six-rotor configurations **1101**.

As previously discussed, individual lift vehicles **100** of a unified lift vehicle **200** are rigidly connected via connection mechanisms **202**. Various embodiments of the connection mechanisms **202** will now be described. The connection mechanisms **202** of FIGS. 15-20 will be discussed in the context of coupling individual lift vehicles **100** having the four-rotor configuration **101** of FIGS. 1-6C. It should be appreciated that the same connection mechanisms **202**, or similar connection mechanisms modified according to the particular implementation, may be utilized to connect any individual lift vehicles **100** having any configuration to create a unified lift vehicle **200**.

Looking at FIGS. 15 and 16, perspective and exploded views, respectively, of a connection mechanism **202** are shown. FIG. 17 depicts a perspective view of individual lift vehicles **100** being coupled with the connection mechanism **202**. According to this example, the connection mechanism **202** is an edge connector **1500**, which is used for rigidly and communicatively connecting two adjacent connector junctions **110** of adjacent individual lift vehicles **100**, as shown in FIG. 17. Examples can additionally be seen in FIGS. 2A, 2C, and at the exterior edges of the unified lift vehicle **200** shown in FIG. 3A, among others. The edge connector **1500** may include a top half **1504**, a bottom half **1506**, associated fasteners **1508**, and connection apertures **1502** at each end of the edge connector **1500**. The connection apertures may be defined by the top half **1504** and bottom half **1506** when joined together as seen in FIG. 15, and may be sized and shaped to receive the connector junctions **110** of the individual lift vehicles **100**.

According to one embodiment, the connection mechanisms **202** may each include signal transfer lines **1510** extending between opposing connection apertures **1502**. The signal transfer lines **1510** may be of the type to transfer electrical and/or data signals between adjacent individual lift vehicles **100**. Each connection aperture **1502** may have one or more connectors for communicatively coupling the signal transfer lines **1510** of the connection mechanism **202** to the distribution lines **122** of the adjacent individual lift vehicles **100**. FIGS. 15 and 16 each illustrate two alternative embodiments for these connectors.

First, a wall-positioned connector **1512** may be located in the top half **1504** and/or the bottom half **1506** of the connection mechanism **202** and configured to mate with a corresponding connector at an outer surface of the connector junction **110** of the individual lift vehicles **100**. In doing so, the wall-positioned connector **1512** may be mated with the corresponding connector of an individual lift vehicle **100** when the top half **1504** and the bottom half **1506** of the connection mechanism **202** are placed around the connector junctions **110** of the adjacent individual lift vehicles **100** such that the connector junctions **110** are sandwiched

11

between the top half **1504** and the bottom half **1506** within the connection apertures **1502**. This action is indicated by the open arrow rising upward from the wall-positioned connector **1512** in FIG. **16**.

Alternatively, an end connector **1514** may be located at or near the inner end of each of the connection apertures **1502** and configured to mate with a corresponding connector at an end of each of the connector junction **110** of the individual lift vehicles **100** being coupled together. In doing so, the end connector **1514** may be mated with the corresponding connector of an individual lift vehicle **100** when the connector junction **110** is slid into a connection aperture **1502**. This action is indicated by the open arrow extending inward toward the end connector **1514** in FIG. **16**.

It should be noted that FIGS. **15** and **16** show both a wall-positioned connector **1512** and an end connector **1514** used within a single connection mechanism **202** for illustrative purposes. However, each connection mechanism **202** may include a single type of connector depending on the particular application. Moreover, the wall-positioned connector **1512** and the end connector **1514** are depicted as ovals using broken lines to convey that any suitable type of connectors may be used depending on the application. Other connector types may include a male/female type push pin connection where the connection junction **110** may include a female electrical connector and the connection mechanism **202** may include a corresponding male electrical connector for communicatively connecting the distribution lines **122** of adjacent individual lift vehicles **100**. This disclosure is not limited to any particular type of connector, or any specific placement of the connector on or within the connection mechanism **202**.

FIG. **17** shows a perspective view of individual lift vehicles **100** being coupled with the edge connector **1500**. According to this embodiment, the connector junctions **110** are positioned within the connection apertures **1502** of the bottom half **1506** of the edge connector **1500** and sandwiched in place by the top half **1504**. The appropriate signal connections are made via the wall-positioned connector **1512** or the end connector **1514** (connectors not shown in FIG. **17**) prior to securing the top half **1504** and bottom half **1506** together using the fasteners **1508**. According to various embodiments, the fasteners **1508** may be of an appropriate material and size to shear during a crash in order to mitigate damage to the individual lift vehicles **100**. In other examples, connection between the connection junction **110** and the connection mechanism **202** may be facilitated by a compression fit, band or saddle type clamp, or similar type connection structure and method.

Looking at FIGS. **18** and **19**, perspective and exploded views, respectively, of a connection mechanism **202** is shown. FIG. **20** depicts a perspective view of individual lift vehicles **100** being coupled using the connection mechanism **202**. According to this example, the connection mechanism **202** is a central connector **1800**, which is used for rigidly and communicatively connecting three or more adjacent connector junctions **110** of adjacent individual lift vehicles **100**, as shown in FIG. **20**. In this example, the central connector **1800** is configured to rigidly couple four connector junctions **110** of four corresponding individual lift vehicles **100**. An example of this use may be seen in the center of the unified lift vehicle **200** shown in FIG. **3A**.

The central connector **1800** may include a top half **1804**, a bottom half **1806**, associated fasteners **1508**, and connection apertures **1802** at each end of the central connector **1800**. The connection apertures **1802** may be defined by the top half **1804** and bottom half **1806** when joined together as

12

seen in FIG. **18**, and may be sized and shaped to receive the connector junctions **110** of the individual lift vehicles **100**. Although not shown in FIGS. **18-20** for clarity purposes, the central connector **1800** may include signal transfer lines **1510** and associated connectors, such as the wall-positioned connector **1512** or the end connector **1514**, described above with respect to the edge connector **1500**.

FIG. **20** shows a perspective view of individual lift vehicles **100** being coupled with the central connector **1800**. According to this embodiment, the connector junctions **110** are positioned within the connection apertures **1802** of the bottom half **1806** of the central connector **1800** and sandwiched in place by the top half **1804**. The appropriate signal connections are made via the wall-positioned connector **1512** or the end connector **1514** (connectors not shown in FIG. **20**) prior to securing the top half **1804** and bottom half **1806** together using the fasteners **1508**. As discussed above, the fasteners **1508** may be of an appropriate material and size to shear during a crash in order to mitigate damage to the individual lift vehicles **100**.

FIGS. **21A** and **21B** illustrate the circuits **2100** created by the communicative coupling of the distribution lines **122** of the individual lift vehicles **100** of a unified lift vehicle **200** via the signal transfer lines **1510** of the connection mechanisms **202** according to one embodiment. FIG. **21A** shows the circuits **2100** that provide for electrical and/or data transmission between the individual lift vehicles **100**. In the context of power distribution, the wiring in the individual lift vehicles **100** and corresponding unified lift vehicle **200** may have a designated polarity such as positive **2102** (represented with broken lines) and negative **2104** (represented with solid lines).

According to various embodiments, each individual lift vehicle **100** includes its own power source **124**, such as a battery stored within the hub **126** or other location as described above. In this manner, each power source **124** may be dedicated to the associated individual lift vehicle **100** in which it is located. Alternatively, power may be shared amongst the individual lift vehicles **100** of a unified lift vehicle **200** via the circuits **2100**. According to one embodiment, a ground power supply line may be used to connect and charge all of the batteries within the unified lift vehicle **200** via a ground power receptacle (not shown) that is electrically connected to the circuits **2100**.

The circuits **2100** may additionally or alternatively be configured to communicatively connect the individual lift vehicles **100** so that data may be transferred between the individual lift vehicles **100**. According to one embodiment, control data may include any computer-implemented instructions or other input that when implemented, may cause one or more speed controllers **114** to alter a speed of a motor **106** and corresponding rotor **104** to affect a flight characteristic of an individual lift vehicle **100** or unified lift vehicle **200**.

According to one embodiment, the control data may be sent wirelessly from a remote control device to each controller **140** associated with each individual lift vehicle **100**. Each controller **140** may then control the appropriate drive unit **102** according to the control data over the circuits **2100** to arrive at the desired result. For example, the remote control device may direct a command to a controller **140**, the command corresponding to an instruction to increase the speed of one or more drive units **102**. The controller **140** may then send an appropriate signal to the speed controller **114** to produce the desired result.

Alternatively, according to another embodiment, the control data may be sent to a controller **140**. The controller **140**

13

then makes the appropriate control command determinations according to the received control data. For example, the controller **140** may interpret the received control data and determine that an operational parameter of a particular individual lift vehicle **100**, or of a particular drive unit **102** of a particular individual lift vehicle **100**, may need to be altered. The controller **140** may then transmit an appropriate command or signal to the applicable individual lift vehicle **100** or drive unit **102** via the circuits **2100** to achieve the desired change. In this manner, a controller **140** of one of the individual lift vehicles **100** of the unified lift vehicle **200** may be used to interpret the flight control input and to provide the appropriate commands to the appropriate individual lift vehicles **100** for producing the desired response. In this embodiment, other controllers **140** may provide redundancy in the event of an operational inconsistency.

Moreover, according to one embodiment, the unified lift vehicle **200** may include one or more data ports (not shown) communicatively coupled to the circuits **2100**, allowing for a wired connection to a source for control data. This implementation may be useful for programming flight parameters of a lift mission into the unified lift vehicle **200** for autonomous flight for all or some of the mission.

FIG. **21B** shows an expanded view of the central connector **1800** with representations of the positive **2102** (represented with broken lines) and negative **2104** (represented with solid lines) wiring polarities associated with the central connector **1800** as it communicatively connects to the circuits **2100**. Embodiments of the connection mechanisms **202** provide for modular, interchangeable components for ease of use and a reduced part count. In other words, the top halves **1504** and the bottom halves **1506** of the edge connectors **1500** are interchangeable. Similarly, the top halves **1804** and the bottom halves **1806** of the central connectors **1800** are interchangeable. Each connection mechanism **202** half includes an identical jumper circuit, such as the signal transfer lines **1510**, to transfer power and data between individual lift vehicles **100** regardless of the positioning of the component as a top half or a bottom half of the connection mechanism **202**. The wiring within the individual lift vehicles **100** is configured to force the positive **2102** pole to be carried by the top half of the connection mechanisms **202**, while the negative **2104** pole is carried by the bottom half of the connection mechanisms **202**.

Turning now to FIGS. **22-33**, a remote control device, associated user interface, and a configuration process for performing a lift mission with a unified lift vehicle **200** will be described according to various embodiments. FIG. **22** shows a user interface **2202** of a remote control device **2200**. It should be appreciated that the user interface **2202** shown and described herein is an example used for illustrative purposes and should not be construed as limiting. Rather, the user interface **2202** may be configured as desired according to the desired configuration processes and the desired format of the control inputs for controlling the unified lift vehicle **200**.

According to one embodiment, the remote control device **2200** may include a tablet computer device, a smartphone, or any handheld remote control input device. A lift mission application **2204** stored on the remote control device **2200** is operative to execute computer-controlled instructions for performing the configuration process operations described below. It should be understood that the remote control device **2200** may include a processor, volatile and/or non-volatile memory, an operating system, and all hardware and software used for wireless communication with the individual lift vehicles **100** and unified lift vehicle **200**.

14

As discussed above, each individual lift vehicle **100** is capable of controlled three-axis flight in response to inputs from the remote control device **2200**. Utilizing concepts described herein, a unified lift vehicle **200** created from any number of individual lift vehicles **100** is also operative to perform controlled three-axis flight in response to inputs from the remote control device **2200**. In order to direct appropriate control commands to the appropriate individual lift vehicles **100** or drive units **102**, the remote control device **2200** provides the user interface **2202** for receiving all applicable data regarding the unified lift vehicle **200** and the corresponding lift mission during a configuration process. Accordingly, the user interface **2202** includes a number of user input controls for initiating various processes.

According to the example shown in FIG. **22**, the user input controls include a define payload control **2204**, a define formation control **2206**, a define waypoints control **2208**, a validate control **2210**, and a run control **2212**. Fewer or additional user input controls may be utilized without departing from the scope of this disclosure. As seen in FIG. **23**, a user may select the define payload control **2204** to initiate the configuration process for a lift mission. According to one embodiment, upon selecting the define payload control **2204**, the user interface **2202** displays a general schematic of a rectangular payload **130**, shown in FIG. **24**. According to various embodiments, other payload shapes may be selected from a menu, or a custom shape created. The user is able to identify attachment positions **2402** in which the unified lift vehicle **200** will be attached to the payload **130** using cables or chains. Alternatively, the attachment positions **2402** may be identified by the lift mission application **2204** after the user has input all other applicable data associated with the payload and unified lift vehicle **200**. The user may also identify the center of gravity **2404**, as well as provide the dimensions **2406** and weight **2408** of the payload.

After the applicable characteristics of the payload **130** have been defined, the user may select the define formation control **2206**. Using this user control input, the formation of the unified lift vehicle **200** will be defined with respect to the number and placement of individual lift vehicles **100** within the unified lift vehicle **200**. FIGS. **26-29** show a modular vehicle lift system **2600** according to various operations in the configuration process. The modular vehicle lift system **2600** includes a unified lift vehicle **200** as described above, as well as the remote control device **2200** with the lift mission application **2204**. According to one embodiment, upon selecting the define formation control **2206**, the user interface **2202** displays a positioning diagram **2604**, as seen in FIG. **26**. The positioning diagram **2604** may include any number of potential positions **2606** within a formation of individual lift vehicles **100** that create the unified lift vehicle **200**.

According to one embodiment, the user may select the appropriate number and position of the individual lift vehicles **100** corresponding to the desired formation used for the unified lift vehicle **200** by touching the positioning diagram **2604** on the user interface **2202** at the appropriate potential positions **2606**. As shown in FIG. **26** and discussed briefly above, the formation of the unified lift vehicle **200** does not have to be symmetric. Rather an asymmetric formation as shown may be beneficial depending on the parameters of the lift mission. For example, the unified lift vehicle **200** may be used to place a piece of equipment on a rooftop that has numerous obstacles projecting from the roof. An asymmetric formation may allow for the unified lift

15

vehicle **200** to position the payload **130** precisely while accommodating the obstacles.

According to another embodiment, the lift mission application **2204** may select or suggest an appropriate formation for the unified lift vehicle **200**, including the number and positioning of the individual lift vehicles **100**. To do so, the lift mission application **2204** may utilize the payload information input by the user, taking into account the performance capabilities of an individual lift vehicle **100**. The lift mission application **2204** may provide multiple formation options, allowing the user to select one for use. Yet another alternative includes the lift mission application **2204** suggesting a formation, while allowing the user to customize the formation as long as the customized formation provides the minimum performance capabilities for the particular lift mission.

Upon selection of the number and positioning of the individual lift vehicles **100** within the unified lift vehicle **200**, the user may assemble the unified lift vehicle **200** using the appropriate connection mechanisms **202** and attach the payload **130**. The user may then select a begin registration control **2602** to initiate a registration process used to establish the position of each individual lift vehicle **100** with respect to the other individual lift vehicles **100** of the unified lift vehicle **200**. According to one embodiment, the individual lift vehicles **100** recognize other vehicles connected to the circuit **2100** and hold a lottery to cause a single random individual lift vehicle **100** to flash or otherwise identify itself. This notification to the user is indicated by the large star **2702** over one of the individual lift vehicles **100** in FIG. **27**. The user selects the corresponding representation of that individual lift vehicle **100** in the formation on the positioning diagram **2604**, as shown in FIG. **28**. In response, the remote control device **2200** establishes the relative location of the individual lift vehicle **100** with respect to the overall formation. This information is then sent to the controller **140** on the individual lift vehicle **100**.

Upon successfully establishing communications with the remote control device **2200**, the individual lift vehicle **100** may then provide a registered indicator **2702** to provide the user with a notification that the individual lift vehicle **100** has been successfully registered. The representation of the individual lift vehicle **100** on the positioning diagram **2604** may also change to notify the user that the registration process for that individual lift vehicle **100** is complete. In this example, the representation of the individual lift vehicle **100** on the positioning diagram **2604** changes from broken lines to solid lines, however, any applicable notification may be used within the scope of this disclosure.

This registration process continues as shown in FIG. **29** until all of the individual lift vehicles **100** have been successfully registered. In this manner, the lift mission application **2204** establishes the position of each individual lift vehicle **100** relative to the other individual lift vehicles **100** of the formation and provides that information to the controllers **140** of the individual lift vehicles **100**. Based on this information, the lift mission application **2204** adapts the control instructions for controlling the multiple drive units **102** of an individual lift vehicle **100** for controlled three-axis flight to controlling the multiple individual lift vehicles **100** of the unified lift vehicle **200** for controlled three-axis flight. When registration is complete, each individual lift vehicle **100** is assigned a number as shown in FIG. **29**. This number is not only used for control purposes, but also for the purposes of health monitoring as well as notifying the user in the event of an operational inconsistency.

16

The control of the unified lift vehicle **200** during the lift mission may occur in various manners. First, the remote control device **2200** and corresponding lift mission application **2204** establishes where each individual lift vehicle **100** is located relative to the others during the registration process. Each individual lift vehicle **100** is then assigned its own mode or category based on its positioning as if it were a control surface of an aircraft so that it responds accordingly to commands directed to that control surface. For example, if a roll command is provided by the remote control device **2200**, the individual lift vehicles **100** located off to the sides from the center of gravity of the unified lift vehicle **200** will drive all four rotors **104** at a similar rate to initiate the roll. Because the individual lift vehicles **100** know their relative position from the center of gravity, they can calculate from their own inertial measurement units the attitude of the unified lift vehicle **200**. A benefit of this control method is that a central computer is not required to capture the state of each individual lift vehicle **100**. Alternatively, all vehicle data associated with each individual lift vehicle **100** may be downlinked to the remote control device **2200**. The remote control device **2200** may then process the data and send individual control signals to each individual lift vehicle **100**.

According to various embodiments, the unified lift vehicle **200** may be controlled autonomously during the lift mission so that user input is not provided, may be controlled manually by the user via controls on the remote control device **220**, or a combination of the two. An example lift mission may include autonomous flight from a starting location, through one or more waypoints to a target location at which the user manually flies the unified lift vehicle **200** and attached payload **130** into position. If all or a portion of the lift mission is to be performed autonomously, then the route, including any waypoints, is to be input into the user interface **2202** for use by the lift mission application **2204**. FIG. **30** shows the initiation of an example procedure for defining waypoints for a lift mission. After selecting a define waypoints control **2208** on the user interface **2202**, the lift mission application **2204** displays a map **3100**, as shown in FIG. **31**.

The map **3100** may include an overhead view of an area encompassing the lift mission. The user may create and revise waypoints **3102** and the flight route **3104** via a touchscreen of the user interface **2202**. Alternatively or additionally, the user may use a keyboard to input the waypoint **3102** information, which is then used by the lift mission application **2204** to display the map **3100** and associated waypoints **3102**. According to various embodiments, any quantity and type of lift mission data **3106** may be displayed in textual format in addition to or in place of the map **3100**.

After the waypoints **3102** have been defined, the user may select the validate control **2210**, as shown in FIG. **32**. The validate control **2210** initiates a validation process that ensures that the unified lift vehicle **200** has been properly configured and is responding appropriately to flight command input. According to one embodiment, when the validation process begins, the remote control device **2200** will test the communication with all individual lift vehicles **100** and will initiate a test lift of the payload **130**. Once the payload **130** has been lifted a predetermined distance, the lift mission application **2204** may validate threshold sensor data from each individual lift vehicle **100** to ensure that each control and sensor suite **118** and each drive unit **102** is functioning within allowed parameters. Any anomalies will be noted. When validation is complete, the user selects the

run control **2212** as shown in FIG. **33** and the lift mission commences and proceeds as programmed.

If all or any portion of the lift mission is to be flown manually, the remote control device **2200** may provide a user interface **2202** having manual controls **3402**, as seen in FIG. **34**. According to this example, the user interface **2202** may include any number and type of information or control areas, including but not limited to, the map **3100**, a health monitor **3402**, and manual controls **3404**. The map **3100** may show an overhead view of an area encompassing the lift mission, including the waypoints **3102** and the flight route **3104** defined during the configuration process described above. The map **3100** may additionally highlight or otherwise identify the current location of the unified lift vehicle **200** on the flight route **3104** in real time during the lift mission.

The health monitor **3402** may provide a representation of the unified lift vehicle **200**, including the assigned numbers of each individual lift vehicle **100** within the formation. If an operational inconsistency is detected with respect to an individual lift vehicle **100** during the lift mission, notification may be provided to the user by the health monitor **3402**. Notification may take the form of a flashing number associated with the individual lift vehicle **100**, a change in color of the individual lift vehicle **100** or corresponding number, or any other suitable visual and/or audible notification mechanism.

The manual controls **3404** may include primary controls **3406** and precision controls **3408**, according to one embodiment. Using the primary controls **3406**, a user may command the unified lift vehicle **200** to perform a counter clockwise rotation (CCW), a clockwise rotation (CW), to move up, down, left, right, forward, and reverse. These commands may occur sequentially or simultaneously. The precision controls **3408** may be used to “nudge” the unified lift vehicle **200**, or provide substantially minor control input, according to the adjacent primary control **3406** command. For example, to provide a very minor altitude correction and nudge the unified lift vehicle **200** downward slightly during payload delivery, the user may press the precision control **3408** adjacent to the down control of the primary controls **3408**.

Turning now to FIG. **35**, additional details will be provided regarding embodiments presented herein for maneuvering a payload **130** utilizing a modular vehicle lift system **2600**. It should be appreciated that the logical operations described herein may be implemented (1) as a sequence of computer implemented acts or program modules running on a computing system and/or (2) as interconnected machine logic circuits or circuit modules within the computing system. The implementation is a matter of choice dependent on the performance and other operating parameters of the computing system. Accordingly, the logical operations described herein are referred to variously as operations, structural devices, acts, or modules. These operations, structural devices, acts, and modules may be implemented in software, in firmware, hardware, in special purpose digital logic, and any combination thereof. It should also be appreciated that more or fewer operations may be performed than shown in the figures and described herein. These operations may also be performed in parallel, or in a different order than those described herein.

FIG. **35** shows a routine **3500** for maneuvering a payload **130** utilizing a modular vehicle lift system **2600**. The routine **3500** begins at operation **3502**, where the payload **130** is defined. As discussed above, the user may input various characteristics of the payload **130** into the user interface

2202 provided by the lift mission application **2204**. These characteristics may include, but are not limited to, dimensions **2406**, weight **2408**, center of gravity **2404**, and attachment positions **2402**. The representation of the payload **130** on the user interface **2202** may be rectangular in shape and may allow the user to select different views or rotate the view to input additional attachment positions **2402** or dimensions **2406**. According to various embodiments, additional shapes corresponding to the payload **130** may be pre-programmed and selected, or the shape may be customizable.

When the payload **130** has been defined in the remote control device **2200**, the routine **3500** continues to operation **3504**, where the formation of individual lift vehicles **100** within the unified lift vehicle **200** is determined. Based at least in part on the characteristics of the payload **130** being lifted and maneuvered, the lift mission application **2204** may suggest one or more formations for the unified lift vehicle **200**, including number and positioning of the individual lift vehicles **100**. From operation **3504**, the routine **3400** continues to operation **3506**, where the individual lift vehicles **100** are rigidly and communicatively connected using the appropriate connection mechanisms **202**. According to one embodiment, edge connectors **1500** may be used to join two adjacent connection junctions **110** of two individual lift vehicles **100**, while central connectors **1800** may be used to join four connection junctions **110** associated with four individual lift vehicles **100**. Each connection mechanism **202** may have a top half (**1504,1804**) and an identical bottom half (**1506,1806**). The top and bottom halves are assembled to sandwich the corresponding connection junctions **110** of the individual lift vehicles **100**, completing the circuits **2100** and rigidly connecting the individual lift vehicles **100** to create the unified lift vehicle **200**.

At operation **3508**, the individual lift vehicles **100** are registered. The registration process provides the lift mission application **2204** with positioning information for each individual lift vehicle **100**, as well as providing the individual lift vehicles **100** with their positions relative to others in the unified lift vehicle **200**. The routine **3500** continues from operation **3508** to operation **3510**, where the waypoints **3102** are defined. During this process, the user may textually input the locations of the waypoints **3102**, may use a touchscreen interface to identify the waypoints **3102** on a map **3100**, or may input the waypoints **3102** in any other available means. Alternatively, the user may remotely control the lift mission manually without providing any waypoint information. With the waypoints **3102** and corresponding flight route **3104** identified, the routine **3500** continues to operation **3512**, where the lift mission application **2204** validates the formation and controls.

As described above, the validation process tests the communications between the individual lift vehicles **100**, as well as between the unified lift vehicle **200** and the remote control device **2200**. The control inputs from the remote control device **2200** to the unified lift vehicle **200** are additionally tested, as is the ability to lift and maneuver with the payload **130**.

When the validation is complete, the routine **3500** proceeds to operation **3514**, where the lift mission is initiated. The user may press the run control **2212** to initiate the mission. If autonomous flight is planned, the unified lift vehicle **200** will fly the designated flight route **3104** via waypoints **3102**. At any time during the mission, or at a designated waypoint **3102**, the user may manually override

19

the autonomous flight operation and manually control the unified lift vehicle **200** via the manual controls **3404** on the remote control device **2200**.

At operation **3516**, the health or operational status of the individual lift vehicles **100** is monitored. The health may be monitored by the control and sensor suite **118** of each individual lift vehicle **100** during all phases of the lift mission. If an operational inconsistency is detected, notification is provided to the lift mission application **2204** and provided to the user via the user interface **2202**. At operation **3518**, when the lift mission is complete, the lift mission application **2204** or the user shuts down the drive units **102** of the individual lift vehicles **100** and the mission is terminated.

The subject matter described above is provided by way of illustration only and should not be construed as limiting. Various modifications and changes may be made to the subject matter described herein without following the example embodiments and applications illustrated and described, and without departing from the true spirit and scope of the present disclosure, which is set forth in the following claims.

What is claimed is:

1. A unified lift vehicle for maneuvering a payload, comprising:
 - a plurality of individual lift vehicles, each individual lift vehicle operative to perform controlled three-axis flight separately from other individual lift vehicles; and
 - a plurality of connection mechanisms rigidly and communicatively connecting the plurality of individual lift vehicles in a lifting array formation to create the unified lift vehicle operative to perform three-axis flight, each connection mechanism comprising either a wall-positioned connector configured to mate with an outer surface of a connector junction of an individual lift vehicle or an end connector configured to mate with an end of the connector junction of the individual lift vehicle.
2. The unified lift vehicle of claim 1, further comprising a controller operative to receive control data from a remote control device and to control an individual lift vehicle according to the control data.
3. The unified lift vehicle of claim 1, wherein each individual lift vehicle comprises:
 - four drive units rigidly coupled to one another to create a four-rotor configuration, each drive unit comprising a motor and a rotor coupled to the motor, wherein each individual lift vehicle comprises only four drive units such that four rotors provide all thrust for the individual lift vehicle;
 - a power source coupled to the four drive units; and
 - a controller communicatively coupled to the four drive units and operative to receive control data, and to control each of the four drive units according to the control data.
4. The unified lift vehicle of claim 3, wherein the four drive units are rigidly coupled to one another in a 2x2 configuration via a frame extending outward from a hub centrally located within the individual lift vehicle between the four drive units.
5. The unified lift vehicle of claim 1, further comprising a speed controller communicatively coupled to each motor and to the controller and operative to receive control data from the controller and alter the speed of the motor according to the control data.

20

6. The unified lift vehicle of claim 1, further comprising a control and sensor suite operative to autonomously control the unified lift vehicle and a payload along a flight route via at least one waypoint.

7. The unified lift vehicle of claim 1, further comprising a circuit communicatively coupling the plurality of individual lift vehicles via the plurality of connection mechanisms.

8. The unified lift vehicle of claim 1, wherein each connection mechanism comprises a top half and a bottom half that are identical and interchangeable.

9. The unified lift vehicle of claim 8, wherein each connection mechanism comprises a plurality of connection apertures defined by the top half and the bottom half when joined together, each connection aperture sized and shaped to receive the connector junction of one individual lift vehicle.

10. The unified lift vehicle of claim 9, wherein the top half and the bottom half each comprise a signal transfer line extending between the plurality of connection apertures and configured to transfer electrical or data signals between adjacent individual lift vehicles.

11. The unified lift vehicle of claim 10, wherein the top half and the bottom half each comprise the wall-positioned connector configured to mate with a corresponding connector at the outer surface of the connector junction of the individual lift vehicle and to communicatively couple the signal transfer line to a distribution line of the individual lift vehicle.

12. The unified lift vehicle of claim 10, wherein the top half and the bottom half each comprise the end connector configured to mate with a corresponding connector at the end of the connector junction of the individual lift vehicle and to communicatively couple the signal transfer line to a distribution line of the individual lift vehicle.

13. The unified lift vehicle of claim 8, wherein the plurality of connection mechanisms comprise a plurality of edge connectors and a central connector, wherein each edge connector is configured to rigidly and communicatively connect two adjacent individual lift vehicles and wherein the central connector is configured to rigidly and communicatively connect more than two adjacent individual lift vehicles.

14. A modular vehicle lift system, comprising:

a plurality of individual lift vehicles positioned adjacent to one another according to a lifting array formation, each individual lift vehicle operative to perform controlled three-axis flight separately from other individual lift vehicles and comprising:

four drive units rigidly coupled to one another to create a four-rotor configuration, each drive unit comprising a motor and a rotor coupled to the motor, wherein each individual lift vehicle comprises only four drive units such that the four drive units provide all thrust for the individual lift vehicle, and

a controller communicatively coupled to the four drive units and operative to receive control data from a remote control device and to control each of the four drive units according to the control data;

a plurality of connection mechanisms rigidly and communicatively connecting the plurality of individual lift vehicles in the lifting array formation to create a unified lift vehicle operative to perform three-axis flight, each connection mechanism comprising either a wall-positioned connector configured to mate with an outer surface of a connector junction of an individual lift

21

vehicle or an end connector configured to mate with an end of the connector junction of the individual lift vehicle; and

the remote control device operative to provide the control data to the controller of each individual lift vehicle and control the unified lift vehicle in three-axis flight.

15 15. The modular vehicle lift system of claim 14, wherein each connection mechanism comprises a top half and a bottom half that are identical and interchangeable.

16. The modular vehicle lift system of claim 15, wherein the top half and the bottom half each comprise a signal transfer line extending between the plurality of connection apertures and configured to transfer electrical or data signals between adjacent individual lift vehicles.

17. The modular vehicle lift system of claim 16, wherein the plurality of connection mechanisms comprise a plurality of edge connectors and a central connector, wherein each edge connector is configured to rigidly and communicatively connect two adjacent individual lift vehicles and wherein the central connector is configured to rigidly and communicatively connect more than two adjacent individual lift vehicles.

18. A method for maneuvering a payload utilizing a modular vehicle lift system, the method comprising:

rigidly and communicatively coupling a plurality of individual lift vehicles with a plurality of connection mechanisms via either a wall-positioned connector of each connection mechanism configured to mate with an outer surface of a connector junction of an individual lift vehicle or an end connector of each connection mechanism configured to mate with an end of the connector junction of the individual lift vehicle to create a unified lift vehicle, wherein each individual lift vehicle is operative to perform controlled three-axis flight separately from other individual lift vehicles; coupling the payload to the unified lift vehicle; and providing flight commands to the unified lift vehicle to maneuver the payload in three-axis flight.

19. The method of claim 18, wherein for each adjoining pair of individual lift vehicles to be connected, rigidly and communicatively coupling the plurality of individual lift vehicles with the plurality of connection mechanisms comprises:

positioning a connection junction of a first individual lift vehicle within a first connection aperture of a first half of a connection mechanism;

22

positioning a connection junction of a second individual lift vehicle within a second connection aperture of the first half of the connection mechanism;

placing a second half of the connection mechanism over the first half; and

securing the first half to the second half.

20. The method of claim 19, further comprising:

communicatively coupling the connection junction of the first individual lift vehicle to a signal transfer line of the connection mechanism when positioning the connection junction within the first connection aperture; and communicatively coupling the connection junction of the second individual lift vehicle to the signal transfer line of the connection mechanism when positioning the connection junction within the first connection aperture.

21. The method of claim 18, further comprising:

determining a formation of the individual lift vehicles for the unified lift vehicle;

registering the individual lift vehicles to identify a position of each individual lift vehicle within the formation; and

identifying a plurality of individual lift vehicles for control according to the position of the identified lift vehicles and the flight commands,

wherein providing flight commands to the unified lift vehicle comprises providing the flight commands to the plurality of individual lift vehicles identified for control.

22. The method of claim 21, further comprising defining characteristics of the payload within a remote control device, wherein determining the formation of the individual lift vehicles for the unified lift vehicle comprises determining the number and positioning of the individual lift vehicles within the unified lift vehicle according to the characteristics of the payload and performance capabilities of each individual lift vehicle.

23. The method of claim 18, further comprising defining waypoints and a flight route within a remote control device, wherein providing flight commands to the unified lift vehicle to maneuver the payload in three-axis flight comprises initiating autonomous flight according to the waypoints and the flight route.

* * * * *