



(12) **United States Patent Hand**

(10) **Patent No.:** US 9,457,918 B2
(45) **Date of Patent:** Oct. 4, 2016

- (54) **MULTI-STAGE SPACE LAUNCH SYSTEMS WITH REUSABLE THRUST AUGMENTATION AND ASSOCIATED METHODS**
- (71) Applicant: **The Boeing Company**, Seal Beach, CA (US)
- (72) Inventor: **Michael Leslie Hand**, Huntington Beach, CA (US)
- (73) Assignee: **The Boeing Company**, Chicago, IL (US)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 213 days.

(21) Appl. No.: **14/219,818**
(22) Filed: **Mar. 19, 2014**

(65) **Prior Publication Data**
US 2015/0266593 A1 Sep. 24, 2015

- (51) **Int. Cl.**
B64G 1/00 (2006.01)
B64G 5/00 (2006.01)
B64G 1/58 (2006.01)
B64G 1/62 (2006.01)
B64G 1/64 (2006.01)
B64G 1/40 (2006.01)
B64G 1/36 (2006.01)

(52) **U.S. Cl.**
CPC **B64G 1/002** (2013.01); **B64G 1/58** (2013.01); **B64G 1/62** (2013.01); **B64G 1/641** (2013.01); **B64G 1/645** (2013.01); **B64G 5/00** (2013.01); **B64G 1/36** (2013.01); **B64G 1/401** (2013.01); **B64G 1/402** (2013.01)

(58) **Field of Classification Search**
CPC B64G 1/005; B64G 1/002; B64G 1/64; B64G 1/40; B64G 1/401; B64G 1/62
See application file for complete search history.

- (56) **References Cited**
U.S. PATENT DOCUMENTS
- 3,013,747 A * 12/1961 Grihangne B64C 25/32 244/100 A
- 4,723,736 A * 2/1988 Rider B64G 1/002 102/377
- 4,834,324 A * 5/1989 Criswell B64G 1/002 244/158.9
- 4,964,340 A * 10/1990 Daniels B64G 1/002 102/377
- 5,031,857 A * 7/1991 MacConochie B64C 3/40 244/159.3
- 5,667,167 A * 9/1997 Kistler B64G 1/002 244/110 E
- 6,454,216 B1 9/2002 Kiselev et al.
- 6,616,092 B1 * 9/2003 Barnes B64D 5/00 244/159.3
- 7,036,773 B2 * 5/2006 Caldwell B64G 1/002 244/137.4

(Continued)

OTHER PUBLICATIONS

Webpage for entry "DC-X" on Encyclopedia Astronautica at <http://www.astronautix.com/lvs/dcx.htm>, downloaded on Mar. 10, 2014.


(Continued)

Primary Examiner — Philip J Bonzell
Assistant Examiner — Michael Kreiner
(74) *Attorney, Agent, or Firm* — DASCENZO Intellectual Property Law, P.C.

(57) **ABSTRACT**

Systems and methods for launching space vehicles into outer space are disclosed. Systems include a launch vehicle with at least two stages. A thrust augmentation stage provides thrust during an initial portion of a launch trajectory. A first stage provides thrust during the initial portion and during a second portion of the launch trajectory. In some systems, the thrust augmentation stage is reusable with a distinct first stage. In some systems, the thrust augmentation stage defines a central bore, through which the first stage extends for initial launch of the launch vehicle.

36 Claims, 5 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

7,226,017 B2 * 6/2007 Blevio, Sr. B64C 25/32
244/1 R
8,498,756 B1 * 7/2013 Sarver B64G 1/62
701/1
8,678,321 B2 * 3/2014 Bezos B64G 1/002
114/261
8,844,876 B2 * 9/2014 Prampolini B64G 1/62
244/158.9
8,960,590 B2 * 2/2015 Rutan B64G 1/005
244/1 TD
9,033,276 B1 * 5/2015 Calvert B64C 25/10
244/102 R
9,073,647 B2 * 7/2015 Helou, Jr. B64G 1/14

9,174,749 B2 * 11/2015 Prampolini B64G 1/002
2015/0048212 A1 * 2/2015 Fricker B64G 1/645
244/158.1
2015/0375875 A1 * 12/2015 Dula B64G 1/002
244/171.3

OTHER PUBLICATIONS

Webpage for entry "McDonnell Douglas DC-X" on Wikipedia at http://en.wikipedia.org/wiki/McDonnell_Douglas_DC-X, downloaded on Mar. 10, 2014.
Delta IV Launch Services User's Guide, United Launch Alliance, Jun. 2013.

* cited by examiner




Fig. 1




Fig. 3

Fig. 2




Fig. 4




Fig. 5




Fig. 6




Fig. 7




Fig. 8

1

MULTI-STAGE SPACE LAUNCH SYSTEMS WITH REUSABLE THRUST AUGMENTATION AND ASSOCIATED METHODS

FIELD

The present disclosure relates to multi-stage space launch systems.

BACKGROUND

Historically, space launch systems have used varying numbers of strap-on solid rocket boosters to provide additional thrust to a multi-stage launch vehicle during an initial portion of a launch trajectory. Even though it may be possible to reuse solid rocket boosters in various circumstances, they typically are difficult and expensive to retrieve and reuse following a launch. Moreover the cost of such solid rocket boosters often is a significant portion of the overall cost associated with placing a space vehicle into outer space.

SUMMARY

Multi-stage space launch systems and methods for launching space vehicles into outer space are disclosed herein. Systems include a launch vehicle configured to operatively support a space vehicle for placement in outer space. The launch vehicle includes at least two stages, including a thrust augmentation stage configured to provide thrust for launching the space vehicle during an initial portion of a launch trajectory, and a first stage configured to be selectively coupled to and decoupled from the thrust augmentation stage and further configured to provide thrust for launching the space vehicle during both the initial portion of the launch trajectory and during a second portion of the launch trajectory following the initial portion of the launch trajectory. The thrust augmentation stage is configured to be selectively decoupled from the first stage during the launch trajectory and subsequently to be retrieved and reused following a launch of the launch vehicle. In some systems, the thrust augmentation stage may be described as a short-range thrust augmentation stage.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic diagram representing multi-stage space launch systems.

FIG. 2 is another schematic diagram representing multi-stage launch systems.

FIG. 3 is a flowchart schematically representing methods of launching a space vehicle into outer space.

FIG. 4 is a perspective view of an illustrative, non-exclusive example of a launch vehicle of a multi-stage launch system.

FIG. 5 is a perspective view of the thrust augmentation stage of the launch vehicle of FIG. 4.

FIG. 6 is a perspective view of the assembly of the first, second, and third stages of the launch vehicle of FIG. 4.

FIG. 7 is another perspective view of the thrust augmentation stage of the launch vehicle of FIG. 4.

FIG. 8 is a perspective view of an illustrative, non-exclusive example of landing structure for use with the thrust augmentation stage of the launch vehicle of FIG. 4.

DESCRIPTION

Multi-stage space launch systems and methods are disclosed herein. FIGS. 1-2 schematically represent illustrative,

2

non-exclusive examples of multi-stage space launch systems **10** according to the present disclosure, and FIG. 3 schematically represents illustrative, non-exclusive examples of methods **200** for launching space vehicles into outer space according to the present disclosure. In general, in FIG. 1, elements that are likely to be included within an example of a system **10** are illustrated schematically in solid lines, while elements that may be optional are illustrated schematically in dashed lines. Moreover, the methods and steps schematically represented in the flowchart of FIG. 3 are not limiting and other methods and steps are within the scope of the present disclosure, including methods having greater than or fewer than the number of steps illustrated, as understood from the discussions herein. Additionally, the illustrated steps are not required to be performed in the order illustrated in all methods according to the present disclosure. FIGS. 4-8 illustrate, somewhat less schematically, an illustrative, non-exclusive example of a multi-stage space launch system according to the present disclosure. Turning first to FIG. 1, as schematically illustrated, a multi-stage space launch system **10** includes at least a launch vehicle **12** that is configured to operatively support a space vehicle **14** for placement in outer space. The launch vehicle includes at least two stages **16** including a thrust augmentation stage **18** and a first stage **20** that is configured to be selectively coupled to and decoupled from the thrust augmentation stage; however, as schematically and optionally represented in FIG. 1, a launch vehicle may include more than two stages, including an optional second stage **22** that is configured to be selectively coupled to and decoupled from the first stage, and so forth. Any suitable number of stages may be incorporated into a launch vehicle **12**, including more than three stages, for example, depending on the mass of the space vehicle **14**, an orbit in which the space vehicle is to be placed by a system **10**, and/or whether or not the space vehicle is to remain in an orbit of Earth or be launched beyond Earth. Illustrative, non-exclusive examples of space vehicles include man-made satellites, such as communication or other types of satellites, inter-planet space vehicles, interstellar space vehicles, including unmanned space vehicles as well as manned space vehicles.

With reference to FIG. 2, the thrust augmentation stage **18** of a launch vehicle **12** is configured to augment the thrust of the first stage **20** for launching the space vehicle during at least an initial portion **21** of a launch trajectory **24**. The first stage **20** of a launch vehicle **12** is configured to provide thrust for launching the space vehicle during the initial portion **21** of the launch trajectory, as well as during a second portion **26** of the launch trajectory following the initial portion of the launch trajectory. In other words, the thrust augmentation stage and the first stage both provide thrust during the initial portion of a launch, and the first stage continues to provide thrust during the launch trajectory following the thrust augmentation stage, that is, during a second portion **26**. Stated differently, in examples of launch vehicles that utilize stages having combustion based engines, or rockets, the engines associated with both the thrust augmentation stage and the first stage may be lit on the ground, that is, at the initiation of a launch, so that both the thrust augmentation stage and the first stage provide thrust to the launch vehicle during the initial portion of the launch trajectory.

Any suitable length of the initial portion **21** of the launch trajectory **24** is within the scope of the present disclosure. As discussed herein, some thrust augmentation stages **18** may be described as short-range thrust augmentation stages, due to their optional landing within the vicinity of a position

from which the launch vehicle was launched. As illustrative, non-exclusive examples of short-range thrust augmentation stages, the initial portion of a launch trajectory may extend to a maximum elevation of one of 10, 20, 30, 40, or 50 kilometers. Additionally or alternatively, the initial portion of a launch trajectory may last for no more than 40, 50, 60, 70, 80, 90, or 100 seconds after liftoff of the launch vehicle. Additionally or alternatively, an initial portion of a launch trajectory may last until the launch vehicle reaches a speed of no more than Mach 2, Mach 3, Mach 4, or Mach 5.

As illustrative, non-exclusive examples only, the first stage **20** and optional second, third, and so forth stages **16** may correspond to and/or be adapted directly from existing space launch systems, such as the various Delta and Atlas space launch systems. That is, the first stage of such existing space launch systems may be adapted to become the first stage **20** of a system **10** according to the present disclosure, and thus configured to be used with a thrust augmentation stage according to the present disclosure.

Some embodiments of thrust augmentation stage **18** may be described as being reusable. For example, a thrust augmentation stage **18** may be configured to be selectively decoupled from the first stage **20** during the launch trajectory and subsequently retrieved and reused following a launch of a launch vehicle that includes the thrust augmentation stage. In some such embodiments, the thrust augmentation stage **18** may be configured to be selectively decoupled from the first stage during the launch trajectory and subsequently retrieved and reused with a distinct first stage to define a distinct launch vehicle for a subsequent launch of a distinct space vehicle into outer space. Additionally or alternatively, a thrust augmentation stage **18** may be configured to land on Earth following a launch, for example without significant, if any, damage to the thrust augmentation stage **18**. This optional configuration of a thrust augmentation stage is schematically illustrated in FIG. 2, with the thrust augmentation stage **18** separating from the first stage at the transition from the initial portion **21** to the second portion **26** of the launch trajectory **24**, and with the thrust augmentation stage returning to and landing on Earth **28**.

In some embodiments, the thrust augmentation stage **18** may be configured to land on Earth with the same orientation as the thrust augmentation stage was launched, for example, in a vertical orientation. In some embodiments, the thrust augmentation stage **18** may be configured to utilize the same source of thrust that is used during the initial portion **21** of the launch trajectory **24** to return to and land on Earth. For example, as discussed herein, the thrust augmentation stage **18** may include one or more engines **54**, with at least a subset of such engines providing thrust both for launching the launch vehicle during the initial portion of the launch trajectory and during a controlled descent **29** of the thrust augmentation stage **18** back to Earth, as schematically and optionally represented in FIG. 2. The controlled descent **29** additionally or alternatively may be described as a controlled landing **29**. By a controlled descent, or landing, it is meant that the thrust augmentation stage **18** may and at a predetermined location, for example, at or near a position from which the launch vehicle was initially launched, as discussed in more detail herein. Additionally or alternatively, controlled landing may mean that the descent and landing of the thrust augmentation stage does not result in significant damage to the thrust augmentation stage and/or does not result in significant cost to retrieve and/or reuse the thrust augmentation stage.

As illustrative, non-exclusive examples, a thrust augmentation stage **18** may include four, six, eight, ten, or more than ten even-numbered engines, with all of the engines being used during the initial portion of the launch and with only a subset (e.g., one-half) of the engines being used for the controlled descent **29**. Moreover, the subset of the engines used for the controlled descent may be evenly spaced around the longitudinal axis **31** of the thrust augmentation stage, so as to have a thrust vector that is aligned with the center of mass of the thrust augmentation stage.

As schematically illustrated in FIG. 1, some systems **10** also may include a land-based landing structure **30** that is configured to selectively mate with the thrust augmentation stage **18** following a launch, that is, when the thrust augmentation stage returns to Earth, for example, in systems **10** in which the thrust augmentation stage is configured to be retrieved and reused following a launch. Similarly, in such embodiments, the thrust augmentation stage **18** is configured to mate with the landing structure **30** following a launch when the thrust augmentation stage returns to Earth. In some embodiments, the thrust augmentation stage **18** may include a plurality of shear cones **32** positioned at the aft of the thrust augmentation stage, and the landing structure **30** may include a plurality of pins **34** that are configured to mate with the plurality of shear cones **32**, as schematically illustrated in FIG. 1. Other mating structures also are within the scope of the present disclosure and may be incorporated into landing structures **30** and thrust augmentation stages **18**.

In some embodiments, the thrust augmentation stage **18** may include a body **36** that defines a central bore **38**, with the first stage **20** extending through the central bore when the thrust augmentation stage and the first stage are operatively coupled together for launch to define a launch vehicle **12**, as schematically illustrated in FIG. 1. In some such embodiments, the central bore **38** may be coaxial with the longitudinal axis of the launch vehicle **12**. Additionally or alternatively, the launch vehicle **12**, the thrust augmentation stage **18**, and the first stage **20** may share a longitudinal axis **31**, at least when the thrust augmentation stage and the first stage are operatively coupled together. Stated differently, the longitudinal axis of the thrust augmentation stage may be coaxial with the longitudinal axis of the first stage when the thrust augmentation stage and the first stage are operatively coupled together for launch of the launch vehicle and during the initial portion of a launch trajectory.

In some embodiments, the central bore **38** may extend completely through the thrust augmentation stage **18**, as schematically represented in FIG. 1. Accordingly, when the first stage **20** is operatively coupled to the thrust augmentation stage **18**, the first stage **20** may extend through, and, in some embodiments, completely through, the central bore **38** of the thrust augmentation stage **18**. Additionally or alternatively, the first stage **20** may be accessible via the central bore from the aft side of the thrust augmentation stage.

In some embodiments, and as schematically represented in FIG. 1, the thrust augmentation stage and the first stage may collectively define a guide track **40** at an interface between the thrust augmentation stage **18** and the first stage **20** when they are operatively coupled together. When present, the guide track **40** may be configured to operatively constrain movement of the first stage **20** relative to the thrust augmentation stage **18** to longitudinal translation when the first stage is being coupled to and decoupled from the thrust augmentation stage. In other words, the guide track **40** may restrict relative rotational movement between the thrust augmentation stage and the first stage and may provide for

5

a guided longitudinal coupling of the first stage to the thrust augmentation stage when they are being coupled together and for a guided longitudinal uncoupling of the first stage from the thrust augmentation stage when they are being decoupled.

Various configurations of optional guide tracks **40** are within the scope of the present disclosure. As an illustrative, non-exclusive example, a guide track may include a plurality of channels **42** and a plurality of corresponding rails **44** that are configured to longitudinally translate within the plurality of channels. For example, the thrust augmentation stage may include or define a plurality of channels, and the first stage may include or define a plurality of rails corresponding to the plurality of channels. Additionally or alternatively, the thrust augmentation stage may include or define a plurality of channels corresponding to the plurality of rails. In some embodiments, the optional rails may include rollers **46** configured to longitudinally roll within corresponding channels. In some such embodiments, the rollers may be spring biased toward the corresponding channels, for example, to facilitate desired tolerances of fit between the thrust augmentation stage and the first stage when they are coupled together, as well as when they are being coupled together and when they are being decoupled from each other. As illustrative, non-exclusive examples, a guide track **40** may include three, four, or more than four sets of channels **42** and corresponding rails **44**.

Additionally or alternatively, as also schematically represented in FIG. 1, the launch vehicle **12** may include a coupling mechanism **48** that is configured to selectively and operatively couple together the thrust augmentation stage **18** and the first stage **20** for launch of the launch vehicle and to selectively and operatively decouple the thrust augmentation stage from the first stage during launch. In some embodiments, although not required, the coupling mechanism **48** may be associated with the guide track **40**. Illustrative, non-exclusive examples of coupling mechanisms **48** may include explosive bolts and/or separation nuts. The coupling mechanism **48** also may include a latch mechanism operable to prevent longitudinal movement of the first stage relative to the thrust augmentation stage when the first stage is operatively coupled to the thrust augmentation stage.

In some embodiments, the thrust augmentation stage **18** may include interface heat shielding structure **50** at the interface between the thrust augmentation stage and the first stage **20** when they are operatively coupled together. When present, this interface heat shielding structure **50** is configured to protect the thrust augmentation stage from heat generated by the first stage to which the thrust augmentation stage may be exposed during separation of the thrust augmentation stage and the first stage and/or during a launch. In embodiments in which the thrust augmentation stage defines a central bore **38**, interface heat shielding structure **50** may line the central bore. In some such embodiments, the interface heat shielding structure may completely line or may substantially line the central bore. Illustrative, non-exclusive examples of interface heat shielding structure **50** of a thrust augmentation stage **18** include (but are not limited to) high-temperature reusable surface insulation, fibrous refractory composite insulation, toughened unipiece fibrous insulation, low-temperature reusable surface insulation, flexible insulation blankets, advanced flexible reusable insulation, reinforced carbon-carbon, and/or flame-resistant meta-aramid material.

In some embodiments, the thrust augmentation stage **18** additionally or alternatively may include aft heat shielding

6

structure **52**. The aft heat shielding structure **52** may be arranged at an aft portion of the thrust augmentation stage **18**. When present, the aft heat shielding structure **52** may be configured to protect the thrust augmentation stage from heat generated by the thrust augmentation stage, such as associated with one or more combustion based engines of the thrust augmentation stage. Additionally or alternatively, the aft heat shielding structure **52** may be configured to protect the thrust augmentation stage from heat generated by the first stage, such as associated with one or more combustion based engines of the first stage, for example, when the thrust augmentation stage and the first stage are coupled together during the initial portion of a launch trajectory. Similar to interface heat shielding structure **50**, the aft heat shielding structure **52** may include (but is not limited to) high-temperature reusable surface insulation, fibrous refractory composite insulation, toughened unipiece fibrous insulation, low-temperature reusable surface insulation, flexible insulation blankets, advanced flexible reusable insulation, reinforced carbon-carbon, flame-resistant meta-aramid material, or combinations thereof.

In embodiments that include both interface heat shielding structure **50** and aft heat shielding structure **52**, the aft heat shielding structure **52** may be more robust than the interface heat shielding structure **50**. Additionally or alternatively, the aft heat shielding structure **52** may be configured to withstand elevated temperatures for a longer period of time than the interface heat shielding structure **50**. For example, during the initial portion of a launch trajectory, the aft heat shielding structure **52** may be exposed to significant elevated temperatures from the thrust augmentation stage and first stage combustion based engines, while the interface heat shielding structure **50** may be exposed to significant elevated temperatures for a short duration, for example, only during operative separation of the first stage from the thrust augmentation stage following the initial portion of the launch trajectory.

As schematically represented in FIG. 1, a thrust augmentation stage **18** of a launch vehicle **12** may include one or more engines **54** that are configured to selectively provide thrust for at least the initial portion **21** of a launch trajectory **24** and optionally also during a controlled descent **29** and landing of the thrust augmentation stage. Any suitable number of engines **54** may be provided depending on the overall desired configuration of a system **10**. As illustrative, non-exclusive examples, a thrust augmentation stage **18** may include six or more engines evenly spaced around the aft end of the thrust augmentation stage.

As also schematically represented in FIG. 1, a first stage **20** of a launch vehicle **12** may include one or more engines **56** that are configured to provide thrust during both the initial portion **21** and the second portion **26** of the launch trajectory. Any suitable configuration of engines **54** and engines **56** may be utilized, including (but not limited to) combustion based engines. As illustrative, non-exclusive examples, engines **54** and engines **56** may be powered by a liquid fuel.

In some embodiments, the thrust augmentation stage **18** may include a liquid fuel tank **58** for holding a volume of liquid fuel **60**, as schematically represented in FIG. 1, with the liquid fuel tank being operatively coupled to the engine(s) **54**. Illustrative, non-exclusive examples of suitable liquid fuels include Rocket Propellant-1 (RP-1, kerosene), liquid hydrogen, liquid methane, and mono-methyl hydrazine; however, any suitable fuel may be used. Additionally, as also schematically and optionally represented in FIG. 1, the thrust augmentation stage also may include a

liquid oxygen tank **62** for holding a volume of liquid oxygen **64**, with the liquid oxygen tank also being operatively coupled to the engine(s) **54**. Additionally or alternatively, in examples of engines that utilize mono-methyl hydrazine as a liquid fuel, tank **62** may hold a volume of nitrogen tetroxide. An illustrative, non-exclusive example of a suitable engine **54** includes (but is not limited to) the RS-27A engine used on first stage Delta II rockets.

In systems **10** that include a thrust augmentation stage **18** that is configured to be retrieved and reused following a launch, such a system **10** also may include a control system **66** that is configured, or programmed, to control a controlled descent **29** of the thrust augmentation stage to Earth following the initial portion **21** of the launch trajectory **24**. In some such embodiments, the control system **66** may be configured to automatically control the controlled descent. By automatically control the controlled descent, it is meant that the control system may be programmed to automatically control the controlled descent without active and/or real-time input from a user, such as from a user that pilots, or otherwise actively steers, directs, and/or controls the controlled descent via real-time human input. Additionally or alternatively, the control system may be configured to actively control the controlled descent **29**. By actively control the controlled descent, it is meant that the control system may be configured to react to the various conditions sensed and/or detected by the control system and actively account for such various conditions with instructions sent to the thrust augmentation stage for controlling the controlled descent, whether such instructions are or are not the direct result of real-time human input.

In some embodiments, the optional control system **66** may include a land-based communication device **68** and a thrust augmentation stage communication device **70**. The thrust augmentation stage communication device **70** may be located onboard the thrust augmentation stage **18**. The land-based communication device **68** may be configured to selectively and/or wirelessly send operational instructions to the thrust augmentation stage communication device **70** to control the controlled descent of the thrust augmentation stage.

In some embodiments, the control system may include one or more sensors **72** that are configured to sense conditions associated with the thrust augmentation stage during a controlled descent of the thrust augmentation stage and to utilize the sensed conditions to control the controlled descent. The one or more sensors **72** may be located onboard the thrust augmentation stage **18** and may be configured to sense such illustrative, non-exclusive conditions as environmental conditions such as wind speed, as well as positional conditions such as velocity, acceleration, and location such as that may be sensed with a global positioning satellite (GPS) system. The control system may utilize such information to facilitate a controlled descent of the thrust augmentation stage.

Additionally or alternatively, the control system may include one or more detectors **74** that are configured to detect a current location of the thrust augmentation stage during a controlled descent and to utilize the detected location to control the controlled descent. For example, such detectors **74** may be land-based and include such systems as radar systems.

Collectively, one or more of the thrust augmentation stage communication device **70**, the land-based communication device **68**, the sensors **72**, and the detectors **74** may be described as an avionics system **71** of the control system **66**. Control systems **66** also may include one or more force

control mechanisms, or systems, **75** that operatively provide controlling forces to the thrust augmentation stage during its controlled descent. For example, the engines **54** of the thrust augmentation stage may be gimbaled and controlled to effectuate changes in the thrust vector associated with the engines during a controlled descent, with this schematically represented in FIG. **1** with the force control mechanism **75** illustrated in an overlapping relationship with an engine **54**. Additionally or alternatively, a force control mechanism **75** may include one or more aerodynamic flaps that are operatively controlled to apply aerodynamic moments on the thrust augmentation stage. Additionally or alternatively, a force control mechanism **75** may include one or more auxiliary engines that are separate and apart from the primary thrust engines **54** and that may be controlled to facilitate the controlled descent of the thrust augmentation stage. Other configurations and implementation of force control mechanisms **75** also are within the scope of the present disclosure.

In some embodiments, the control system may be configured to control the controlled descent **29** of the thrust augmentation stage to Earth following the initial portion **21** of the launch trajectory **24** to within a threshold distance from a position from which the launch vehicle is launched. Illustrative, non-exclusive examples of such a threshold include distances of 1000, 500, 100, 10, and 1 meters. In other words, following the initial portion of a launch trajectory, the thrust augmentation stage may be controlled to return to the location from which it was initially launched with the first stage as part of the launch vehicle. In such systems **10**, the thrust augmentation stage may be described as a short-range thrust augmentation stage, because the thrust augmentation stage returns to Earth at least within the vicinity of the position from which the launch vehicle was launched, as opposed to a long-range system with an augmentation stage returning to Earth a significant distance from the position from which the launch vehicle was launched and thus requiring transportation of the augmentation stage over a significant distance.

In some such systems **10**, a system may be described as including a launch facility **76**, from which the launch vehicle is launched, and the control system **66** may be configured to control the controlled descent **29** of the thrust augmentation stage to the launch facility following the initial portion **21** of the launch trajectory **24**. For example, the launch facility may include a launch pad **78**, from which the launch vehicle is launched, and optional landing structure **30** may be within a threshold distance of the launch pad. Illustrative, non-exclusive examples of such a threshold include distances of 1000, 500, 100, 10, and 1 meters. Additionally or alternatively, the control system may be configured to control the controlled descent of the thrust augmentation stage directly to the launch pad itself. Additionally or alternatively, in some embodiments, the optional landing structure **30** may be placed a distance away from the launch pad, such as within one of the aforementioned threshold distances, for mating with the thrust augmentation stage when landing, and then following the landing, the landing structure optionally may be used to support the thrust augmentation stage for transportation back to the launch pad for use with a subsequent launch of a launch vehicle.

FIG. **3** schematically provides a flowchart that represents illustrative, non-exclusive examples of methods **200** for launching space vehicles into outer space. Methods **200** may correspond with one or more examples of systems **10** according to the present disclosure. Accordingly, the following discussion makes reference to the various discussed,

including optional, components of systems **10**; however, not all systems **10** necessarily correspond to a method **200**, and methods **200** as discussed herein do not limit systems **10** to the discussed methods and associated steps.

With reference also to FIG. 2, methods **200** include powering a thrust augmentation stage **18** of a launch vehicle **12** during at least an initial portion **21** of a launch trajectory **24** to provide thrust to the launch vehicle, as schematically indicated at **202** in FIG. 3. Methods **200** also include, following the initial portion of the launch trajectory, separating a first stage **20** from the thrust augmentation stage **18**, as schematically indicated at **204**. Methods **200** also include powering the first stage **20** of the launch vehicle during the initial portion **21** and a second portion **26** of the launch trajectory to provide thrust to the launch vehicle, as schematically indicated at **206** in FIG. 3.

As schematically indicated at **208** in FIG. 3, methods **200** also include separating the space vehicle **14** from the launch vehicle **12** and placing the space vehicle **14** into outer space. Depending on the number of stages **16** that a launch vehicle includes, the space vehicle may be separated from the first stage **20** or from a second or subsequent stage.

Methods **200** also include controlling a controlled descent **29** of the thrust augmentation stage **18** to Earth **28** following the initial portion **21** of the launch trajectory **24**, as schematically indicated at **210** in FIG. 3.

Methods **200** also include retrieving and reusing the thrust augmentation stage **18** with a distinct first stage **20** to define a distinct launch vehicle **12** for subsequent launch of a distinct space vehicle **14** into outer space, as schematically indicated at **212** in FIG. 3. Further optional steps may include recharging or refueling the thrust augmentation stage **18** for use with another launch vehicle.

Turning now to FIGS. 4-8, illustrative non-exclusive examples of component parts of a system **10** are illustrated. Where appropriate, the reference numerals from the schematic illustrations of FIGS. 1-2 are used to designate corresponding parts of the examples; however, the examples of FIGS. 4-8 are non-exclusive and do not limit systems **10** to the illustrated embodiments of FIGS. 4-8. That is, systems **10** are not limited to the specific embodiments of FIGS. 4-8, and systems **10** may incorporate any number of the various aspects, configurations, characteristics, properties, etc. of systems **10** that are illustrated in and discussed with reference to the schematic representations of FIGS. 1-2 and/or the embodiments of FIGS. 4-8, as well as variations thereof, without requiring the inclusion of all such aspects, configurations, characteristics, properties, etc. For the purpose of brevity, each previously discussed component, part, portion, aspect, region, etc. or variants thereof may not be discussed, illustrated, and/or labeled again with respect to the examples of FIGS. 4-8; however, it is within the scope of the present disclosure that the previously discussed features, variants, etc. may be utilized with these examples.

FIGS. 4-7 illustrate an example launch vehicle **12**, indicated generally at **112**. As illustrated, launch vehicle **112** is an example of a launch vehicle that includes four stages **16**, including a thrust augmentation stage **18**, a first stage **20**, a second stage **22**, and a third stage **23** that supports a space vehicle **14**. The thrust augmentation stage of launch vehicle **112** is identified herein as thrust augmentation stage **118**. The first stage, the second stage, and the third stage of launch vehicle **112** are identified herein as the main, or primary, stages **116**.

The thrust augmentation stage **118** of launch vehicle **112** is an example of a thrust augmentation stage **18** that defines a central bore **38**, with the first stage **20** extending through

the central bore when the thrust augmentation stage and the first stage are operatively coupled together for launch, as illustrated in FIG. 4. The thrust augmentation stage **118** may include a body **36** which may be aerodynamically shaped to reduce drag during launch and/or the initial portion of the launch trajectory. The body **36** may include a first portion **37** which may define a first fuel tank (e.g., a liquid fuel tank **58** which may contain a liquid fuel **60**, such as RP-1) and a second portion **39** which may define a second fuel tank (e.g., a liquid oxygen tank **62**, which may contain liquid oxygen **64**).

Moreover, launch vehicle **112** is an example of a launch vehicle in which the thrust augmentation stage and the first stage collectively define a guide track **40** at an interface between the thrust augmentation stage and first stage. In the illustrated example, the thrust augmentation stage **118** includes three channels **42**, as seen in FIG. 5, and the first stage includes three corresponding rails **44**, as seen in FIG. 6.

The thrust augmentation stage **118** of launch vehicle **112** also is an example of a thrust augmentation stage that includes a plurality of shear cones **32** positioned at the aft of the thrust augmentation stage, as illustrated in FIG. 7. More specifically, the example thrust augmentation stage includes six shear cones evenly spaced about the aft of the thrust augmentation stage interspaced with six engines **54**. FIG. 8 illustrates an illustrative, non-exclusive example of corresponding landing structure **30** that is configured to mate with the shear cones of the thrust augmentation stage following a launch of the launch vehicle **112**. The example landing structure, identified as landing structure **130**, includes six pins **34** that are positioned and sized to mate with the shear cones. Accordingly, a control system **66** of a system **10** may control a controlled descent of the thrust augmentation stage **118** so that it lands on and mates with the example landing structure **130**.

Illustrative, non-exclusive examples of inventive subject matter according to the present disclosure are described in the following enumerated paragraphs:

A. A multi-stage space launch system for launching a space vehicle into outer space, the system comprising:

a launch vehicle configured to operatively support a space vehicle for placement in outer space, wherein the launch vehicle includes at least two stages including:

- a thrust augmentation stage configured to provide thrust for an initial portion of a launch trajectory; and
- a first stage configured to be selectively coupled to and decoupled from the thrust augmentation stage and further configured to provide thrust during the initial portion and during a second portion of the launch trajectory following the initial portion of the launch trajectory.

A1. The system of paragraph A, wherein the thrust augmentation stage is configured to be selectively decoupled from the first stage during the launch trajectory and subsequently to be retrieved and reused following a launch of the launch vehicle.

A2. The system of any of paragraphs A-A1, wherein the thrust augmentation stage is configured to be selectively decoupled from the first stage during the launch trajectory.

A2.1. The system of paragraph A2, wherein the thrust augmentation stage is further configured to be subsequently retrieved and reused with a distinct first stage to define a distinct launch vehicle for a subsequent launch of a distinct space vehicle into outer space.

11

A2.2. The system of any of paragraphs A2-A2.1, wherein the thrust augmentation stage is further configured for controlled landing following separation from the first stage.

A3. The system of any of paragraphs A-A2.2, wherein the thrust augmentation stage is configured to land on Earth following a launch, optionally without significant damage to the thrust augmentation stage.

A4. The system of any of paragraphs A-A3, wherein the thrust augmentation stage is configured to land on Earth with the same orientation as was launched, optionally vertically, following a launch.

A5. The system of any of paragraphs A-A4, wherein the thrust augmentation stage is configured to utilize the same source of thrust that is used during the initial portion of the launch trajectory to return to and land on Earth.

A6. The system of any of paragraphs A1-A5, further comprising:

a land-based landing structure configured to selectively mate with the thrust augmentation stage following a launch when the thrust augmentation stage returns to Earth;

wherein the thrust augmentation stage is configured to mate with the landing structure following a launch when the thrust augmentation stage returns to Earth.

A6.1. The system of paragraph A6,

wherein the thrust augmentation stage includes a plurality of shear cones positioned at an aft portion of the thrust augmentation stage; and

wherein the landing structure includes a plurality of pins configured to mate with the plurality of shear cones.

A7. The system of any of paragraphs A-A6.1, wherein the thrust augmentation stage includes a body that defines a central bore, and wherein the first stage extends through the central bore for launch.

A7.1. The system of paragraph A7, wherein the launch vehicle has a longitudinal axis, and wherein the central bore is coaxial with the longitudinal axis.

A7.2. The system of any of paragraphs A7-A7.1, wherein the central bore extends completely through the thrust augmentation stage.

A8. The system of any of paragraphs A-A7.2, wherein the thrust augmentation stage and the first stage collectively define a guide track at an interface between the thrust augmentation stage and the first stage when the thrust augmentation stage and the first stage are operatively coupled together, wherein the guide track is configured to operatively constrain longitudinal translation of the first stage relative to the thrust augmentation stage when the first stage is being decoupled from the thrust augmentation stage during launch.

A8.1. The system of paragraph A8, wherein the guide track includes at least one channel and at least one rail configured to longitudinally translate within the at least one channel.

A8.1.1. The system of paragraph A8.1, wherein one of the thrust augmentation stage and the first stage includes the at least one channel and the other of the thrust augmentation stage and the first stage includes the at least one rail.

A8.1.2. The system of any of paragraphs A8.1-A8.1.1, wherein the rail includes rollers configured to longitudinally roll within the at least one channel.

A8.1.2.1. The system of paragraph A8.1.2, wherein the rollers are spring biased toward the at least one channel.

A9. The system of any of paragraphs A-A8.1.2.1,

wherein the launch vehicle includes a coupling mechanism configured to selectively and operatively couple together the thrust augmentation stage and the first stage for launch of the launch vehicle, wherein the coupling mecha-

12

nism is further configured to selectively and operatively decouple the thrust augmentation stage from the first stage during the launch trajectory.

A9.1. The system of paragraph A9, wherein the coupling mechanism includes explosive bolts.

A9.2. The system of any of paragraphs A9-A9.1, wherein the coupling mechanism includes separation nuts.

A10. The system of any of paragraphs A-A9.2, wherein the thrust augmentation stage includes interface heat shielding structure at an interface between the thrust augmentation stage and the first stage, wherein the interface heat shielding structure is configured to protect the thrust augmentation stage from heat associated with the first stage during separation of the thrust augmentation stage and the first stage during launch of the launch vehicle.

A10.1 The system of paragraph A10, wherein the interface heat shielding structure includes one or more of high-temperature reusable surface insulation, fibrous refractory composite insulation, toughened unipiece fibrous insulation, low-temperature reusable surface insulation, flexible insulation blankets, advanced flexible reusable insulation, reinforced carbon-carbon, and flame-resistant meta-aramid material.

A11. The system of any of paragraphs A-A10.1, wherein the thrust augmentation stage includes aft heat shielding structure at the aft of the thrust augmentation stage, wherein the aft heat shielding structure is configured to protect the thrust augmentation stage from heat generated by the thrust augmentation stage and from heat generated by the first stage during launch of the launch vehicle.

A11.1. The system of paragraph A11 when depending from paragraph A10, wherein the aft heat shielding structure is more robust than the interface heat shielding structure.

A11.2. The system of any of paragraphs A11-A11.1 when depending from paragraph A10, wherein the aft heat shielding structure is configured to withstand elevated temperatures for a longer period of time than the interface heat shielding structure.

A12. The system of any of paragraphs A-A11.2, wherein the thrust augmentation stage is configured to be powered by a liquid fuel.

A13. The system of any of paragraphs A-A12, wherein the thrust augmentation stage includes a liquid fuel tank, optionally further comprising liquid fuel in the liquid fuel tank, optionally wherein the liquid fuel includes Rocket Propellant-1 (RP-1).

A14. The system of any of paragraphs A-A13, wherein the thrust augmentation stage includes a liquid oxygen tank, optionally further comprising liquid oxygen in the liquid oxygen tank.

A15. The system of any of paragraphs A-A14, wherein the thrust augmentation stage includes one or more engines configured to be powered by a liquid fuel and to provide thrust for launching the space vehicle during at least the initial portion of the launch trajectory, and optionally during a controlled descent of the thrust augmentation stage to Earth following the initial portion of the launch trajectory.

A16. The system of any of paragraphs A-A15, further comprising:

a control system configured, or programmed, to control a controlled descent of the thrust augmentation stage to Earth following the initial portion of the launch trajectory.

A16.1. The system of paragraph A16, wherein the control system is configured to automatically control the controlled descent.

A16.2. The system of any of paragraphs A16-A16.1, wherein the control system is configured to actively control the controlled descent.

A16.3. The system of any of paragraphs A16-A16.2, wherein control system includes a land-based communication device and a thrust augmentation stage communication device, and wherein the land-based communication device is configured to selectively send operational instructions to the thrust augmentation stage communication device to control the controlled descent of the thrust augmentation stage.

A16.4. The system of any of paragraphs A16-A16.3, wherein the control system includes one or more sensors configured to sense environmental conditions associated with the thrust augmentation stage during the controlled descent, and wherein the control system is configured to utilize the environmental conditions to control the controlled descent.

A16.5. The system of any of paragraphs A16-A16.4, wherein the control system includes one or more detectors configured to actively detect a detected location of the thrust augmentation stage during the controlled descent, and wherein the control system is configured to utilize the detected location of the thrust augmentation stage to control the controlled descent.

A16.6. The system of any of paragraphs A16-A16.5, further comprising:

a launch facility, from which the launch vehicle is configured to launch;

wherein the control system is configured to control the controlled descent of the thrust augmentation stage to the launch facility following the initial portion of the launch trajectory.

A16.6.1. The system of paragraph A16.6 when depending from paragraph A6, wherein the launch facility includes a launch pad, from which the launch vehicle is configured to launch, and wherein the landing structure is within 1000 meters, 500 meters, 100 meters, 10 meters, or 1 meter of the launch pad, optionally wherein the launch pad includes the landing structure.

A16.7. The system of any of paragraphs A16-A16.6.1, wherein the control system is configured to control the controlled descent of the thrust augmentation stage to Earth following the initial portion of the launch trajectory to within 1000 meters, 500 meters, 100 meters, 10 meters, or 1 meter from a position from which the launch vehicle is launched.

A17. The system of any of paragraphs A-A16.7, wherein the first stage is configured to be used only once as a component of a launch vehicle;

wherein the first stage is not configured to be reused following a launch of the launch vehicle; and/or

wherein the first stage is configured to not be reused following a launch of the launch vehicle.

A18. The system of any of paragraphs A-A17, further comprising the space vehicle, wherein the space vehicle is supported by the launch vehicle.

A19. The system of any of paragraphs A-A18, wherein the first stage is decoupled from the thrust augmentation stage, wherein the first stage is along the second portion of the launch trajectory, and wherein the thrust augmentation stage is being controlled in a controlled descent to Earth.

A20. The use the system of any of paragraphs A-A19 to place a space vehicle into outer space.

B. A method of launching a space vehicle into outer space, the method comprising:

powering a thrust augmentation stage of a launch vehicle during an initial portion of a launch trajectory to provide thrust to the launch vehicle;

following the initial portion of the launch trajectory, separating a first stage of the launch vehicle from the thrust augmentation stage;

powering the first stage of the launch vehicle during the initial portion and during a second portion of the launch trajectory following the initial portion of the launch trajectory to provide thrust to the launch vehicle; and

controlling a controlled descent of the thrust augmentation stage to Earth following separation of the thrust augmentation stage from the first stage.

B1. The method of paragraph B, further comprising:

separating the space vehicle from the launch vehicle and placing the space vehicle into outer space;

B2. The method of any of paragraphs B-B1, further comprising:

retrieving and reusing the thrust augmentation stage with a distinct first stage to define a distinct launch vehicle for a subsequent launch of a distinct space vehicle into outer space.

B3. The method of any of paragraphs B-B2, wherein the first stage provides thrust to the launch vehicle during the separating.

B3.1. The method of paragraph B3, wherein exhaust from the first stage directly engages the thrust augmentation stage during the separating.

B4. The method of any of paragraphs B-B3.1, wherein the thrust augmentation stage and the first stage of the launch vehicle are lit on the ground and both provide thrust for initial launch of the launch vehicle.

B5. The method of any of paragraphs B-B4, utilizing the system of any of paragraphs A-A19.

As used herein, the terms “selective” and “selectively,” when modifying an action, movement, configuration, or other activity of one or more components or characteristics of an apparatus, mean that the specific action, movement, configuration, or other activity is intended and/or is a direct or indirect result of user manipulation of an aspect of, or one or more components of, the apparatus.

As used herein, the terms “adapted” and “configured” mean that the element, component, or other subject matter is designed and/or intended to perform a given function. Thus, the use of the terms “adapted” and “configured” should not be construed to mean that a given element, component, or other subject matter is simply “capable of” performing a given function but that the element, component, and/or other subject matter is specifically selected, created, implemented, utilized, programmed, and/or designed for the purpose of performing the function. It is also within the scope of the present disclosure that elements, components, and/or other recited subject matter that is recited as being adapted to perform a particular function may additionally or alternatively be described as being configured to perform that function, and vice versa. Similarly, subject matter that is recited as being configured to perform a particular function may additionally or alternatively be described as being operative to perform that function.

The various disclosed elements of apparatuses and steps of methods disclosed herein are not required to all apparatuses and methods according to the present disclosure, and the present disclosure includes all novel and non-obvious combinations and subcombinations of the various elements and steps disclosed herein. Moreover, one or more of the various elements and steps disclosed herein may define independent inventive subject matter that is separate and

15

apart from the whole of a disclosed apparatus or method. Accordingly, such inventive subject matter is not required to be associated with the specific apparatuses and methods that are expressly disclosed herein, and such inventive subject matter may find utility in apparatuses and/or methods that are not expressly disclosed herein.

The invention claimed is:

1. A multi-stage space launch system for launching a space vehicle into outer space, the multi-stage space launch system comprising:

a launch vehicle configured to operatively support a space vehicle for placement in outer space, wherein the launch vehicle includes at least two stages including:
a thrust augmentation stage configured to provide thrust for an initial portion of a launch trajectory, wherein the thrust augmentation stage includes a plurality of shear cones positioned at an aft portion of the thrust augmentation stage; and

a first stage configured to be selectively coupled to and decoupled from the thrust augmentation stage and further configured to provide thrust during the initial portion and during a second portion of the launch trajectory following the initial portion of the launch trajectory; and

a land-based landing structure configured to selectively mate with the thrust augmentation stage following a launch when the thrust augmentation stage returns to Earth, wherein the land-based landing structure includes a plurality of pins configured to mate with the plurality of shear cones;

wherein the thrust augmentation stage is configured to be selectively decoupled from the first stage during the launch trajectory and further configured for controlled landing following separation from the first stage; and wherein the thrust augmentation stage is configured to mate with the land-based landing structure following the launch when the thrust augmentation stage returns to Earth.

2. The multi-stage space launch system of claim 1, wherein the launch vehicle is configured to launch vertically, and wherein the thrust augmentation stage is configured to land vertically on Earth following separation from the first stage.

3. The multi-stage space launch system of claim 1, wherein the thrust augmentation stage is configured to utilize the same source of thrust that is used during the initial portion of the launch trajectory to return to and land on Earth.

4. The multi-stage space launch system of claim 1, wherein the thrust augmentation stage includes a body that defines a central bore, and wherein the first stage extends through the central bore for launch of the launch vehicle.

5. The multi-stage space launch system of claim 4, wherein the launch vehicle has a longitudinal axis, and wherein the central bore is coaxial with the longitudinal axis.

6. The multi-stage space launch system of claim 4, wherein the central bore extends completely through the thrust augmentation stage.

7. The multi-stage space launch system of claim 4, wherein the thrust augmentation stage and the first stage collectively define a guide track at an interface between the thrust augmentation stage and the first stage when the thrust augmentation stage and the first stage are operatively coupled together, wherein the guide track is configured to operatively constrain longitudinal translation of the first

16

stage relative to the thrust augmentation stage when the first stage is being decoupled from the thrust augmentation stage during launch.

8. The multi-stage space launch system of claim 7, wherein the guide track includes at least one channel and at least one rail configured to longitudinally translate within the at least one channel.

9. The multi-stage space launch system of claim 8, wherein the at least one rail includes rollers configured to longitudinally roll within the at least one channel, and wherein the rollers are spring biased toward the at least one channel.

10. The multi-stage space launch system of claim 4, wherein the thrust augmentation stage includes interface heat shielding structure at an interface between the thrust augmentation stage and the first stage, wherein the interface heat shielding structure is configured to protect the thrust augmentation stage from heat associated with the first stage during separation of the thrust augmentation stage and the first stage during launch of the launch vehicle;

wherein the thrust augmentation stage further includes aft heat shielding structure at the aft portion of the thrust augmentation stage, wherein the aft heat shielding structure is configured to protect the thrust augmentation stage at least from heat generated by the thrust augmentation stage during launch of the launch vehicle; and

wherein the aft heat shielding structure is configured to withstand elevated temperatures for a longer period of time than the interface heat shielding structure.

11. The multi-stage space launch system of claim 1, wherein the launch vehicle includes a coupling mechanism configured to selectively and operatively couple together the thrust augmentation stage and the first stage for launch of the launch vehicle, wherein the coupling mechanism is further configured to selectively and operatively decouple the thrust augmentation stage from the first stage during the launch trajectory, and wherein the coupling mechanism includes at least one of explosive bolts and separation nuts.

12. The multi-stage space launch system of claim 1, wherein the thrust augmentation stage is configured to be powered by a liquid fuel.

13. The multi-stage space launch system of claim 1, further comprising:

a control system configured to actively control a controlled descent of the thrust augmentation stage to land vertically on Earth following the initial portion of the launch trajectory.

14. The multi-stage space launch system of claim 13, further comprising:

a launch facility, from which the launch vehicle is configured to launch;

wherein the control system is configured to control the controlled descent of the thrust augmentation stage to the launch facility following the initial portion of the launch trajectory.

15. The multi-stage space launch system of claim 13, wherein the control system is configured to control the controlled descent of the thrust augmentation stage to Earth following the initial portion of the launch trajectory to within 1000 meters from a position from which the launch vehicle was launched.

16. The multi-stage space launch system of claim 1, further comprising:

17

a control system configured to automatically control a controlled descent of the thrust augmentation stage to land vertically on Earth following the initial portion of the launch trajectory.

17. A method of launching a space vehicle into outer space, the method comprising:

providing the multi-stage space launch system of claim 1; powering the thrust augmentation stage of the launch vehicle during the initial portion of the launch trajectory to provide thrust to the launch vehicle;

following the initial portion of the launch trajectory, separating the first stage of the launch vehicle from the thrust augmentation stage;

powering the first stage of the launch vehicle during the initial portion and the second portion of the launch trajectory following the initial portion of the launch trajectory to provide thrust to the launch vehicle; and controlling a controlled descent of the thrust augmentation stage to Earth following separation of the thrust augmentation stage from the first stage.

18. The method of claim 17, further comprising:

retrieving and reusing the thrust augmentation stage with a distinct first stage to define a distinct launch vehicle for a subsequent launch of a distinct space vehicle into outer space.

19. A multi-stage space launch system for launching a space vehicle into outer space, the multi-stage space launch system comprising:

a launch vehicle configured to operatively support a space vehicle for placement in outer space, wherein the launch vehicle includes at least two stages including: a thrust augmentation stage configured to provide thrust for an initial portion of a launch trajectory, wherein the thrust augmentation stage includes a body that defines a central bore; and

a first stage configured to be selectively coupled to and decoupled from the thrust augmentation stage and further configured to provide thrust during the initial portion and during a second portion of the launch trajectory following the initial portion of the launch trajectory, wherein the first stage extends through the central bore for launch of the launch vehicle;

wherein the thrust augmentation stage is configured to be selectively decoupled from the first stage during the launch trajectory and further configured for controlled landing following separation from the first stage; and wherein the thrust augmentation stage and the first stage collectively define a guide track at an interface between the thrust augmentation stage and the first stage when the thrust augmentation stage and the first stage are operatively coupled together, wherein the guide track is configured to operatively constrain longitudinal translation of the first stage relative to the thrust augmentation stage when the first stage is being decoupled from the thrust augmentation stage during launch.

20. The multi-stage space launch system of claim 19, wherein the launch vehicle is configured to launch vertically, and wherein the thrust augmentation stage is configured to land vertically on Earth following separation from the first stage.

21. The multi-stage space launch system of claim 19, wherein the thrust augmentation stage is configured to utilize the same source of thrust that is used during the initial portion of the launch trajectory to return to and land on Earth.

22. The multi-stage space launch system of claim 19, further comprising:

18

a land-based landing structure configured to selectively mate with the thrust augmentation stage following the launch when the thrust augmentation stage returns to Earth;

wherein the thrust augmentation stage is configured to mate with the land-based landing structure following the launch when the thrust augmentation stage returns to Earth.

23. The multi-stage space launch system of claim 22, wherein the thrust augmentation stage includes a plurality of shear cones positioned at an aft portion of the thrust augmentation stage; and

wherein the land-based landing structure includes a plurality of pins configured to mate with the plurality of shear cones.

24. The multi-stage space launch system of claim 19, wherein the launch vehicle has a longitudinal axis, and wherein the central bore is coaxial with the longitudinal axis.

25. The multi-stage space launch system of claim 19, wherein the central bore extends completely through the thrust augmentation stage.

26. The multi-stage space launch system of claim 19, wherein the guide track includes at least one channel and at least one rail configured to longitudinally translate within the at least one channel.

27. The multi-stage space launch system of claim 26, wherein the at least one rail includes rollers configured to longitudinally roll within the at least one channel, and wherein the rollers are spring biased toward the at least one channel.

28. The multi-stage space launch system of claim 19, wherein the thrust augmentation stage includes interface heat shielding structure at an interface between the thrust augmentation stage and the first stage, wherein the interface heat shielding structure is configured to protect the thrust augmentation stage from heat associated with the first stage during separation of the thrust augmentation stage and the first stage during launch of the launch vehicle;

wherein the thrust augmentation stage further includes aft heat shielding structure at the aft portion of the thrust augmentation stage, wherein the aft heat shielding structure is configured to protect the thrust augmentation stage at least from heat generated by the thrust augmentation stage during launch of the launch vehicle; and

wherein the aft heat shielding structure is configured to withstand elevated temperatures for a longer period of time than the interface heat shielding structure.

29. The multi-stage space launch system of claim 19, wherein the launch vehicle includes a coupling mechanism configured to selectively and operatively couple together the thrust augmentation stage and the first stage for launch of the launch vehicle, wherein the coupling mechanism is further configured to selectively and operatively decouple the thrust augmentation stage from the first stage during the launch trajectory, and wherein the coupling mechanism includes at least one of explosive bolts and separation nuts.

30. The multi-stage space launch system of claim 19, wherein the thrust augmentation stage is configured to be powered by a liquid fuel.

31. The multi-stage space launch system of claim 19, further comprising:

19

a control system configured to actively control a controlled descent of the thrust augmentation stage to land vertically on Earth following the initial portion of the launch trajectory.

32. The multi-stage space launch system of claim **31**,
further comprising:

a launch facility, from which the launch vehicle is configured to launch;

wherein the control system is configured to control the controlled descent of the thrust augmentation stage to the launch facility following the initial portion of the launch trajectory.

33. The multi-stage space launch system of claim **31**, wherein the control system is configured to control the controlled descent of the thrust augmentation stage to Earth following the initial portion of the launch trajectory to within 1000 meters from a position from which the launch vehicle was launched.

34. The multi-stage space launch system of claim **19**, further comprising:

a control system configured to automatically control a controlled descent of the thrust augmentation stage to land vertically on Earth following the initial portion of the launch trajectory.

20

35. A method of launching a space vehicle into outer space, the method comprising:

providing the multi-stage space launch system of claim **19**;

powering the thrust augmentation stage of the launch vehicle during the initial portion of the launch trajectory to provide thrust to the launch vehicle;

following the initial portion of the launch trajectory, separating the first stage of the launch vehicle from the thrust augmentation stage;

powering the first stage of the launch vehicle during the initial portion and the second portion of the launch trajectory following the initial portion of the launch trajectory to provide thrust to the launch vehicle; and controlling a controlled descent of the thrust augmentation stage to Earth following separation of the thrust augmentation stage from the first stage.

36. The method of claim **35**, further comprising:

retrieving and reusing the thrust augmentation stage with a distinct first stage to define a distinct launch vehicle for a subsequent launch of a distinct space vehicle into outer space.

* * * * *